



FLOOR PLAN  
SCALE: 1/8"=1'-0"

LEGEND

GENERAL NOTES:

1. INSULATION AND INSULATION ASSEMBLES SHALL COMPLY WITH SECTION 718, INTERNATIONAL CODE.
- A. CONCEALED INSULATION SHALL HAVE A FLAME RATING OF 25 AND A SMOKE DEVELOPED INDEX OF 450.
- B. FACING SHALL COMPLY WITH IBC 718.2.1.
2. PROVIDE 5' X 5' LANDINGS OUTSIDE EXTERIOR FLOOR. THRESHOLDS SHALL BE NOT MORE THAN 1/4" AND SHALL BE REVEALED IF MORE THAN 1/4". ALL GROUND AND FLOOR SURFACES SHALL BE NC.
3. DIMENSIONS ARE TO CENTER LINE OR FACE OF COLUMNS OR FACE OF VINYL.
4. CONTRACTOR TO VERIFY ALL SITE CONDITIONS PRIOR TO CONSTRUCTION.
5. MATERIALS SHALL BE NEW AND U.L. LISTED.
6. NO WORK SHALL BE CONCEALED UNTIL APPROVED BY INSPECTORS.
7. CONSTRUCTION SHALL COMPLY WITH ALL CITY CODES.
8. CONTRACTOR TO GUARANTEE WORK FOR ONE YEAR.
9. CONTRACTOR SHALL FURNISH WATER AND POWER SOURCES.
10. EXTERIOR CAULKING SHALL BE THIKOL CAULK.
11. PAINT GRADE TO BE SHERWIN WILLIAMS OR EQ TO RECEIVE 2 COATS.

**Plan View**

Scale: Scale to Fit



Lightolier Gulfcoast

Harahan, LA

7/5/2005

Prepared for: