



FLOOR PLAN
SCALE: 3/16"=1'-0"

LEGEND

- 2 HOUR RATED WALL WP 4230
- 1 HOUR RATED WALL WP 3514
- 1 HOUR RATED WALL WP 9021

GA FILE NO. WP 3514 **GENERIC**

ONE LAYER 5/8" TYPE X GYPSUM WALLBOARD OR GYPSUM VENEER BASE APPLIED PARALLEL OR AT RIGHT ANGLES TO EACH SIDE OF 2x4 WOOD STUDS 16" O.C. WITH 1-1/4" TYPE W DRYWALL SCREENS 12" O.C.
JOINTS STAGGERED 16" ON OPPOSITE SIDES. (LOAD BEARING)

THICKNESS: 4-3/4"
APPROX. WEIGHT: 7 PSF
FIRE TEST: SWRI 01-4511-619, 8-19-02
SEE WP 3520
SOUND TEST: (G&H NG-246FT, 7-2-05)

WINDOW SCHEDULE

MARK	SIZE	TYPE	FRAME	GLASS	LITES	ACCESS.	REMARKS
A	3/0x9/0	FIXED	WOOD	PLAIN	2/2		MAX. U-FACTOR 1 HR.
B	2/6x3/0	VERT. SLIDE	WOOD	PLAIN	2/2		MAX. U-FACTOR 1 HR.
C	3/0x3/0	HORIZ. SLIDE	WOOD	PLAIN	2/2		MAX. U-FACTOR 1 HR.

ROOM FINISH SCHEDULE

NAME	FLOOR	BASE	WALLS	CEILING	REMARKS
CLASSROOMS	CARPET	CONCRETE	CERAMIC TILE	CEILING HGT	
TOILET AREAS	CONCRETE	CONCRETE	RUBBER WALL BASE		
STORAGE	CONCRETE	CONCRETE	WOOD BASE		
ENTR/HALLWAYS	CONCRETE	CONCRETE	WOOD BASE		
CLOSETS	CONCRETE	CONCRETE	FRP PANELS		
KITCHEN	CONCRETE	CONCRETE	FRP PANELS		
GENERAL PURPOSE AREA	CONCRETE	CONCRETE	FRP PANELS		

NOTE: INTERIOR FLOOR FINISH AND FLOOR COVERING MATERIALS SHALL MEET CLASS I OR CLASS II IN ACCORDANCE WITH NFPA253.

DOOR & HARDWARE SCHEDULE

NO.	SIZE	RAISED FIN. M.S.	TYPE	FRAME	HINGE	LOCK	ACCESSORIES	RATINGS	REMARKS
1	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	KEYED HANDLE		1 HR.	DEL. USE
2	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	PUSH PULL		1 HR.	DEL. USE
3	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	PASSAGE		1 HR.	DEL. USE
4	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	PRIVACY		1 HR.	DEL. USE
5	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	DEADBOLT		1 HR.	DEL. USE
6	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	KEYED HANDLE		1 HR.	DEL. USE
7	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	PUSH PULL		1 HR.	DEL. USE
8	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	PASSAGE		1 HR.	DEL. USE
9	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	PRIVACY		1 HR.	DEL. USE
10	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	DEADBOLT		1 HR.	DEL. USE
11	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	KEYED HANDLE		1 HR.	DEL. USE
12	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	PUSH PULL		1 HR.	DEL. USE
13	2-2/0x8/0	HOLLOW METAL	ALUM.	WOOD	BUTT	PASSAGE		1 HR.	DEL. USE

NOTE: EGRESS DOORS SHALL BE READILY OPERABLE FROM THE EGRESS SIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE OR EFFORT.

FOR GENERAL NOTES
SEE DRAWING A-3

FLOOR PLAN
ALDRSGATE UNITED METHODIST
360 ROBERT BLVD.
SLIDELL, LOUISIANA

ACTIVITY CENTER
DAMMON ENGINEERING, INC.
1095 FLORIDA AVENUE 985-649-5832 SLIDELL, LA. 70458
DAMMONENGINEERING.COM

SCALEAS NOTED
FILE:
JOB NO. 1849
DATE: 5-23-07

SHEET
A-1
OF