


MAP SHOWING SURVEY OF
LOT 55, TREASURE ISLE

LOCATED IN SECTION 37, TOWNSHIP 10 SOUTH – RANGE 14 EAST,
GREENSBURG LAND DISTRICT, ST. TAMMANY PARISH, LOUISIANA,
FOR
MICHAEL DIVINCENTI



GENERAL NOTES:

1. PROPERTY RESTRICTIONS, SERVITUDES, RIGHTS-OF-WAY, EASEMENTS, IMPROVEMENTS AND/OR OTHER BURDENS, OTHER THAN THOSE NOTED, MAY EXIST ON THIS PROPERTY. OWNERS OR POTENTIAL BUYERS SHOULD BE AWARE THAT ABSTRACTING FOR VERIFICATION OF TITLE AND/OR ACTUAL OWNERSHIP WAS NOT IN THE SCOPE OF THIS SURVEY MADE BY BEI SURVEYING, LLC.

2. THE WORDS "CERTIFY," "CERTIFIES" OR "CERTIFICATION" AS USED HEREON IS UNDERSTOOD TO BE AN EXPRESSION OF PROFESSIONAL OPINION BY THE SURVEYOR, BASED UPON HIS BEST KNOWLEDGE, INFORMATION, AND BELIEF, AS SUCH, IT DOES NOT CONSTITUTE A GUARANTEE NOR A WARRANTY, EXPRESSED OR IMPLIED.

3. BEI SURVEYING, LLC HAS NOT AND DOES NOT PROVIDE WETLAND DELINEATION OR DETERMINATION AND WAS NOT REQUESTED NOR INCLUDED IN THIS SURVEY.

4. THE LINES SHOWN ASSOCIATED WITH SECTIONS, TOWNSHIPS, RANGES AND FLOOD ZONES WERE DIGITIZED FROM AERIAL IMAGERY, F.E.M.A. FLOOD INSURANCE RATE MAPS AND U.S.G.S. QUADRANGLE MAPS. THESE LINES ARE SHOWN FOR REFERENCE ONLY AND WERE NOT FIELD VERIFIED AT THE TIME OF THIS SURVEY WAS PERFORMED.

5. THE UTILITIES SHOWN HEREON WERE LOCATED FROM ABOVE GROUND, VISIBLE EVIDENCE ONLY. ONLY THOSE UTILITIES THAT WERE DEEMED PERTINENT TO THE PURPOSE OF THE SURVEY ARE SHOWN. OTHER UTILITIES ARE CONSIDERED TO EXIST EVEN IF NOT SHOWN HEREON.

6. ADJACENT PROPERTY OWNER INFORMATION AS SHOWN HEREON WAS TAKEN FROM THE ST. TAMMANY PARISH TAX ASSESSORS GIS WEBSITE.

CERTIFICATION:

I CERTIFY THAT THIS PLAT REPRESENTS AN ACTUAL GROUND SURVEY MADE BY ME OR UNDER MY DIRECTION, AND IT DOES CONFORM TO THE REQUIREMENTS FOR THE STANDARDS OF PRACTICE FOR PROPERTY BOUNDARY SURVEYS AS FOUND IN LOUISIANA ADMINISTRATIVE CODE TITLE 46: LXI, CHAPTER 25 FOR A CLASS C SURVEY.

Seth J. Mosby
SETH J. MOSBY, P.L.S.
PROFESSIONAL LAND SURVEYOR #5073
FILE: "TREASURE ISLE(ST. TAMMANY)..."

NOVEMBER 24, 2023
DATE



REFERENCES:


1. "MAP AND SURVEY TREASURE ISLE...", DATED 07/31/1950, LAST REVISED 05/15/1951, BY G.A. HEFT & CO. RECORDED IN THE ST. TAMMANY PARISH CLERK OF COURT AS ENTRY NO. 792650.

FLOOD CERTIFICATION:

BY GRAPHIC PLOTTING ONLY, THIS PROPERTY FALLS IN FLOOD ZONE(S) "VE(ELEVATION 16)" OF THE FLOOD INSURANCE RATE MAP, COMMUNITY PANEL NO. 225205 MAP NO. 22106C0635F WHICH BEARS AN EFFECTIVE DATE OF 04/30/2008.

BASIS OF BEARINGS:

THE BEARINGS & COORDINATES SHOWN HEREON ARE BASED ON THE LOUISIANA STATE PLANE COORDINATE SYSTEM, SOUTH ZONE (1702), NAD 1983 (2011, EPOCH 2010.00) AS DETERMINED BY GPS OBSERVATIONS.




JOB NO.:	23-154
FIELD BOOK:	SEE FOLDER
PAGE(S):	SEE FOLDER
PARTY CHIEF:	SJM




BEI
SURVEYING, LLC

PHONE: 225-715-8307
EMAIL: beisurveys@gmail.com
ADDRESS: 16709 AMY LANE
FRENCH SETTLEMENT, LA, 70733



site plan
scaled at 1" = 20'-0"



builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity - builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted

lot 55, treasure isle
slidell, louisiana

the divincinti residence


project 21-154

december 11, 2023


thefrontdoor **fd**
design studio

1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com

a-1.1




floor plan - level 1
scaled at 1/4" = 1'-0"



square footage	
LIVING AREA - LEVEL 1	2,726 SQ. FT.
LIVING AREA - LEVEL 2	1,214 SQ. FT.
TOTAL LIVING AREA	3,940 SQ. FT.
REAR PORCH	805 SQ. FT.
LOWER STORAGE	218 SQ. FT.
PUMP ROOM	55 SQ. FT.
FRONT PORCH	153 SQ. FT.
TOTAL AREA	5,171 SQ. FT.

general note

ALL DRAWINGS PREPARED BY THE FRONT DOOR DESIGN STUDIO ARE DESIGNED TO MEET THE REQUIREMENTS OF IRC 2021 ASSUMING WIND SPEEDS OF 142 MPH, SDC CATEGORY A. DRAWINGS ARE PREPARED AND CERTIFIED BY LICENSED ARCHITECT #LA 5271.



builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity - builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted


lot 55, treasure isle
slidell, louisiana

the divincinti residence


thefrontdoor **fd**
design studio

1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com

project 21-154
december 11, 2023
a-1.2



floor plan - level 2
scaled at 1/4" = 1'-0"



builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity - builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted

lot 55, treasure isle
slidell, louisiana

the divincinti residence


project 21-154

december 11, 2023

thefrontdoor **fd.**
design studio

1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com

a-1.3



roof plan

scaled at 1/8" = 1'-0"

DOOR SCHEDULE

MARK	SIZE	THICK	DESCRIPTION
1	3'-0" X 8'-0"	1 3/4"	2 PANEL, FIBERGLASS, EXTERIOR GRADE, 20 MIN RATING
2	6'-0" X 9'-0"	1 3/4"	PAIR, FIBERGLASS, EXTERIOR GRADE, 1 LITE , FULL GLASS
3	6'-0" X 8'-0"	1 3/4"	PAIR, 2 PANEL, FIBERGLASS, EXTERIOR GRADE
4	3'-0" X 8'-0"	1 3/4"	FIBERGLASS, EXTERIOR GRADE, 1 LITE, FULL GLASS
5	2'-8" X 8'-0"	1 3/4"	2 PANEL, FIBERGLASS, EXTERIOR GRADE
6	2'-4" X 8'-0"	1 3/4"	2 PANEL, FIBERGLASS, EXTERIOR GRADE
7	3'-0" X 8'-0"	1 3/8"	2 PANEL, SMOOTH MASONITE FACE, INTERIOR GRADE
8	2'-8" X 8'-0"	1 3/8"	2 PANEL, SMOOTH MASONITE FACE, INTERIOR GRADE
9	2'-4" X 8'-0"	1 3/8"	2 PANEL, SMOOTH MASONITE FACE, INTERIOR GRADE
10	3'-0" X 8'-0"	1 3/8"	2 PANEL, SMOOTH MASONITE FACE, INTERIOR GRADE, POCKET
11	4'-0" X 8'-0"	1 3/8"	PAIR, 2 PANEL, SMOOTH MASONITE FACE, INTERIOR GRADE
12	3'-0" X 8'-0"	1 3/8"	PAIR, 2 PANEL, SMOOTH MASONITE FACE, INTERIOR GRADE
13	4'-6" X 8'-0"	1 3/8"	CUSTOM BARN DOOR ON SURFACE MOUNT TRACK, AS SELECTED BY OWNER
14	3'-0" X 8'-0"	1 3/4"	2 PANEL, FIBERGLASS, EXTERIOR GRADE
15	6'-0" X 8'-0"	STD	OVERHEAD GARAGE DOOR W/ AUTO OPENER, 142 MPH WIND RATED

WINDOW SCHEDULE


MARK	SIZE	LITES	DESCRIPTION
A	5'-0" X 6'-0"	1/1	FIXED, VINYL, INSULATING W/ 5'-0" X 2'-0", 1-LITE TRANSOM, MULLED
B	2 - 5'-0" X 6'-0"	1/1	PAIR, FIXED, VINYL, INSULATING W/ 5'-0" X 2'-0", 1-LITE TRANSOM, MULLED
C	8'-0" X 5'-6"	1	FIXED, VINYL, INSULATING
D	5'-0" X 5'-0"	1	FIXED, VINYL, INSULATING
E	3 - 4'-0" X 6'-0"	1/1	TRIPLE, FIXED, VINYL, INSULATING W/ 4'-0" X 2'-0" 1-LITE TRANSOMS, MULLED
F	4'-0" X 6'-0"	1/1	FIXED, VINYL, INSULATING W/ 4'-0" X 2'-0" 1-LITE TRANSOM, MULLED
G	3'-0" X 5'-6"	1	CASEMENT, VINYL, INSULATING
H	3'-0" X 5'-0"	1	FIXED, VINYL, INSULATING
J	3'-0" X 5'-0"	1	CASEMENT, VINYL, INSULATING

WINDOW NOTES:

- ALL WINDOWS TO HAVE 2" BRICK MOULD TRIM, TYPICAL.
- ALL WINDOW UNITS SHALL MEET ALL LOCAL WIND AND ENERGY REQUIREMENTS AS PER IRC 2021
- ALL WINDOWS SHALL HAVE BOTH INTERIOR AND EXTERIOR APPLIED, RAISED PROFILE MULLIONS
- TEMPERED GLAZING REQUIRED AS PER IRC 2021 R308.4.3 AT LOCATIONS AS LISTED.
- WINDOW MANUFACTURER TO PROVIDE AS REQUIRED.
- 1- PANE IS LARGER THAN 9 SQ FT
- 2- BOTTOM EDGE OF GLASS IS LESS THAN 18" AFF
- 3- TOP EDGE OF GLASS IS MORE THAN 36" AFF
- 4- ONE OR MORE WALKING SURFACE IS WITHIN 36" OF THE WINDOW
- 5- ALL DOOR GLAZING SHALL BE TEMPERED
- 6- ALL GLAZING WITHIN 24" OF A DOOR


GENERAL ROOF NOTES:

- ALL ROOFING SHALL BE COLOR-CLAD STANDING SEAM METAL WITH CONTINUOUS RIDGE VENTS AT ALL RIDGES. PROVIDE ADDITIONAL VINYL UNDERLAY AT ANY PITCH LESS THAN 4 ON 12.
- ALL ROOF PROTRUSIONS SHALL BE LOCATED ON REAR ROOF SURFACES AND PAINTED TO MATCH ROOFING.
- PROVIDE MECHANICAL VENTILATION AS REQUIRED TO VENT ROOF



floor plan - grade level

scaled at 1/4" = 1'-0"



builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity - builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted

lot 55, treasure isle
slidell, louisiana


the divincinti residence

project 21-154

december 11, 2023


the front door **fd**
design studio
1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com

a-1.4



rear elevation

scaled at 1/4" = 1'-0"



builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity - builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted

lot 55, treasure isle
slidell, louisiana

the divincinti residence


thefrontdoor **fd.**
design studio

1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com

project 21-154


december 11, 2023

a-2.1



rear side elevation

scaled at 1/4" = 1'-0"



builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity - builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted

lot 55, treasure isle
slidell, louisiana

the divincinti residence

project 21-154


december 11, 2023

the front door **fd**
design studio
1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com

a-2.2



left side elevation
scaled at 1/4" = 1'-0"



builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity - builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted

lot 55, treasure isle
slidell, louisiana


the divincinti residence

project 21-154
december 11, 2023

the front door **fd.**
design studio


1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com

a-2.3



right side elevation

scaled at 1/4" = 1'-0"



builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity - builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted

lot 55, treasure isle
slidell, louisiana

the divincinti residence

project 21-154

december 11, 2023

thefrontdoor **fd.**
design studio

1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com

a-2.4

FRAMING NOTES

- ALL FRAMING SHALL BE IN ACCORDANCE WITH IRC 2021, SECTION 602, 602.3(1) AND 602.3(2).
- REFER TO FLOOR PLANS AND BUILDING SECTIONS FOR FRAMING SIZES AND LOCATIONS, INCLUDING BEAMS, WALLS, RAFTERS, ETC.
- ALL WOOD SHALL BE NO. 2 GRADE SOUTHERN YELLOW PINE.
- PROVIDE JOIST HANGERS AS REQUIRED PER FRAMING. HANGERS SHALL BE SIMPSON OR EQUAL.
- ALL COLUMNS SHALL BE ANCHORED WITH SIMPSON ABU BASE, SIZED TO FIT COLUMN, TO PREVENT LATERAL DISPLACEMENT AS PER IRC 2021 SECTION 407.3.
- ALL SILLS SHALL BE PRESSURE TREATED AND HAVE 1/2" CONTINUOUS CAULK AND FOAM STRIP SEALER UNDER ALL PLATES.
- PROVIDE ALL BLOCKING AS REQUIRED TO PROVIDE FULL NAILING SURFACE FOR GYP BOARD, SIDING, ETC.
- ALL EXPOSED MATERIALS FOR SOFFITS, PATIOS, OVERHANGS, ETC SHALL BE EXTERIOR GRADE PRESSURE TREATED WOOD OR EQUIVALENT ROT-RESISTANT MATERIAL.
- WRAP ENTIRE BUILDING SURFACE WITH BUILDING PAPER (TYVEK OR EQUAL), INSTALL PER MANUFACTURER'S SPECS.
- ATTIC ACCESS SHALL BE PROVIDED TO ALL ATTIC AREAS. ACCESS OPENINGS SHALL BE MINIMUM 22X30" AND SHALL MAINTAIN 30" MINIMUM VERTICAL HEIGHT AT OPENING.
- ALL PENETRATIONS OF ANY WALL, FLOOR OR CEILING SHALL BE SEALED IN AN AIR-TIGHT MANNER. FLASH AND COUNTER FLASH AS REQUIRED.
- IN LOCATIONS AS NOTED ON PLANS, ENGINEERED FLOORS AND BEAM SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH ANY ENGINEERED DRAWINGS OR SYSTEM SPECIFICATIONS.
- ALL BEAMS SHALL BE SIZED BY MANUFACTURER AND SHALL MEET LOAD AND DEFLECTION LIMITS PER IRC 2021, 602. PROVIDE FULL STUD BEARING UNDER ALL BEAM BEARING POINTS TO FOUNDATION. PROVIDE LATERAL SUPPORT VIA BLOCKING OR ANCHOR AS REQUIRED.
- GARAGE AND OTHER OVERSIZED OPENINGS SHALL BE FRAMED AS PER THE PORTAL FRAMING DETAIL ATTACHED.
- TALL WALL FRAMING SHALL BE BALLOON FRAMED AND CONSTRUCTED AS PER TALL WALL DETAIL ATTACHED.

HURRICANE STRAPPING AND BRACES

- EXTERIOR SILL PLATES - SIMPSON MAS @ 24" OC
- FLOOR TO FLOOR TIES - SIMPSON CS200, 18GA @ 32" OC
- TRUSS/RAFTER TIES - SIMPSON H7, 16GA @ EACH RAFTER
- SHEAR WALLS - REFER TO SHEAR WALL NOTES
- ALL NAILING PATTERNS, SPLICES, ETC SHALL BE AS PER CODE.

ROOF FRAMING NOTES

- EXTERIOR SILL PLATES - SIMPSON MAS @ 24" OC ALL WOOD FRAMED ROOF CONSTRUCTION SHALL COMPLY WITH IRC 2021, SECTION 602.
- ALL LUMBER SHALL BE NO. 2 GRADE SOUTHERN YELLOW PINE.
- CEILING JOIST SPANS SHALL BE AS PER PLANS BASED ON IRC 2015, 20F LIVE LOAD / 10F DEAD LOAD AND L/240 DEFLECTION ALLOWANCES.
- ALL RAFTERS SHALL BE MINIMUM 2X6, SPACED AT 24" OC UNLESS ADDITIONAL LOADING IS REQUIRED. ALL RIDGES, HIPPS AND VALLEYS SHALL BE MINIMUM 2X8 UNLESS OTHERWISE NOTED.
- ROOF SHALL BE FULLY BRACED AS PER IRC 2015.
- PROVIDE 2X4 COLLAR BRACING AT EVERY OTHER RAFTER IN THE TOP THIRD OF THE SPAN.
- CEILING JOISTS SHALL BE FASTENED TO EVERY OTHER RAFTER PER IRC 602.3.1 AND SHALL BE SECURED TO PLATE PER IRC 602.11.
- ALL BRACING SHALL BE T-BRACING AS REQUIRED
- PROVIDE 2X6 STRONGBACK AT THE CENTER OF ALL CEILING JOISTS WITH SPANS GREATER THAN 10' IN LENGTH.
- ROOF SHEATHING SHALL COMPLY WITH SPAN CHART AS PER IRC R503.2.1.1(1)

HEADER SPAN TABLE

SINGLE STORY		TWO STORY	
2X6	4'-6" MAX	2X6	3'-2" MAX
2X8	5'-9" MAX	2X8	4'-1" MAX
2X10	7'-0" MAX	2X10	4'-11" MAX
2X12	8'-1" MAX	2X12	5'-9" MAX

SPAN CALCULATIONS ARE BASED ON IRC 2021 TABLE 602.7(1) ASSUMING ALLOWABLE BEARING OF 30 PSF / 28 SPAN. CHANGES IN LENGTH MAY BE REQUIRED PENDING DIFFERING BUILDING WIDTHS. REFER TO IRC 2021 TABLE 602.7(1) FOR ADDITIONAL SIZES AND LENGTHS.

TYPICAL INSULATION NOTES

CONTRACTOR SHALL PROVIDE INSULATION AS SPECIFIED:

WALLS	R-13 BATT
CEILING - STANDARD	R-30 BLOWN
CEILING - VAULTED	R-30 BATT
FLOORS (2-STORY ONLY)	R-19 BATT

PROVIDE INTERIOR INSULATION AROUND ALL BATHROOMS AND BETWEEN ALL LIVING SPACES AND BEDROOM WALLS, TYPICAL

INSULATOR SHALL SEAL ALL PERIMETER WALL PLATES

INSULATOR SHALL NOT USE EXPANSIVE SEALERS AROUND WINDOWS AND DOORS AS IT AFFECTS THEIR PROPER OPERATION.

TERMITE PROTECTION

ALL SLABS SHALL BE TERMITE TREATED AND PROTECTED AS PER IRC 2021 R320. CONTRACTOR SHALL PROVIDE A 12 MONTH CERTIFICATION TO OWNER AT COMPLETION.

SHEAR WALL NOTES

SHEAR WALL CALCULATIONS BASED ON DESIGN WIND SPEED OF 130 MPH AND IRC 2021. SHEAR WALL DESIGN BASED ON WIND PRESSURE COEFFICIENTS AND LOAD COMBINATIONS AS PER ASCE 7 FOR WIND LOADS.

ONE-STORY PLANS:

SHEAR WALLS SHALL BE LOCATED AS PER PLANS AND BE A MINIMUM LENGTH AS NOTED ON FLOOR PLAN.

GYP SUM BOARD WALLS

SHEAR WALLS BE CONSTRUCTED OF 2X4 STUDS (UNLESS OTHERWISE NOTED) AT 16" OC WITH 1/2" GYP SUM BOARD AT BOTH SIDES.

GYP SUM BOARD SHALL BE NAILED TO THE WOOD STUDS SPACED AT NO MORE THAN 16" OC WITH 5D COOLER (.086 X 1-5/8", 15/64" HEAD) OR WALLBOARD NAIL (.086X1-5/8", 9/32" HEAD) OR .120" NAIL X 1-1/2", MIN 3/8" HEAD. DRYWALL SCREWS MAY NOT BE USED FOR SHEAR WALL CONSTRUCTION.

THE SPACING OF THE NAILING OF THE GYP SUM BOARD SHALL BE 4" OC INCLUDING ALL EDGES. ALL EDGES SHALL BE FULLY BLOCKED.

EACH END OF THE SHEAR WALL SHALL BE ANCHORED TO THE SLAB WITH A SIMPSON STRONG TIE HT4 OR BETTER WITH A 5/8" DIA THREADED ROD WITH 6" MIN EMBEDMENT AND EPOXIED INTO THE CONCRETE WITH EITHER HILTI HIT-RE 100 EPOXY OR SIMPSON STRONG TIE SET-XP EPOXY.

PLYWOOD WALLS

SHEAR WALLS BE CONSTRUCTED OF 2X4 STUDS (UNLESS OTHERWISE NOTED) AT 16" OC WITH 3/8" WOOD SHEATHING AT BOTH SIDES.

PLYWOOD SHALL BE NAILED TO THE WOOD STUDS SPACED AT NO MORE THAN 16" OC WITH 6D COMMON OR GALVANIZED BOX NAILS

THE SPACING OF THE NAILING OF THE GYP SUM BOARD SHALL BE 4" OC INCLUDING ALL EDGES. ALL EDGES SHALL BE FULLY BLOCKED. JOINTS SHALL BE OFFSET AND NOT ALIGNED ON THE SAME STUD.

EACH END OF THE SHEAR WALL SHALL BE ANCHORED TO THE SLAB WITH A SIMPSON STRONG TIE HT4 OR BETTER WITH A 5/8" DIA THREADED ROD WITH 6" MIN EMBEDMENT AND EPOXIED INTO THE CONCRETE WITH EITHER HILTI HIT-RE 100 EPOXY OR SIMPSON STRONG TIE SET-XP EPOXY.

THE BOTTOM PLATE OF THE WALL SHALL BE ANCHORED TO SLAB WITH 5/8" DIA THREADED ROD AT MAX 2'-0" OC WITH 6" MIN EMBEDMENT AND EPOXIED INTO THE CONCRETE WITH EITHER HILTI HIT-RE 100 EPOXY OR SIMPSON STRONG TIE SET-XP EPOXY.

TWO-STORY PLANS:

SHEAR WALLS SHALL BE LOCATED AS PER PLANS AND BE A MINIMUM LENGTH AS NOTED ON FLOOR PLAN. FOR 1-STORY WALLS WITH NO SECOND FLOOR ABOVE REFER TO ONE-STORY NOTES.

GYP SUM BOARD WALLS

GYP SUM BOARD SHALL BE NAILED TO THE WOOD STUDS SPACED AT NO MORE THAN 16" OC WITH 5D COOLER (.086 X 1-5/8", 15/64" HEAD) OR WALLBOARD NAIL (.086X1-5/8", 9/32" HEAD) OR .120" NAIL X 1-1/2", MIN 3/8" HEAD. DRYWALL SCREWS MAY NOT BE USED FOR SHEAR WALL CONSTRUCTION.

THE SPACING OF THE NAILING OF THE GYP SUM BOARD SHALL BE 4" OC INCLUDING ALL EDGES. ALL EDGES SHALL BE FULLY BLOCKED.

EACH END OF THE SHEAR WALL SHALL BE ANCHORED DOWN THROUGH THE 2ND FLOOR TO AN IN-LINE SHEAR WALL ON THE 1ST FLOOR WITH A SET OF SIMPSON STRONG TIE HT4 OR BETTER (ONE ON DOUBLE STUDS ON THE 2ND FLOOR AND THE OTHER ON DOUBLE STUDS ON THE 1ST FLOOR) WITH A 5/8" DIA THREADED ROD SET BETWEEN THE TWO HT4s. THE MATCHING TENSION STUDS ON THE 1ST FLOOR MUST BE ANCHORED TO THE SLAB AS PER BELOW.

THE BOTTOM PLATE SHALL BE NAILED TO A SOLID JOIST OR BLOCKING BETWEEN THE FLOORS WITH 16D COMMON NAILS AT 16" OC MAX.

EACH END OF THE SHEAR WALL (AT 1ST FLOOR) SHALL BE ANCHORED TO THE SLAB WITH A SIMPSON STRONG TIE HT4 OR BETTER WITH A 5/8" DIA THREADED ROD WITH 6" MIN EMBEDMENT AND EPOXIED INTO THE CONCRETE WITH EITHER HILTI HIT-RE 100 EPOXY OR SIMPSON STRONG TIE SET-XP EPOXY.

THE BOTTOM PLATE OF THE WALL SHALL BE ANCHORED TO SLAB WITH 5/8" DIA THREADED ROD AT MAX 4'-0" OC WITH 6" MIN EMBEDMENT AND EPOXIED INTO THE CONCRETE WITH EITHER HILTI HIT-RE 100 EPOXY OR SIMPSON STRONG TIE SET-XP EPOXY.

PLYWOOD WALLS

SHEAR WALLS BE CONSTRUCTED OF 2X4 STUDS (UNLESS OTHERWISE NOTED) AT 16" OC WITH 3/8" WOOD SHEATHING AT BOTH SIDES.

PLYWOOD SHALL BE NAILED TO THE WOOD STUDS SPACED AT NO MORE THAN 16" OC WITH 6D COMMON OR GALVANIZED BOX NAILS

THE SPACING OF THE NAILING OF THE GYP SUM BOARD SHALL BE 4" OC INCLUDING ALL EDGES. ALL EDGES SHALL BE FULLY BLOCKED. JOINTS SHALL BE OFFSET AND NOT ALIGNED ON THE SAME STUD.


EACH END OF THE SHEAR WALL SHALL BE ANCHORED DOWN THROUGH THE 2ND FLOOR TO AN IN-LINE SHEAR WALL ON THE 1ST FLOOR WITH A SET OF SIMPSON STRONG TIE HT4 OR BETTER (ONE ON DOUBLE STUDS ON THE 2ND FLOOR AND THE OTHER ON DOUBLE STUDS ON THE 1ST FLOOR) WITH A 5/8" DIA THREADED ROD SET BETWEEN THE TWO HT4s. THE MATCHING TENSION STUDS ON THE 1ST FLOOR MUST BE ANCHORED TO THE SLAB AS PER BELOW.

EACH END OF THE SHEAR WALL SHALL BE ANCHORED TO THE SLAB WITH A SIMPSON STRONG TIE HT4 OR BETTER WITH A 5/8" DIA THREADED ROD WITH 6" MIN EMBEDMENT AND EPOXIED INTO THE CONCRETE WITH EITHER HILTI HIT-RE 100 EPOXY OR SIMPSON STRONG TIE SET-XP EPOXY.






THE BOTTOM PLATE OF THE WALL SHALL BE ANCHORED TO SLAB WITH 5/8" DIA THREADED ROD AT MAX 2'-0" OC WITH 6" MIN EMBEDMENT AND EPOXIED INTO THE CONCRETE WITH EITHER HILTI HIT-RE 100 EPOXY OR SIMPSON STRONG TIE SET-XP EPOXY.

HEADER SPAN TABLE


SPAN CALCULATIONS ARE BASED ON IRC 2021 TABLE 602.7(1) ASSUMING ALLOWABLE BEARING OF 30 PSF / 28 SPAN. CHANGES IN LENGTH MAY BE REQUIRED PENDING DIFFERING BUILDING WIDTHS. REFER TO IRC 2021 TABLE 602.7(1) FOR ADDITIONAL SIZES AND LENGTHS.



PORTAL FRAMING DETAIL
NOT TO BE SCALED




TYPICAL WALL SECTION - ONE STORY WALLS
SCALED AT 1/2" = 1'-0"




TYPICAL WALL SECTION - TWO STORY WALLS
SCALED AT 1/2" = 1'-0"

TYPICAL STAIR DETAIL
SCALED AT 3/4" = 1'-0"



TYPICAL BEAM DETAIL
SCALED AT 1-1/2" = 1'-0"

TYPICAL EAVE DETAIL
SCALED AT 1-1/2" = 1'-0"



builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity - builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted


lot 55, treasure isle
slidell, louisiana

the divincinti residence

project 21-154
december 11, 2023

thefrontdoor **fd**
design studio

1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com



HVAC NOTES:

ALL UNITS

HEATING: GAS FIRED, HORIZONTAL FLOW, ATTIC INSTALLATION
SIZED PER MANUFACTURER'S RECOMMENDATION

GENERAL HVAC NOTES:

1. RETURN AIR: CEILING MOUNT, WHITE; UNIT A = 20 X 30
2. COIL DRAINS CONNECTED TO PLUMBING WITH 1 1/2" P-TRAP
3. DUCTS: 26 GA. GALVANIZED SHEETMETAL WITH 2" INSULATION WRAP. OR FOIL-WRAPPED INSULATED FLEX DUCT
4. REGISTERS: 8X16, THREE-WAY DIFFUSER, W/ SHUT OFF, WHITE
5. VOLUME CONTROL DAMPERS INSTALLED AT EACH BRANCH CONNECTION.
6. INSTALL DRAIN PAN WITH FLOAT SWITCH UNDER EVAPORATOR COIL.
7. COPPER REFRIGERANT LINES WITH ARMAFLEX INSULATION.
8. MANUFACTURER SHALL VERIFY LOCATIONS OF ALL REGISTERS, DUCT ROUTING AND SIZING TO COMPLY WITH MFG RECOMMENDATIONS
9. INSTALLER SHALL BALANCE ENTIRE SYSTEM AFTER POWER AT RESIDENCE HAS BEEN PROVIDED AND PRIOR TO OWNER OCCUPANCY.
10. INSTALL PLYWOOD ACCESS WALKWAY AND SERVICE PLATFORM. PLATFORM SHALL BE A MINIMUM OF 30X30 AT THE UNIT.

GENERAL MECHANICAL NOTES:


1. ALL VENTS, STACKS, AND ROOF JACKS SHALL BE LOCATED ON REAR ROOF SURFACE, AND PAINTED TO MATCH ROOF COLOR.
2. ALL VENTED KITCHEN HOODS SHALL VENT DIRECTLY TO THE EXTERIOR SHALL BE 6" HARD METAL PIPE AND CFM OF 250 LENGTH NOT TO EXCEED 25' AS PER IRC 2021
3. ALL TOILET ROOMS SHALL BE EQUIPPED WITH MECHANICAL VENTILATION AND VENTED DIRECT TO EXTERIOR
4. DRYER VENTS SHALL VENT DIRECT TO THE EXTERIOR AND MADE OF 4" HARD METAL PIPE AND LENGTH NOT TO EXCEED 12" REQUIREMENTS AS PER IRC 2021
5. ALL EXHAUST FANS SHALL BE MIN 50 CFM, W/ 4" FLEX PIPE LENGTH NOT TO EXCEED 56' AS PER IRC 2021

WATER HEATER NOTE:

1. PROVIDE GAS TANKLESS WATER HEATERS AS REQUIRED FOR THE CAPACITY OF THE HOUSE. UNITS SHALL BE FIELD LOCATED AND BE READILY ACCESSIBLE AND VENTED AS REQUIRED PER IRC 2021

hvac plan - level 1

scaled at 1/4" = 1'-0"



builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity -builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted

lot 55, treasure isle
slidell, louisiana

the divincinti residence


project 21-154

december 11, 2023

thefrontdoor **fd**
design studio

1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com

m-1.1



ELECTRICAL LEGEND	
	CEILING FAN
	RECESSED LED
	RECESSED LED 4" CAN
	LED EAVE LIGHTING
	CEILING MOUNT INCANDESCENT
	WALL MOUNT INCANDESCENT
	SWITCH
	SWITCH, DIMMABLE
	1X4, 2 BULB FLUORESCENT
	OUTLET
	OUTLET, 220V
	OUTLET, GFI GROUNDED, EXTERIOR
	CABLE OUTLET
	TELEPHONE
	VENT / RECESSED CAN LIGHT COMBO
	VENT
	SMOKE DETECTOR
	ALARM KEYPAD, BY OTHERS
	DOOR BELL
	EXTERIOR FLOOD LIGHT

ELECTRICAL NOTES

SERVICE: 120/240 V, 1 PH., 3 W


MAIN: 200 AMP
ELECTRICAL CONTR. TO VERIFY

PANEL: FLUSH MOUNT, 30 CIRCUITS


CIRCUITRY SHALL BE AS SHOWN, AND VERIFIED BY ELECTRICAL CONTRACTOR. PANEL AND SERVICE LOCATIONS SHALL BE AS PER PLANS. SERVICE LOCATION SHALL BE AS PER UTILITY GUIDELINES

NOTE: ALL SWITCHES SHALL BE LOCATED WITHIN 6" OF DOOR FRAME OR CORNER OF WALL

NOTE: SMOKE DETECTORS SHALL BE INTERCONNECTED WITH BATTERY AND CARBON MONOXIDE DETECTION AS PER IRC 2021




electrical plan - level 1
scaled at 1/4" = 1'-0"




builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity - builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted

lot 55, treasure isle slidell, louisiana	the divincinti residence	project 21-154 december 11, 2023
		e-1.1
1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com		



plumbing plan - level 1

scaled at 1/4" = 1'-0"



builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity - builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted


lot 55, treasure isle
slidell, louisiana

the divincinti residence


project 21-154

december 11, 2023


thefrontdoor **fd**
design studio
1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com



plumbing plan - level 2
scaled at 1/4" = 1'-0"



plumbing plan - ground level
scaled at 1/4" = 1'-0"



builder shall be allowed to deviate from all plans and specifications in such that given changes do not affect structural or design integrity - builder shall verify all dimensions - plans remain the property of the front door design studio and are released for the sole residence hereby noted - illegal use of drawings will be prosecuted

lot 55, treasure isle
slidell, louisiana

the divincinti residence

project 21-154

december 11, 2023

thefrontdoor **fd**
design studio

1010 nicholson drive . baton rouge . 225 . 338 . 9353 www.thefrontdoor-architecture.com

