



GENERAL SHEET NOTES

- WHERE METAL "Z" FLASHING OCCURS OVERLAP IN AIR BARRIER MEMBRANE OR TAPE WITH COMPATIBLE ADHESIVE.
- ALL METAL FLASHING SHALL BE 6198 GALV. MIN 20 GA. DO NOT USE ALUM WHERE IT COMES INTO CONTACT WITH TRTD WD UNLESS A DRAINABLE BARRIER MATERIAL IS PROVIDED.
- ALL EXPOSED WD DECKING, TRAVELS, GUARDRAILS, ETC SHALL BE INSTALLED WITH BEST SIDE UP OR OUT.
- PROVIDE TRTD 6x6 PLYWOOD POST POINTS W/ COPPER CAPS AT ALL STRK NELL POSTS.

DAMMON ENGINEERING, INC.
Architects & Engineers
Chief Architect: Kevin J. Kinchen, NCARB
Chief Engineer: Brian Misch, PE
554 Old Spanish Trail
Slidell, LA 70458
www.dammoneengineering.com
info@dammoneengineering.com
PH: 985.649.5832
F: 985.641.5950

#	DESCRIPTION	DATE

95% SUBMITTAL NOT FOR CONSTRUCTION
10/9/2014
CAMP VILLERE, LOUISIANA
LA 14-A-037

CAMP VILLERE NEW HOME CONSTRUCTION
CAMP VILLERE, LOUISIANA
JOB No: 2210 DATE: OCTOBER 8, 2014
DRAWN BY: [Signature] CHECKED BY: [Signature]

A3
SHEET NO. 1 OF 12