



PARKING LOT PHOTOMETRIC PLAN
SCALE: 1"=30'-0"

SITE LIGHTING

EXTERIOR LIGHTING SHALL BE SHADED OR INWARDLY DIRECTED IN SUCH A MANNER SO THAT NO DIRECT LIGHTING OR GLARE IS CAST BEYOND THE PROPERTY LINE. THE INTENSITY OF SUCH LIGHTING SHALL NOT EXCEED ONE FOOT CANDLE AS MEASURED AT THE ABUTTING PROPERTY LINE.

LUMINAIRE TYPE SUMMARY

TYPE	BRAND NAME	CATALOG NUMBER	QUANTITY
AA (P2)	TECHLIGHT	MS-BB-3A1	3
AA (P3)	TECHLIGHT	MS-BB-3A1	5
BB	TECHLIGHT	DCL-B1-AP1-BLACK	1
BB1	TECHLIGHT	DCM-B2-AN1-BLACK	3
JJ	CONSOLIDATED ARCH. LIGHTING	7525-MW/5,E17,75W	7
X416	PROGRESS	P-5431-25	9

DESCRIPTION

AA (P2)	1 (33)	ON A 30' POLE WITH	A 2 FOOT PEDESTACK
AA (P3)	1 (54)	ON A 30' POLE WITH	A 2 FOOT PEDESTACK
BB	1 (55)	ON A 30' POLE	
BB1	1 (56)	ON A 30' POLE	
JJ	1 (57)	GROUND MOUNTED	
X416	1 (58)	POST MOUNTED	

NOTE:
SEE SHEET E-1 FOR BUILDING EXTERIOR LIGHTING LOCATIONS, SHEET E-7 FOR LIGHTING FIXTURE DETAILS & SCHEDULES.

NOTE:
ALL UTILITIES SHALL BE INSTALLED UNDERGROUND.

LEGEND

- — — — — PROPERTY LINE
- — — — — FENCE LINE
- — — — — WIRING
- ⊙ — 2 @ 90° LUMINAIRE
- ⊙ — 250W 208V HP SODIUM
- ⊙ — 6 FT. HIGH POST LIGHT
- ⊙ — AROUND SWIMMING POOL
- ▲ — LANDSCAPE UPLIGHT

DESIGN 3 REVISED: 09-22-06

PARKING PHOTOMETRIC PLAN

DR. EDUARDO HERNANDEZ
CEDAR LAKE ROAD
BILOXI, MISSISSIPPI

LA QUINTA INN & SUITES

DAMMON ENGINEERING, INC.

1095 FLORIDA AVENUE 985-649-5832 SLIDELL, LA. 70458
DAMMONENGINEERING.COM

SCALE:AS NOTED

FILE:

JOB NO. 1694

DATE:11-01-05

SHEET

E-6

OF