

GENERAL NOTES

- INSULATION AND INSULATION ASSEMBLIES SHALL MEET THE REQUIREMENTS OF SECTION 719. CONCEALED INSULATION SHALL HAVE A FLAME SPREAD OF 0-25 AND SMOKE DEVELOPED INDEX OF 0-450, EXCEPT THAT IN COMBUSTIBLE (WOOD FRAME) CONSTRUCTION.
 - INSULATION SHALL BE NEW AND U.L. LISTED.
 - NO WORK SHALL BE CONCEALED UNTIL APPROVED BY LOCAL INSPECTORS.
 - CONSTRUCTION SHALL COMPLY WITH ALL PARISH, STATE, AND LOCAL CODES.
 - CONTRACTOR TO GUARANTEE WORK FOR ONE YEAR.
 - CONTRACTOR SHALL FURNISH WATER AND POWER FROM EXISTING SOURCES.
 - EXTERIOR CALCULATING SHALL BE DOW CORNING 790 SILICONE; INSTALL IN ACCORDANCE WITH MANUFACTURER RECOMMENDATION WITH ARCH/OOWNER TO SELECT COLOR. INTERIOR CALCULATING TO BE EQUAL TO DAP PAINTABLE LATEX WITH SILICONE.
 - PAINT GRADE TO SHALL BE SHERWIN WILLIAMS OR EQUIVALENT. ALL WORK TO RECEIVE 3 COATS. COLOR SELECTION BY OWNER.
 - PROVIDE CLEANUP ON A REGULAR BASIS. NO TRASH STORED IN BUILDING.
 - ALL BATT INSULATION SHALL HAVE A CLASS "X" (0-25) FLAME SPREAD IN COMPLIANCE WITH APPLICABLE CODE.
 - USE 6" STUDS, OR 4" STAGGERED STUDS AT ALL PLUMBING WALLS.
 - PROVIDE GALVANIZED METAL PAN WITH DRAIN AT WATER HEATER LOCATION.
 - ALL CORNERS SHALL BE PROPERLY BRACED FOR WIND LOADS. A 48" SHEATHING SHALL BE PROVIDED EVERY 20 FEET OF WALL LENGTH.
 - FLOORING SHALL BE NON-SLIP.
 - INTERIOR LOCKS ON DOORS IN MEANS OF EGRESS SHALL NOT REQUIRE THE USE OF A KEY. SPECIAL KNOWLEDGE, OR SPECIAL DEVICE TO OPEN IN THE DIRECTION OF EGRESS. ALL DOORS SHALL HAVE LEVER TYPE HANDLES.
 - INTERIOR WALLS AND CEILINGS SHALL HAVE A FLAME SPREAD OF 0-200 AND A SMOKE DEVELOPMENT RATING OF 0-450.
 - ALL WORK SHALL COMPLY WITH THE LATEST EDITION OF ALL LOCAL, STATE, AND NATIONAL CODES COVERING THE TYPE OF WORK BEING PERFORMED.
 - PROVIDE PORTABLE FIRE EXTINGUISHERS IN ACCORDANCE WITH NFPA 101. SEE APPENDIX "E" OF NFPA 101 FOR DISTRIBUTION OF EXTINGUISHERS.
 - ALL FIRE WALLS SHALL EXTEND TIGHT TO ROOF SHEATHING, AND BE SEALED WITH AN APPROVED FIRE CAULK.
 - ALL ELECTRICAL, MECHANICAL, AND PLUMBING MATERIALS PENETRATING FIRE WALLS SHALL BE FIRE CAULKED. (PENETRATIONS THROUGH RATED CONSTRUCTION SHALL BE SEALED WITH A MATERIAL CAPABLE OF PREVENTING THE PASSAGE OF FLAMES AND HOT GASES WHEN TESTED IN ACCORDANCE WITH ASTM-E814.)
 - SERVICE COUNTER SHALL HAVE A HCP ACCESSIBLE WRITING SURFACE. MAX. 36" FROM F.F. (ADAAG MANUAL 1998, PG. 135)

DOOR & HARDWARE SCHEDULE

NO.	DESCRIPTION	TYPE	FRAME	HINGE	LOCK	ACCESSORIES	REMARKS
1	3/04x6/8	SOLID WOOD					
2	3/04x6/8	HOLLOW METAL					
3	3/04x6/8	ALUM/GLASS					
4	12/0x12/0	STOREFRONT					
5	3/04x6/8	ROLL UP					
6	3/04x6/8	STEEL					
7	3/04x6/8	ALUMINUM					
8	2/6x6/8	WOOD					
9	3/04x6/8	CASED OPENING					
10	PR. 3/04x6/8	DBL SWING					
11	3/04x6/8	BUTT 1-1/2 PR					
12	14/0x14/0	BURGLERPRF					
13	12/0x12/0	FIXED					
14	3/04x6/8	PASSAGE					
15	3/04x6/8	PRIVACY					
16	3/04x6/8	DEADBOLT					
17	3/04x6/8	KEYED HANDLE					
18	3/04x6/8	OFFICE/ENTRANCE					
19	3/04x6/8	STORE ROOM					
20	3/04x6/8	PANIC BAR					
21	3/04x6/8	THRESHOLD					
22	3/04x6/8	WEATHERSTRIP					
23	3/04x6/8	DOOR STOP					
24	3/04x6/8	ALARM					
25	3/04x6/8	SILENCER					
26	3/04x6/8	CLOSER					
27	3/04x6/8						
28	3/04x6/8						
29	3/04x6/8						
30	3/04x6/8						
31	3/04x6/8						
32	3/04x6/8						
33	3/04x6/8						
34	3/04x6/8						
35	3/04x6/8						
36	3/04x6/8						
37	3/04x6/8						
38	3/04x6/8						
39	3/04x6/8						
40	3/04x6/8						
41	3/04x6/8						
42	3/04x6/8						
43	3/04x6/8						
44	3/04x6/8						
45	3/04x6/8						
46	3/04x6/8						
47	3/04x6/8						
48	3/04x6/8						
49	3/04x6/8						
50	3/04x6/8						
51	3/04x6/8						
52	3/04x6/8						
53	3/04x6/8						
54	3/04x6/8						
55	3/04x6/8						
56	3/04x6/8						
57	3/04x6/8						
58	3/04x6/8						
59	3/04x6/8						
60	3/04x6/8						
61	3/04x6/8						
62	3/04x6/8						
63	3/04x6/8						
64	3/04x6/8						
65	3/04x6/8						
66	3/04x6/8						
67	3/04x6/8						
68	3/04x6/8						
69	3/04x6/8						
70	3/04x6/8						
71	3/04x6/8						
72	3/04x6/8						
73	3/04x6/8						
74	3/04x6/8						
75	3/04x6/8						
76	3/04x6/8						
77	3/04x6/8						
78	3/04x6/8						
79	3/04x6/8						
80	3/04x6/8						
81	3/04x6/8						
82	3/04x6/8						
83	3/04x6/8						
84	3/04x6/8						
85	3/04x6/8						
86	3/04x6/8						
87	3/04x6/8						
88	3/04x6/8						
89	3/04x6/8						
90	3/04x6/8						
91	3/04x6/8						
92	3/04x6/8						
93	3/04x6/8						
94	3/04x6/8						
95	3/04x6/8						
96	3/04x6/8						
97	3/04x6/8						
98	3/04x6/8						
99	3/04x6/8						
100	3/04x6/8						

DOOR & HARDWARE NOTES:

- ALL GLAZING TO BE LAMINATED SAFETY GLASS.
- DOOR HINGES TO BE STANLEY FULL MORTISE STANDARD WEIGHT BALL BEARING HINGES. STAINLESS STEEL WITH DARK BRONZE FINISH @ EXTERIOR & MATCHING DARK BRONZE FINISH ON STANDARD STEEL @ INTERIOR.
- PROVIDE LEVER HANDLE ADA APPROVED LOCKSETS WITH MATCHING DARK BRONZE FINISH TO BE SELECTED BY OWNER.
- COORDINATE KEYSING SCHEDULE WITH OWNER.
- DOOR STOPS TO BE EQUAL TO VES. NO. 436 OR 437, AS REQUIRED IN MATCHING DARK BRONZE FINISH.
- WEATHER-STRIP & THRESHOLD FINISH TO COMPLEMENT OTHER HARDWARE.
- STORAGE ROOM DOOR MARK #7 TO BE WOOD WITH STORE ROOM LOCK.

WINDOW SCHEDULE

NO.	DESCRIPTION	TYPE	FRAME	GLASS	LITES	ACCESSORIES	REMARKS
1	4/0x27/0	FIXED					
2	4/0x27/0	S. HUNG					
3	4/0x27/0	D. HUNG					
4	4/0x27/0	HORIZ SLIDE					
5	4/0x27/0	STEEL					
6	4/0x27/0	ALUMINUM					
7	4/0x27/0	WOOD					
8	4/0x27/0	LOW E					
9	4/0x27/0	PLAIN					
10	4/0x27/0	TEMPERED					
11	4/0x27/0	WIREGLASS					
12	4/0x27/0	INSULATED					
13	4/0x27/0	NONE					
14	4/0x27/0	2/2					
15	4/0x27/0	2/4					
16	4/0x27/0	6/6					
17	4/0x27/0	8/8					
18	4/0x27/0	ALARM					
19	4/0x27/0	SCREEN					
20	4/0x27/0	SHUTTER					
21	4/0x27/0	NONE					
22	4/0x27/0						
23	4/0x27/0						
24	4/0x27/0						
25	4/0x27/0						
26	4/0x27/0						
27	4/0x27/0						
28	4/0x27/0						
29	4/0x27/0						
30	4/0x27/0						
31	4/0x27/0						
32	4/0x27/0						
33	4/0x27/0						
34	4/0x27/0						
35	4/0x27/0						
36	4/0x27/0						
37	4/0x27/0						
38	4/0x27/0						
39	4/0x27/0						
40	4/0x27/0						
41	4/0x27/0						
42	4/0x27/0						
43	4/0x27/0						
44	4/0x27/0						
45	4/0x27/0						
46	4/0x27/0						
47	4/0x27/0						
48	4/0x27/0						
49	4/0x27/0						
50	4/0x27/0						
51	4/0x27/0						
52	4/0x27/0						
53	4/0x27/0						
54	4/0x27/0						
55	4/0x27/0						
56	4/0x27/0						
57	4/0x27/0						
58	4/0x27/0						
59	4/0x27/0						
60	4/0x27/0						
61	4/0x27/0						
62	4/0x27/0						
63	4/0x27/0						
64	4/0x27/0						
65	4/0x27/0						
66	4/0x27/0						
67	4/0x27/0						
68	4/0x27/0						
69	4/0x27/0						
70	4/0x27/0						
71	4/0x27/0						
72	4/0x27/0						
73	4/0x27/0						
74	4/0x27/0						
75	4/0x27/0						
76	4/0x27/0						
77	4/0x27/0						
78	4/0x27/0						
79	4/0x27/0						
80	4/0x27/0						
81	4/0x27/0						