



**FLOOR PLAN**  
SCALE: 1/8" = 1'-0"

AREA BY USE:  
TOTAL AREA: 20,000 SQ. FT.  
COVERED DRIVEWAY: 1,200 SQ. FT.  
CHURCH GROSS AREA: 18,800 SQ. FT.

PLUMBING FIXTURE COUNT:  
PER LA STATE PLUMBING CODE 2000 EDITION  
OCCUPANT LOAD FOR CHURCH BASED ON NUMBER OF SEATS  
534 SEATS AVAILABLE  
MENS TOILETS REQUIRED = 4  
MENS TOILETS PROVIDED = 6 (5 TOILETS AND 6 URINALS)  
MENS LAVATORY REQUIRED = 3  
FEMALE TOILETS REQUIRED = 4  
FEMALE TOILETS PROVIDED = 11  
FEMALE LAVATORY REQUIRED = 3  
FEMALE LAVATORY PROVIDED = 7

T.O.S. = 11.0

COVERED DRIVEWAY

RECEPTION

FOYER

HALLWAY

CHOIR ROOM

MEETING RM

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

HALLWAY

MEETING RM

GENERAL NOTES

1. INSULATION AND INSULATION ASSEMBLIES SHALL MEET THE REQUIREMENTS OF SECTION 7.19.

2. A CONCEALED INSULATION SHALL HAVE A FLAME SPREAD OF 0.25 AND SMOKE DEVELOPED INDEX OF 0.450, EXCEPT THAT IN COMBUSTIBLE (WOOD FRAME) CONSTRUCTION.

3. FACING SHALL COMPLY WITH IBC 2009.

4. THRESHOLDS SHALL BE NOT MORE THAN 1/2" IN HEIGHT AND SHALL BE BEVELLED IF MORE THAN 1/4".

5. CONTRACTOR TO VERIFY ALL SITE CONDITIONS, BUILDING LOCATIONS, AND DIMENSIONS PRIOR TO CONSTRUCTION.

6. MATERIALS SHALL BE NEW AND U.L. LISTED.

7. NO WORK SHALL BE CONCEALED UNTIL APPROVED BY LOCAL INSPECTORS.

8. CONSTRUCTION SHALL COMPLY WITH ALL PARISH, STATE, AND LOCAL CODES.

9. CONTRACTOR TO GUARANTEE WORK FOR ONE YEAR.

10. EXTERIOR CAULKING SHALL BE SHERWIN WILLIAMS OR EQUIVALENT. ALL WORK TO RECEIVE 3 COATS. COLOR SELECTION BY OWNER.

11. PROVIDE CLEANUP ON A REGULAR BASIS. NO TRASH STORED IN BUILDING.

12. ALL BATT INSULATION SHALL HAVE A CLASS 1/4" (0.25) FLAME SPREAD IN COMPLIANCE WITH APPLICABLE CODE.

13. USE 6" STUDS OR 4" STRAGGERED STUDS AT ALL PLUMBING WALLS.

14. PROVIDE GALVANIZED METAL PAN WITH DRAIN AT WATER HEATER LOCATION.

15. ALL CORNERS SHALL BE PROPERLY BRACED FOR WIND LOADS. A 48" SHEATHING SHALL BE PROVIDED EVERY 20 FEET OR WALL LENGTH.

16. INTERIOR LOCKS ON DOORS IN MEANS OF EGRESS SHALL NOT REQUIRE THE USE OF A KEY. SPECIAL KNOWLEDGE OR SPECIAL DEVICE TO OPEN IN THE DIRECTION OF EGRESS. ALL DOORS SHALL HAVE LEVER TYPE HANDLES.

17. INTERIOR WALLS AND CEILINGS SHALL HAVE A FLAME SPREAD OF 0.25 AND A SMOKE DEVELOPMENT RATING OF 0.450.

18. ALL WORK SHALL COMPLY WITH THE LATEST EDITION OF ALL LOCAL, STATE, AND NATIONAL CODES COVERING THE TYPE OF WORK BEING PERFORMED.

19. PROVIDE PORTABLE FIRE EXTINGUISHERS IN ACCORDANCE WITH NFPA 1.01. SEE APPENDIX "E" OF NFPA 1.01 FOR DISTRIBUTION OF EXTINGUISHERS.

20. ALL FIRE WALLS SHALL EXTEND TIGHT TO ROOF DECK AND BE SEALED WITH AN APPROVED FIRE GULCH.

21. ALL ELECTRICAL, MECHANICAL, AND PLUMBING MATERIALS REQUIRING PRE VALUUS SHALL BE FIRE CALKED.

22. PENETRATIONS THROUGH STAIR CONSTRUCTION SHALL BE SEALED WITH A MATERIAL CAPABLE OF PREVENTING THE PASSAGE OF FLAMES AND HOT GASES WHEN TESTED IN ACCORDANCE WITH ASTM E91, E91.4, AND ASTM E119, E119.4.

23. SERVICE COUNTERS SHALL HAVE A HCP ACCESSIBLE WRITING SURFACE. MAX. 36" FROM F.F. (ADAAG MANUAL 1998, PG. 1.35)

WINDOW SCHEDULE

MARK SIZE WINDOW TYPE FRAME GLASS REMARKS

A OVERALL UNIT SIZE = 410 W x 148 H ALUMINUM STOREFRONT LOW E SEE EXT. ELEVATIONS FOR ARCH TOP

B OVERALL UNIT SIZE = 410 W x 168 H ALUMINUM STOREFRONT LOW E SEE EXT. ELEVATIONS FOR ARCH TOP

C OVERALL UNIT SIZE = 610 W x 101.0 H ALUMINUM STOREFRONT LOW E SEE EXT. ELEVATIONS FOR ARCH TOP

D EXTERIOR WINDOW SYSTEM SHALL BE CAPABLE OF RESISTING 130 MPH WIND LOAD.

GENERAL NOTES

1. INSULATION AND INSULATION ASSEMBLIES SHALL MEET THE REQUIREMENTS OF SECTION 7.19.

2. A CONCEALED INSULATION SHALL HAVE A FLAME SPREAD OF 0.25 AND SMOKE DEVELOPED INDEX OF 0.450, EXCEPT THAT IN COMBUSTIBLE (WOOD FRAME) CONSTRUCTION.

3. FACING SHALL COMPLY WITH IBC 2009.

4. THRESHOLDS SHALL BE NOT MORE THAN 1/2" IN HEIGHT AND SHALL BE BEVELLED IF MORE THAN 1/4".

5. CONTRACTOR TO VERIFY ALL SITE CONDITIONS, BUILDING LOCATIONS, AND DIMENSIONS PRIOR TO CONSTRUCTION.

6. MATERIALS SHALL BE NEW AND U.L. LISTED.

7. NO WORK SHALL BE CONCEALED UNTIL APPROVED BY LOCAL INSPECTORS.

8. CONSTRUCTION SHALL COMPLY WITH ALL PARISH, STATE, AND LOCAL CODES.

9. CONTRACTOR TO GUARANTEE WORK FOR ONE YEAR.

10. EXTERIOR CAULKING SHALL BE SHERWIN WILLIAMS OR EQUIVALENT. ALL WORK TO RECEIVE 3 COATS. COLOR SELECTION BY OWNER.

11. PROVIDE CLEANUP ON A REGULAR BASIS. NO TRASH STORED IN BUILDING.

12. ALL BATT INSULATION SHALL HAVE A CLASS 1/4" (0.25) FLAME SPREAD IN COMPLIANCE WITH APPLICABLE CODE.

13. USE 6" STUDS OR 4" STRAGGERED STUDS AT ALL PLUMBING WALLS.

14. PROVIDE GALVANIZED METAL PAN WITH DRAIN AT WATER HEATER LOCATION.

REVISIONS

SCALE: AS NOTED

JOB#: 2128

DATE: 01-27-12

SHEET 9

A-1

OF 21

2528

OLD SPANISH TRAIL

SLIDELL, LA

70461

LIVING THE WORD

INTERNATIONAL

ARCHITECTURE

ENGINEERING

PLANNING

STUDIES

INVESTIGATION

EXPERT WITNESSES

WWW.DAMMONENGINEERING.COM

554 OLD SPANISH TRAIL

SUDBELL, LA 70456

OFFICE: 985-649-5632

FAX: 985-641-5950

WWW.DAMMONENGINEERING.COM

DAMMON ENGINEERING, INC.

CHIEF ENGINEER

EMMETT DAMMON, P.E.

CHIEF ARCHITECT

ROBERT WILTSE

ARCHITECTURE

ENGINEERING

PLANNING

STUDIES

INVESTIGATION

EXPERT WITNESSES

WWW.DAMMONENGINEERING.COM

554 OLD SPANISH TRAIL

SUDBELL, LA 70456

OFFICE: 985-649-5632

FAX: 985-641-5950

WWW.DAMMONENGINEERING.COM

DAMMON ENGINEERING, INC.

CHIEF ENGINEER

EMMETT DAMMON, P.E.

REVISIONS

SCALE: AS NOTED

JOB#: 2128

DATE: 01-27-12

SHEET 9

A-1

OF 21

2528

OLD SPANISH TRAIL

SLIDELL, LA

70461

LIVING THE WORD

INTERNATIONAL

ARCHITECTURE

ENGINEERING

PLANNING

STUDIES

INVESTIGATION

EXPERT WITNESSES

WWW.DAMMONENGINEERING.COM

554 OLD SPANISH TRAIL

SUDBELL, LA 70456

OFFICE: 985-649-5632

FAX: 985-641-5950

WWW.DAMMONENGINEERING.COM

DAMMON ENGINEERING, INC.

CHIEF ENGINEER

EMMETT DAMMON, P.E.

CHIEF ARCHITECT

ROBERT WILTSE

ARCHITECTURE

ENGINEERING

PLANNING

STUDIES

INVESTIGATION

EXPERT WITNESSES

WWW.DAMMONENGINEERING.COM

554 OLD SPANISH TRAIL

SUDBELL, LA 70456

OFFICE: 985-649-5632

FAX: 985-641-5950

WWW.DAMMONENGINEERING.COM

DAMMON ENGINEERING, INC.

CHIEF ENGINEER

EMMETT DAMMON, P.E.