PLUMBING FIXTURE SPECIFICATIONS

PLUMBING FIXTURES

WATER CLOSET (W.C.–1): KOHLER KINGSTON MODEL K–4330 WALL MOUNTED TOILET, FLUSH VALVE, ELONGATED BOWL, VITREOUS CHINA, 1.6 GPF. SLOAN ROYAL OPTIMA SYSTEMS MODEL #111–SMO LOW CONSUMPTION, 1.6 GPF, BATTERY POWERED FLUSHOMETER, EXPOSED, DIAPHRAM TYPE, SIDE MOUNT SENSOR OPERATED, TOUCHLESS INFRARED SENSOR OPERATED WITH OVERRIDE BUTTON, CHROME PLATED FINISH. KOHLER LUSTA COMMERCIAL TOILET SEAT K–4667–C EXTRA HEAVY ELONGATED OPEN FRONT SEAT WITH CHECK HINGE, LESS COVER. (ADA COMPLIANT)

URINAL (U.–1): KOHLER STANWELL MODEL K–4972–ET URINAL, VITREOUS CHINA, 1.0 GPF, BLOW–OUT. SLOAN ROYAL OPTIMA SYSTEMS MODEL 180–1.0–SMO, LOW CONSUMPTION 1.0 GPF, SIDE MOUNT SENSOR OPERATED, BATTERY POWERED FLUSHOMETER, EXPOSED, DIAPHRAGM TYPE, TOUCHLESS INFRARED SENSOR OPERATED WITH OVERRIDE BUTTON, CHROME PLATED FINISH. (ADA COMPLIANT)

LAVATORY (L.–1): KOHLER CAXTON MODEL K–2211 UNDERCOUNTER MOUNTED LAVATORY, VITREOUS CHINA, 19"x15" OVAL, WITH OVERFLOW AND CLAMPS. TOTO AXIOM ECO–POWER FAUCET MODEL #TEL3GK60#CP, SINGLE SUPPLY, SINGLE HOLE, INFRARED SENSOR ACTIVATED, ANTI–SCALD THERMAL MIXING, HYDRO–POWER CHARGE WITH BATTERY BACK–UP. (ADA COMPLIANT)

LAVATORY (L.–2): KOHLER CAMBER MODEL K–2349 UNDERCOUNTER MOUNTED LAVATORTY, VITREOUS CHINA, 14" DIAMETER, WITHOUT OVERFLOW, INCLUDES CLAMP ASSEMBLY. CHICAGO FAUCETS HYTRONIC MODEL 116.111.21.1, SINGLE HOLE, DECK MOUNTED, DUAL SUPPLY WITH CHECK VALVES ON INLETS, INFRARED SENSORS (12 VOLT AC TRANSFORMER REQUIRED), ABOVE DECK HERMETICALLY SEALED ELECTRONICS, 0.5 GPM OUTLET, POLISHED CHROME PLATED FINISH. (ADA COMPLIANT)

LAVATORY (L.–3): AMERICAN STANDARD COMRADE MODEL 0124.024 WALL HUNG LAVATORY, VITREOUS CHINA, WALL HANGER, REAR OVERFLOW. MOEN MODEL CA8948 CLINIC FAUCET, WRIST BLADE HANDLES, CHROME FINISH, 2.2 GPM MAX AERATOR, PERFORATED GRID DRAIN. (ADA COMPLIANT)

LAVATORY (L.–4): TOTO MODEL LT401.8 SELF–RIMMING LAVATORY, VITEREOUS CHINA, 17½"x20" OVAL. WITH 8" FAUCET CENTERS AND CONCEALED FRONT OVERFLOW. MOEN MODEL CA8924 WIDESPREAD FAUCET WITH METAL GRID DRAIN, LEVER STYLE HANDLES, METAL CONSTRUCTION WITH CHROME PLATED FINISH, DESIGNED TO BE INSTALLED ON 8"CENTERS, 2.2 GPM MAX AERATOR. (ADA COMPLIANT)

SHOWER (SH.–1): ACCESSIBILITY PROFESSIONAL MODEL APTXSS369 8 BF 625, 36"x36"x76½" HEIGHT, WHITE FIBERGLASS WITH 2 – INTEGRAL SOAP LEDGES, TO INCLUDE KOHLER K–9132 POLISHED CHROME SHOWER DRAIN WITH PERFORATED STRAINER. KOHLER CORALAIS MODEL K–T15611–4 SHOWER MIXING VALVE FAUCET TRIM WITH LEVER HANDLE, METAL CONSTRUCTION WITH POLISHED CHROME FINISH AND KOHLER K–304–K–NA RITE TEMP VALVE WITHOUT STOPS. (FOR ADA COMPLIANT – ACCESSIBILITY PROFESSIONALS MODEL APES3698BF625 ADA TRANSFER SHOWER STALL, 36"x36", WHITE GELCOAT FIBERGLASS, INCLUDES GRAB BARS, FOLDING SEAT, CURTAIN ROD AND DRAIN. SYMMONS MODEL 25–300–B30–V TEMPTROL II SHOWER SYSTEM WITH HAND SPRAY, PRESSURE BALANCING MIXING VALVE WITH 5' FLEXABLE METAL HOSE, IN–LINE VACUUM BREAKER, 30" SLIDE BAR FOR HAND SHOWER MOUNTING, CHROME PLATED FINISH, 2.5 GPM FLOW RATE.) CONTRACTOR SHALL VERIFY ADA LOCATIONS WITH ARCHITECTURAL DRAWINGS.

KITCHEN SINK (K.S.–1): ELKAY MODEL LR–3319 GOURMET DOUBLE COMPARTMENT SINK, 18 GAUGE TYPE 304 STAINLESS STEEL, 33"x19"x8" DEEP, EACH BOWL 14"x14", WITH LK–335 BASKET STRAINER. KOHLER FORTE MODEL D–10430 REMOTE VALVE KITCHEN SINK FAUCET WITH 9" SWING SPOUT REACH, ADA COMPLIANT REMOTE LEVER HANDLE, POLISHED CHROME FINISH, 2.2 GPM MAXIMUM FLOW RATE.

LAUNDRY SINK (L.S.–1): SWAN CORPORATION MODEL MF–2W DOUBLE LAUNDRY TUB, WHITE SWANSTONE VERITEK WITH WALL MOUNT BRACKET ASSEMBLY, LEGS, FACTORY DRAIN, KOHLER K–15270–B POLISHED CHROME FAUCET WITH BLADE HANDLES.

⚠1 SINK (H.W.S.–1): KOHLER K–3373 SELF RIMMING SINK, 18 GUAGE STAINLESS STEEL, SINGLE COMPARTMENT, 33"x28"x8¼" DEEP, K–8813 STAINLESS STEEL SINK STRAINER WITH TAILPIECE, K–15171–F FAUCET WITH LEVER HANDLES, CHROMEPLATED. PROVIDE ZURN MODEL Z1176 DURA–COATED CAST IRON HAIR AND SOLIDS INTERCEPTOR IN LIEU OF FIXTURE P–TRAP.

SERVICE SINK (S.S.–1): FIAT MOLDED STONE MODEL MSB–3624 MOP SERVICE BASIN, 36"x24"x10" DEEP, WITH INTEGRAL MOLDED SHELF, STAINLESS STEEL DRAIN BODY FOR 3" DRAIN PIPE, AND COMBINATION DOME STRAINER AND STAINLESS STEEL LINT BASKET. CHICAGO FAUCET MODEL 897–CP WALL MOUNTED SERVICE SINK FAUCET WITH ATMOSPHERIC VACUUM BREAKER SPOUT WITH PAIL HOOK AND WALL BRACE, SOLID BRASS CONSTRUCTION, CHROME PLATED FINISH, LEVER HANDLES, ¾" MALE THREAD OUTLET, INTEGRAL SUPPLY STOPS AND BACK CHECKS.

SERVICE SINK (S.S.–2): FIAT MOLDED STONE MODEL MSB–2424 MOP SERVICE BASIN, 24"x24"x10" DEEP, WITH STAINLESS STEEL DRAIN BODY FOR 3" DRAIN PIPE, AND COMBINATION DOME STRAINER AND STAINLESS STEEL LINT BASKET. CHICAGO FAUCET MODEL 897–CP WALL MOUNTED SERVICE SINK FAUCET WITH ATMOSPHERIC VACUUM BREAKER SPOUT WITH PAIL HOOK AND WALL BRACE, SOLID BRASS CONSTRUCTION, CHROME PLATED FINISH, LEVER HANDLES, ¾" MALE THREAD OUTLET, INTEGRAL SUPPLY STOPS AND BACK CHECKS.

DRINKING FOUNTAIN (D.F.–1): HALSEY TAYLOR MODEL OVL–11 BARRIER–FREE BI–LEVEL WALL MOUNTED DRINKING FOUNTAIN, STAINLESS STEEL, WITH BRUSHED SATIN FINISH, OVAL SHAPED FOUNTAINS, WITH MOUNTING FRAME.

ELECTRICAL WATER COOLER (E.W.C.–1): HALSEY TAYLOR MODEL HTV8BL–Q BARRIER–FREE BI–LEVEL WALL MOUNTED WATER COOLERS, SELF–CONTAINED, RECTANGULAR SHAPED FOUNTAINS, MOLDED TWO–TONE GRAY POLMER FINISH, REFRIGERATION SYSTEM TO DELIVER 7.5 GPH OF 50°F WATER AT 80°F INLET TEMP, 4.0 F.L. AMPS, 120 VOLT, 60 HZ, 1ø.

ELECTRICAL WATER COOLER (E.W.C.–2): HALSEY TAYLOR MODEL HTV8–Q BARRIER–FREE WALL MOUNTED WATER COOLER, SELF CONTAINED, RECTANGULAR SHAPED FOUNTAIN, MOLDED TWO–TONE GRAY POLMER FINISH, REFRIGERATION SYSTEM TO DELIVER 7.5 GPH OF 50°F WATER AT 80°F INLET TEMP, 4.0 F.L. AMPS, 120 VOLT, 60 HZ, 1ø.

EMERGENCY EYEWASH (E.W.–1): HAWS MODEL 7360BT EYEWASH, WALL MOUNTED, STAINLESS STEEL BOWL, CAST ALUMINUM CHROMATE PROTECTED WALL BRACKET, YELLOW PLASTIC POP–OFF DUST COVER TAILPIECE, TRAP AND SIGN. FURNISH WITH TEMPERED WATER BLENDING SYSTEM MODEL TWBS.EW WITH RECESSED CABINET.

SUPPLIES, TRAPS AND MISCELLANEOUS

SUPPLIES: FOR CONCEALED APPLICATIONS, CONNECT WATER CLOSETS, LAVATORIES AND SINKS WITH McGUIRE BV 2165 CC BALL VALVE ANGLE STOP WITH SS–16 16" S.S. CONNECTOR FOR LAVATORY, SINKS; McGUIRE BV 2166 CC BALL VALVE ANGLE STOP WITH SS–12 12" STAINLESS STEEL CONNECTOR TAILPIECE AND INSULATE WASTE AND SUPPLIES AT ALL HANDICAPPED LAVATORIES WITH McGUIRE PW 2150 PRE–WRAP INSULATION KIT). CONCINNITY MODEL NO. 19–L3 "IN WALL STOPS" SATIN CHROME WITH BRUSHED BRASS ACCENT AT WALL MOUNTED LAVATORY. WHERE EXPOSED, PIPING TRIM FINISH SHALL MATCH FIXTURE FINISH.

TRAPS: McGUIRE B8902 CHROME PLATED CAST BRASS WITH CLEANOUT PLUG AND TUBING OUTLET WITH TRAP ADAPTOR & ESCUTCHEON. (B–155WC FOR OFFSET TAILPIPE)

STRAINERS: McGUIRE 155A CAST BRASS SOLID TOP OPEN GRID DRAIN WITH 17 GAUGE 1¼" OVERFLOW DRAIN TAILPIECE FOR LAVS WITH OVERFLOW OR McGUIRE PRODRAIN CAST BRASS GRID DRAIN WITH 17 GAUGE SEAMLESS BRASS 1¼" TAILPIECE FOR LAVATORIES WITHOUT OVERFLOWS.

CLEANOUT (C.O.): J.R. SMITH FIG. 4472 (WALL), FIG. 4043 (FLR. INSIDE), FIG. 4880 (EXTERIOR).

FLOOR DRAIN (F.D.): J.R. SMITH FIG. 2005–Y CAST IRON DRAIN, FLASHING COLLAR WITH 8" NICKEL–BRONZE TOP (TOILET ROOMS). J.R. SMITH FIG. 2120–Y–AREWITH ALUMINUM SEDIMENT BUCKET AND STAINLESS STEEL GRATE (KITCHEN/BARS). J.R. SMITH NO. 2233–Y 11½" CAST IRON GRATE (MECHANICAL ROOM).

FLOOR SINK (F.S.): COMMERCIAL ENAMELING CAST IRON DRAIN, 10" DEEP WITH ENAMELED CAST IRON HALF GRATE EXCEPT WHERE INDICATED OTHERWISE ON PLUMBING DRAWINGS.

HOSE BIBB (H.B.): ACORN NO. 8121, ¾" HOSE THREADED VACUUM BREAKER WITH REMOVABLE WHEEL HANDLE.

RECESSED HOSE BIBB (R.H.B.): WOODFORD MODEL B65 WITH FREEZE PROTECTION.

CLOTHES WASHER BOX (C.W.B.–1): GUY GREY MODEL T200 WHITE 20 GAUGE BOX AND FACE PLATE, DOMESTIC VALVES, 2" DRAIN.

ICE MAKER BOX (I.M.B.–1): GUY GREY BI M875 WITH ½" x ¼" COMPRESSION ANGLE STOP. FURNISH WITH 3'–0" OF ¼" COILED TUBING.

DISHWASHER (D.W.–1): AMER–FLEX AIR–GAP SINK FITTING WITH STOP AND HOSE.

ROOF DRAIN (R.D.): J.R. SMITH NO. 1010–Y CAST IRON BODY AND DOME WITH FLASHING COLLAR AND UNDERDECK CLAMP.

OVERFLOW ROOF DRAIN (O.R.D.): J.R. SMITH NO. 1080–Y CAST IRON BODY AND DOME WITH FLASHING COLLAR AND UNDERDECK CLAMP.

REFER TO ARCHITECTURAL FOR EXACT MOUNTING HEIGHTS.

FINAL COLOR, FIXTURE, TRIM AND ACCESSORIES SHALL BE APPROVED BY ARCHITECT AND INTERIORS PRIOR TO FIXTURE RELEASE.

⚠1 PLUMBING FIXTURES IN A.D.A. UNIT SHALL COMPLY IN ALL RESPECTS WITH A.D.A. GUIDELINES.

PLUMBING FIXTURE SCHEDULE

ABBR.	FIXTURE	ROUGH–IN SIZES (INCHES)					REMARKS
		HW	CW	V	TRAP	S OR W	
W.C.–1	WATER CLOSET	–	1	2	–	4	FLUSH VALVE, WALL HUNG
U.–1	URINAL	–	¾	1½	–	2	FLUSH VALVE, WALL HUNG
L.–1	LAVATORY	½	½	1½	1¼x1½	1½	UNDERCOUNTER MOUNTED
L.–2	LAVATORY	½	½	1½	1¼x1½	1½	UNDERCOUNTER MOUNTED
L.–3	LAVATORY	½	½	1½	1¼x1½	1½	WALL HUNG
L.–4	LAVATORY	½	½	1½	1¼x1½	1½	COUNTERTOP
SH.–1	SHOWER	½	½	1½	2	2	PRE–FORMED STALL
K.S.–1	KITCHEN SINK	½	½	1½	1½	2	COUNTERTOP
L.S.–1	LAUNDRY SINK	½	½	1½	1½	2	WALL HUNG
H.W.S.–1	SINK	½	½	1½	1½	2	COUNTER TOP
S.S.–1	SERVICE SINK	½	½	2	3	3	FLOOR MOUNTED
S.S.–2	SERVICE SINK	½	½	2	3	3	FLOOR MOUNTED
D.F.–1	DRINKING FOUNTAIN	–	½	1½	1½	1½	WALL HUNG
E.W.C.–1	ELECTRIC WATER COOLER	–	½	1½	1¼	1½	WALL HUNG
E.W.C.–2	ELECTRIC WATER COOLER	–	½	1½	1¼	1½	WALL HUNG
E.W.–1	EMERGENCY EYEWASH	½	½	1½	1½	1½	WALL HUNG

NOTES:

1. PLUMBING FIXTURES SHALL COMPLY WITH STATE AND COUNTY WATER CONSERVATION REQUIREMENTS.
2. SHOWER VALVES SHALL BE PRESSURE BALANCING OR THERMOSTATIC CONTROL TYPE IN ACCORDANCE WITH THE LOUISIANA STATE PLUMBING CODE.

THE SAENGER THEATRE RENEWAL PROJECT

142 North Rampart Street
New Orleans, LA

Client
Saenger Theatre Redevelopment Company
200 West Loop South, Suite
1040 Houston TX 77027

Architect
MARTINEZ+JOHNSON
ARCHITECTURE
1412 Eye St., NW
Washington, DC 20005
202.333.4480

Structural Engineer
Shawn J. Franke, P.E.
549 Heimer Road San
Antonio TX 78232
210.979.7900

Theatre Consultant
Schuler Shook
123 Third Street North #210
Minneapolis, MN 55401
612.339.5958

Acoustical Engineer
Akustiks
93 North Main Street South
Norwalk, CT 06854
202.299.1904

MEP Engineer
JBA Consulting Engineers, Inc.
3525 N. Causeway BLVD. Suite
500 Metairie, LA 70002
504.830.0139

Civil Engineer
Linfield, Hunter, & Junius, Inc.
3608 18th Street Suite 200
Metairie, LA 70002
504.833.5300

Architectural Historian
EHT Traceries, Inc.
1121 Fifth Street NW
Washington, DC 20001
202.393.1199

THESE DRAWINGS, SPECIFICATIONS, AND OTHER DOCUMENTS, (COLLECTIVELY, THE "DOCUMENTS") INCLUDING WITHOUT LIMITATION ELECTRONIC VERSIONS THEREOF AND THE IDEAS, DESIGNS, AND ARRANGEMENTS REPRESENTED THEREBY, ARE AND SHALL REMAIN THE PROPERTY OF MARTINEZ & JOHNSON ARCHITECTURE PC, AS DEFINED BY APPLICABLE CONTRACTUAL AGREEMENTS ("THE AGREEMENTS") AND AS PROTECTED BY THE COPYRIGHT STATUTES OF THE UNITED STATES. USE OF THE DOCUMENTS SHALL BE STRICTLY LIMITED TO THE PROJECT FOR WHICH THEY WERE PREPARED AND DEVELOPED ("THE PROJECT") PER THE TERMS OF THE AGREEMENTS. NO PART OF THE DOCUMENTS SHALL BE COPIED, DISCLOSED TO OTHERS, OR USED IN CONNECTION WITH ANY OTHER WORK OR PROJECT, OR BY ANY OTHER PERSONS FOR ANY PURPOSES, OTHER THAN THE COMPLETION OF THE PROJECT, WITHOUT THE SPECIFIC WRITTEN AUTHORIZATION OF MARTINEZ & JOHNSON ARCHITECTURE PC. THE DOWNLOADING, OPENING, OR VIEWING OF ELECTRONIC VERSIONS OF THE DOCUMENTS OR VISUAL CONTACT WITH ANY PRINTED FORM THEREOF SHALL CONSTITUTE CONCLUSIVE EVIDENCE OF ACCEPTANCE OF THESE RESTRICTIONS.

7502

DATE:	No.:	ISSUE:
02.19.10	1	PERMIT SET
04.02.10	2	GMP CONTRACT SET

DATE:	No.:	REVISION:
11.11.10		CONTRACT SET

SHEET TITLE:
PLUMBING FIXTURE SCHEDULE AND SPECIFICATIONS

09.0384

P-0.03

ISSUED FOR PERMIT

© 2010 M+J

P:\09-0394 Saenger Theatre\CRAWINGS\PLUMBING\09039d_P003.dwg, 11/19/2010 3:37:39 PM, jjohnson