



Precast Concrete
Never Looked So Good!

www.gaineysconcrete.com

December 2, 2016

M. Natal Contractor, Inc.
Attn: Patricia

Re: City of Slidell Sidewalk Improvements

In reference to the above mentioned project, Precast Reinforced Concrete Drainage Structures manufactured by Gainey's Concrete Products, Holden, LA, meet or exceed all reinforcement requirements of the LA DOTD Specifications for Roads and Bridges. The concrete for some structures will have a minimum compressive strength of 5,000 PSI @ 28 days. For reinforcing steel detail, please refer to Gainey's Concrete Products Typical Catch Basin Specification Sheet. In addition, joints for some structures meet or exceed all requirements for flexible plastic gaskets and Louisiana DOTD specifications.

If you have any questions or need assistance, please don't hesitate to contact me.

Sincerely,

Brandon Frierson



Brandon Frierson
Gainey's Concrete Products, Inc.

Enc:
Gainey's Concrete Typical Catch Basin Details
Shop Drawings
4618 Frame Casting Specifications
6258 Cover Casting Specifications
Ram-Nek Joint Sealant Data Sheet

PRECAST DRAIN UNITS	
SIZES (ID)	1.5' X 1.5' 2' X 2.5' 2' X 3' 3' X 3' 4' X 2' 4' X 3' 4' X 4'
MAX HT	AS <input checked="" type="checkbox"/>
FEET	in ² /ft.
	8 0.20

- NOTES:
1. AREA STEEL CALCULATED WITH ENGINEERED MAT & REBAR DESIGNED TO MEET REQUIRED AREA OF STEEL. ALL GRADE 60 MINIMUM.
 2. AREA OF STEEL APPLIES TO BOTH DIRECTIONS & AT ALL LOCATIONS.
 3. CLASS 1 CONCRETE WITH DESIGN STRENGTH OF 4500 PSI AT 28 DAYS.
 4. PIPE TO BE GROUTED IN BY CONTRACTOR AFTER INSTALLATION.

APPROVED FOR PRODUCTION: _____
 APPROVED FOR PRODUCTION
 W/ CHANGES: _____
 RESUBMITTAL REQUIRED: _____



gaineys
CONCRETE PRODUCTS



28021 Colket-Vail Road
 Phone (225) 567-2700

Holden, LA
 Fax (225) 567-3089

www.gaineyconcrete.com

TYPICAL CATCH BASIN DETAIL

SCALE: NOT TO SCALE

DATE: 9/14/12

DRAWN BY: DC

CHECKED BY: CG

Structure Product Detail


Item	Product	Qty	Product Description	Yards	Weight
Top 3	FT3X3	1	Flat Top 36" x 36" w/ 4618	0.19	755
Base	CB2X2-6	1	CB2X2-6 BASE x 32"	0.53	2,136
	1 1/4 TS	1	1 1/4" Tar Seal	0.00	0
	USF 461	1	USF 4618 Frame (24" x 24")	0.00	0
	USF 625	1	USF 6258 Grate (24" x 24")	0.00	0
Structure Totals				0.72	2,891

Elevations

Rim	Elev	Angle	Pipe	Hole Type	Hole" Height	Hole" Width	Up"	Item
(1)	0	90	15 RCP	HOLE	24	24	0	Base
(2)	0	270	15 RCP	HOLE	24	24	0	Base
(3)	0	0			0	0	0	
(4)	0	0			0	0	0	
(5)	0	0			0	0	0	
(6)	0	0			0	0	0	
(7)	0	0			0	0	0	
(8)	0	0			0	0	0	

Description: CB2X2-6 BASE x 32"
 Product ID: CB2X2-6B
 Item: Base Step Location:

	Inside Area View	Wall
Rim to Invert	3.00'	7.00"
Less Casting	3.00'	
Invert to Floor	0.19'	Sumpp
Adjustment (Brick/Mort.)	0.02	
		3.67'



15 RCP/HOLE
 H 24" / W 24.00"
 L 0 / R 0
 Up: 0" / Ang 90

15 RCP/HOLE
 H 24" / W 24.00"
 L 0 / R 0
 Up: 0" / Ang 270

----- Side 24.0" -----

----- Side 24.0" -----


Structure Product Detail

Item	Product	Qty	Product Description	Yards	Weight
Top 3	FT3X3	1	Flat Top 36" x 36" w/ 4618	0.19	755
Base	CB2X2-6	1	CB2X2-6 BASE x 32"	0.53	2,136
	1 1/4 TS	1	1 1/4" Tarseal	0.00	0
	USF 461	1	USF 4618 Frame (24" x 24")	0.00	0
	USF 625	1	USF 6258 Grate (24" x 24")	0.00	0
Structure Totals				0.72	2,891

Elevations


Rim	Elev	Angle	Pipe	Hole Type	Hole Height	Hole Width	Up"	Item
(1)	0	90	15 RCP	HOLE	24	24	0	Base
(2)	0	270	15 RCP	HOLE	24	24	0	Base
(3)								
(4)								
(5)								
(6)								
(7)								
(8)								

Description: CB2X2-6 BASE x 32"
 Product ID: CB2X2-6B
 Item: Base Step Location:



----- Side 24.0" -----

Inside Area View



Item	Description	Height	Width	Area
Rim to Invert		3.00'		
Less Casting		3.00'		
Invert to Floor		0.19'		
Adjustment (Block/Mort.)		0.02		
Precast Height		3.17'		
Floor		6.00"		
Plus Floor		3.67'		
Wall		7.00"		
Sump		0.00'		

Structure Product Detail



Item	Product	Qty	Product Description	Yards	Weight
Top 3	FT4X3	1	Flat Top 4' x 3' w/ 4618	0.22	900
Base	CB2X3B	1	CB2X3 BASE x 33"	0.81	3,229
	1 1/4 TS	1	1 1/4" Tarsenal	0.00	0
	USF 461	1	USF 4618 Frame (24" x 24")	0.00	0
	USF 625	1	USF 6258 Grate (24" x 24")	0.00	0
Structure Totals				1.03	4,129

Elevations

Rim	Elev	Angle	Pipe	Hole Type	Hole Height	Hole Width	Up"	Item
(1)	0	270	15 RCPA	Hole	19	26	0	Base
(2)	0	0			0	0	0	
(3)	0	0			0	0	0	
(4)	0	0			0	0	0	
(5)	0	0			0	0	0	
(6)	0	0			0	0	0	
(7)	0	0			0	0	0	
(8)	0	0			0	0	0	

Description: CB2X3 BASE x 33"
 Product ID: CB2X3B
 Item: Base Step Location:

Inside Area View	Wall	Summp
Rim to Invert	3.00'	6.00"
Less Casting	3.00'	
Invert to Floor	0.25'	
Adjustment (Brick/Mort.)	0.00	
Precast Height	3.25'	
Floor	6.00"	
Plus Floor	3.75'	



----- Side 24.0" -----
 ----- Side 36.0" -----


Structure Product Detail

Item	Product	Qty	Product Description	Yards	Weight
Top 3	FT4X3	1	Flat Top 4' x 3' w/ 4618	0.22	900
Base	CB2X3B	1	CB2X3 BASE x 33"	0.77	3,083
	1 1/4 TS	1	1 1/4" Tarseal	0.00	0
	USF 461	1	USF 4618 Frame (24" x 24")	0.00	0
	USF 625	1	USF 6258 Grate (24" x 24")	0.00	0
Structure Totals				0.99	3,983

Elevations

Rim	Elev	Angle	Pipe	Hole Type	Hole Height	Hole Width	Up"	Item
(1)	0	270	15 RCPA	Hole	19	26	0	Base
(2)	0	90	15 RCPA	Hole	19	26	0	Base
(3)	0	0			0	0	0	
(4)	0	0			0	0	0	
(5)	0	0			0	0	0	
(6)	0	0			0	0	0	
(7)	0	0			0	0	0	
(8)	0	0			0	0	0	

Description: CB2X3 BASE x 33"
 Product ID: CB2X3B
 Item: Base Step Location:




----- Side 24.0" -----

----- Side 36.0" -----

Inside Area View

Item	Description	Height	Width	Area
Top 3	Flat Top 4' x 3' w/ 4618	0.50'	2.75'	1.375 sq ft
Base	CB2X3 BASE	2.75'	2.75'	7.56 sq ft
Rim to Invert		3.00'		
Less Casting		3.00'		
Invert to Floor		0.25'		
Adjustment (Brick/Mort.)		0.00'		
Precast Height		3.25'		
Floor		6.00"		
Plus Floor		3.75'		
Wall		6.00"		
Sump		0.00'		




Structure Product Detail

Item	Product	Qty	Product Description	Yards	Weight
Top 3	FT4X3	1	Flat Top 4' x 3' w/ 4618	0.22	900
Base	CB2X3B	1	CB2X3 BASE x 33"	0.77	3,098
	1 1/4 TS	1	1 1/4" Tarselal	0.00	0
	USF 461	1	USF 4618 Frame (24" x 24")	0.00	0
	USF 625	1	USF 6258 Gate (24" x 24")	0.00	0
Structure Totals				0.99	3,998

Elevations

Rim	Elev	Angle	Pipe	HOLE Type	Hole" Height	Hole" Width	Up"	Item
(1)	0	270	12 RCP	HOLE	18	18	1	Base
(2)	0	90	15 RCPA	Hole	19	26	0	Base
(3)	0	0			0	0	0	
(4)	0	0			0	0	0	
(5)	0	0			0	0	0	
(6)	0	0			0	0	0	
(7)	0	0			0	0	0	
(8)	0	0			0	0	0	

Description: **CB2X3 BASE x 33"**
 Product ID: **CB2X3B**
 Item: **Base** Step Location:




----- Side 24.0" -----

----- Side 36.0" -----

Rim to Invert 3.00'
 Less Casting 3.00'
 Invert to Floor 0.25'
 Adjustment (Brick/Mort.) 0.00

Inside Area View

Precast Height 3.25'
 Floor 6.00"
 Plus Floor 3.75'
 Wall 6.00"
 Sump 0.00'



Structure Product Detail



Item	Product	Qty	Product Description	Yards	Weight
Top 3	FT4X3	1	Flat Top 4' x 3' w/ 4618	0.22	900
Base	CB2X3B	1	CB2X3 BASE x 33"	0.77	3,098
	1 1/4 TS	1	1 1/4" Tarseal	0.00	0
	USF 461	1	USF 4618 Frame (24" x 24")	0.00	0
	USF 625	1	USF 6258 Grate (24" x 24")	0.00	0
Structure Totals				0.99	3,998

Elevations

Rim	Elev	Angle	Pipe	Hole Type	Hole Height	Hole Width	Up"	Item
(1)	0	270	15 RCPA	HOLE	19	26	0	Base
(2)	0	90	12 RCP	HOLE	18	18	1	Base
(3)	0	0			0	0	0	
(4)	0	0			0	0	0	
(5)	0	0			0	0	0	
(6)	0	0			0	0	0	
(7)	0	0			0	0	0	
(8)	0	0			0	0	0	

Description: **CB2X3 BASE x 33"**
 Product ID: **CB2X3B**
 Item: **Base** Step Location:

	Inside Area View	Wall
Rim to Invert	3.00'	6.00"
Less Casting	3.00'	
Invert to Floor	0.25'	
Adjustment (Brick/Mort.)	0.00	
		Summp
		0.00'



----- Side 24.0" -----

----- Side 36.0" -----


Structure Product Detail

Item	Product	Qty	Product Description	Yards	Weight
Top 3	FT4X3	1	Flat Top 4' x 3' w/ 4618	0.22	900
Base	CB2X3B	1	CB2X3 BASE x 33"	0.77	3,098
	1 1/4 TS	1	1 1/4" Tarseal	0.00	0
	USF 461	1	USF 4618 Frame (24" x 24")	0.00	0
	USF 625	1	USF 6258 Grate (24" x 24")	0.00	0
Structure Totals				0.99	3,998

Elevations

Rim	Elev	Angle	Pipe	Hole Type	Hole Height	Hole Width	Up"	Item
(1)	0	270	15 RCPA	HOLE	19	26	0	Base
(2)	0	90	12 RCP	HOLE	18	18	1	Base
(3)	0	0			0	0	0	
(4)	0	0			0	0	0	
(5)	0	0			0	0	0	
(6)	0	0			0	0	0	
(7)	0	0			0	0	0	
(8)	0	0			0	0	0	


Description: CB2X3 BASE x 33"
 Product ID: CB2X3B
 Item: Base Step Location:



----- Side 24.0" -----

----- Side 36.0" -----

Inside Area View



Top 3 0.50 Flat Top 4' x 3' w/ 4618

2.75 CB2X3 BASE

Base

Structure Product Detail


Item	Product	Qty	Product Description	Yards	Weight
Top 3	FT4X3	1	Flat Top 4' x 3' w/ 4618	0.22	900
Base	CB2X3B	1	CB2X3 BASE x 33"	0.77	3,083
	1 1/4 TS	1	1 1/4" Tarseal	0.00	0
	USF 461	1	USF 4618 Frame (24" x 24")	0.00	0
	USF 625	1	USF 6258 Grate (24" x 24")	0.00	0
Structure Totals				0.99	3,983

Elevations


Rim	Elev	Angle	Pipe	Hole Type	Hole Height	Hole Width	Up"	Item
(1)	0	270	15 RCPA	Hole	19	26	0	Base
(2)	0	90	15 RCPA	Hole	19	26	0	Base
(3)	0	0			0	0	0	
(4)	0	0			0	0	0	
(5)	0	0			0	0	0	
(6)	0	0			0	0	0	
(7)	0	0			0	0	0	
(8)	0	0			0	0	0	

Description: CB2X3 BASE x 33"
 Product ID: CB2X3B
 Item: Base Step Location:

	Inside Area View	Wall
Rim to Invert	3.00'	6.00"
Less Casting	3.00'	
Invert to Floor	0.25'	
Adjustment (Brick/Mort.)	0.00	
		Sump
		0.00'



15 RCPA/Hole
 H 19" / W 26.00"
 L 5.00 / R 5.00
 Up: 0" / Ang 90



----- Side 24.0" -----

----- Side 36.0" -----


Structure Product Detail

Item	Product	Qty	Product Description	Yards	Weight
Top 3	FT4X3	1	Flat Top 4' x 3' w/ 4618	0.22	900
Base	CB2X3B	1	CB2X3 BASE x 33"	0.77	3,098
	1 1/4 TS	1	1 1/4" Tarseal	0.00	0
	USF 461	1	USF 4618 Frame (24" x 24")	0.00	0
	USF 625	1	USF 6258 Grate (24" x 24")	0.00	0
Structure Totals				0.99	3,998

Elevations

Rim	Elev	Angle	Pipe	Hole Type	Hole Height	Hole Width	Up"	Item
(1)	0	270	12 RCP	HOLE	18	18	1	Base
(2)	0	90	15 RCPA	Hole	19	26	0	Base
(3)	0	0			0	0	0	
(4)	0	0			0	0	0	
(5)	0	0			0	0	0	
(6)	0	0			0	0	0	
(7)	0	0			0	0	0	
(8)	0	0			0	0	0	

Description: **CB2X3 BASE x 33"**
 Product ID: **CB2X3B**
 Item: **Base** Step Location:




----- Side 24.0" -----

----- Side 36.0" -----

Inside Area View

	Precast Height	Wall
Rim to Invert	3.00'	6.00"
Less Casting	3.00'	
Invert to Floor	0.25'	
Adjustment (Brick/Mort.)	0.00	
Plus Floor	3.75'	Sump




0.50' Flat Top 4' x 3' w/ 4618
 2.75' CB2X3 BASE

Structure Product Detail

Item	Product	Qty	Product Description	Yards	Weight
Top 3	FT4X3	1	Flat Top 4' x 3' w/ 4618	0.22	900
Base	CB2X3B	1	CB2X3 BASE x 33"	0.77	3,098
	1 1/4 TS	1	1 1/4" Tar Seal	0.00	0
	USF 461	1	USF 4618 Frame (24" x 24")	0.00	0
	USF 625	1	USF 6258 Grate (24" x 24")	0.00	0
Structure Totals				0.99	3,998

Inside Area View


Item	Height	Width	Area
Rim to Invert	3.00'	3.00'	9.00'
Less Casting	0.25'	3.00'	0.75'
Invert to Floor	0.00'	3.00'	0.00'
Adjustment (Brick/Mort.)	0.00'	3.00'	0.00'
Total	3.75'	3.00'	11.25'



Elevations

Rim	Elev	Angle	Pipe	Hole Type	Hole Height	Hole Width	Up"	Item
(1)	0	270	15 RCPA	HOLE	18	18	1	Base
(2)	0	90	12 RCP	HOLE	0	0	0	Base
(3)	0	0			0	0	0	
(4)	0	0			0	0	0	
(5)	0	0			0	0	0	
(6)	0	0			0	0	0	
(7)	0	0			0	0	0	
(8)	0	0			0	0	0	

Description: **CB2X3 BASE x 33"**
 Product ID: **CB2X3B**
 Item: **Base** Step Location:



----- Side 24.0" -----

----- Side 36.0" -----

Structure Product Detail



Item	Product	Qty	Product Description	Yards	Weight
Top 3	FT4X3	1	Flat Top 4' x 3' w/ 4618	0.22	900
Base	CB2X3B	1	CB2X3 BASE x 33"	0.77	3,098
	1 1/4 TS	1	1 1/4" Tarseal	0.00	0
	USF 461	1	USF 4618 Frame (24" x 24")	0.00	0
	USF 625	1	USF 6258 Grate (24" x 24")	0.00	0
Structure Totals				0.99	3,998

Elevations

Rim	Elev	Angle	Pipe	HOLE Type	Hole" Height	Hole" Width	Up"	Item
(1)	0	270	12 RCP	HOLE	18	18	1	Base
(2)	0	90	15 RCPA	Hole	19	26	0	Base
(3)	0	0			0	0	0	
(4)	0	0			0	0	0	
(5)	0	0			0	0	0	
(6)	0	0			0	0	0	
(7)	0	0			0	0	0	
(8)	0	0			0	0	0	

Description: **CB2X3 BASE x 33"**
 Product ID: **CB2X3B**
 Item: **Base** Step Location:

	Inside Area View	Wall
Rim to Invert	3.00'	6.00"
Less Casting	3.00'	
Invert to Floor	0.25'	
Adjustment (Brick/Mort.)	0.00	
		Summ
		6.00"



----- Side 36.0" -----

----- Side 24.0" -----

Physical Properties

Appearance Semi-solid	Maximum VOC <5 g/l	Softening Point (ASTM D 36) 320°F
Ductility @ 77° F, 5cm/min (ASTM D113) Min. 5.0	Penetration @ 77°F (150g 5 sec) (ASTM D217) Min. 50 - Max. 120	Specific Gravity @ 77° F (25°C) (ASTM D71) Min. 1.20 - Max. 1.35
Flash Point, C.O.C. (ASTM D92) Min. 600°F		

Approvals and Certifications

Meets or exceeds all requirements of **ASTM C990 Standard Specification** for joints, concrete pipe, manholes and precast box sections, using Preformed Flexible Joint Sealants.

Meets requirements of **Federal Specifications SS-S210-A**, "Sealing Compound Preformed Plastic For Pipe Joints", Type 1, Rope Form.

Usage

Flexible Plastic Gaskets for sealing the following Precast products, regardless of size or shape:

- Storm Sewer Pipe
- Box Culverts
- Manhole Risers
- Septic Tanks
- Utility & Burial Vaults
- Wet Wells

Application

Vertical Application:

1. Apply one brush coat of **Ram-Nek Primer** to concrete surfaces to be sealed. Primer is recommended but not required unless conditions are wet.
2. Remove protective wrapper on one side only of preformed **Ram-Nek** coil and press firmly to the dry, clean joint surface. Leave the outside wrapper in place to protect the gasket and keep it from stretching.
3. Remove protective wrapper from **Ram-Nek** gasket and set next section. Each unit is forced "home" by its own weight, compressing **Ram-Nek** to tightly pack and immediately seal the joint. "Squeeze out" is visible proof of a watertight joint.
4. After last section is set and fully "seated", the installation is complete. Backfilling and compaction can start immediately.

Horizontal Application:

1. Trench conditions shall be such that pipe jointing can be accomplished without getting mud, silt, gravel or other foreign materials into the joint. Generally, the trench should be dewatered and have a firm bottom free of muck.
2. Remove protective wrapper on one side only of preformed **Ram-Nek** coil and press firmly to the dry, clean joint surface. Before laying the pipe in the trench, attach the gaskets end-to-end to the leading edge of the tongue or groove of each pipe joint, forming a continuous gasket around the circumference. Remove the protective wrapper before joining pipe sections.
3. After the gasket is applied, the pipe should be handled carefully to avoid displacing or soiling of gasket. Any gasket so disturbed should be replaced.
4. The pipe should be properly aligned before joints are forced home. For tongue and groove pipe, the pipe should be partially

supported to maintain concentricity until the gasket is properly compressed in the joint space and sufficient pressure applied to make sure that the joint is properly made.

5. Backfilling and compaction can begin when jointing is completed.

Product Sizes

9 (.75in x 14.5ft) COILS/CASE
5 (1.25in x 14.5ft) COILS/CASE

8 (1in x 14.5ft) COILS/CASE (46.8

5 (1.5in x 10.5ft) COILS/CASE (49