



HONOR OF VETERANS  
MEMORIAL SITE

NEW 16' OF 15" RCP  
WITH NEW CATCH BASIN.  
TOP CONCRETE 3.32'  
INVERT 1.70'

BACKFILL EXISTING SWALE WITH  
GRANULAR MATERIAL IN 6" LIFTS  
COMPACTED TO 95%  
DENSITY AND SOD. SEE TYPICAL  
DETAIL FOR CULVERTS IN DITCH.

A  
C2/C2

RELOCATED  
CROSSING  
SIGN

CUT EXISTING CURB @ 45 DEGREE  
# TAPER DOWN TO NEW SIDEWALK.  
INSTALL 2'x4' CAST IN PLACE  
DETECTABLE  
WARNING

3RD S

EXISTING SWALE

NEW 6" X 7' PVC  
DRAIN PIPE

3" OAK

CLEVELAND AVENUE

ASPHALT

DRAIN INLET  
T.C. EL. 4.91'  
INV. EL. 0.96'

T.B.M.  
EL. 5.14'

EXISTING  
CULVERT  
INV. EL. 1.61'

CONCRETE

SEWER MANHOLE  
T.C. EL. 5.31'  
INV. EL. -0.69'

ASPHALT

LIGHT POLE

BACKFILL IN 6" LAYERS @ 95% STD.  
OR TO SATISFACTION OF ENGINEERING  
AND SOD.

GEOTEXTILE FABRIC AT JOINTS ONLY  
(STORM DRAIN ONLY) SEE NOTE BELOW

SAND BEDDING (AS DIRECTED)

3RD STREET

PARTIAL SITE PLAN

SCALE: 1" = 10'

