

PROTECTED SHALL BE A MINIMUM OF 6 INCHES ABOVE FINISHED GRADE AT THE PERIMETER OF THE BUILDING, EXCEPT WHERE REQUIREMENTS FOR VEHICLE ACCESS EXISTS.

REQUIRED R-13
ACTUAL R-13.0

DETAIL #1
N.T.S. -
A1.3

BLOCK LEDGE 1 1/2" x 5 1/2"

SSSMR MET. ROOF SYSTEM ON INSULATED STRUCTURAL DECK

TOP OF MASONRY 24.0' (40'.0' MSL)

2nd FLR. CLG. HGT. 22'-3"

1'-4"

9'-6"
2nd FLOOR CLG. HEIGHT

BRIEFING

2nd FLR. T.O.S. 12'-9"

JOIST P.O.B. 12'-3 1/2"

BEAM P.O.B. 10'-9 1/2"

CEILING HEIGHT 10'-0"

25'-0"
EAVE HEIGHT

2'-9"

14K3 STEEL BAR JOIST 18" o.c.
(TYP) SEE SHEET F-1

METAL PANEL SYSTEM

6"Ø PIPE COLUMN

CAST STONE LINTEL

8" CMU

10'-0"
1st FLOOR CLG. HEIGHT

4" CMU SPLIT FACE BLOCK
6' IN HEIGHT

2" AIR SPACE

1
A1.3

1st FLR. T.O.S. 0.0' (16.0' MSL)

FOR FOUNDATION DETAILS,
SEE SHT S1.1

1'-2"

18'-10"

