

ROOM FINISH SCHEDULE

NAME	FLOOR	BASE	WALL	CEILING	REMARKS						
						VCT	CERAMIC TILE	CARPET	CONC. WSEALER	RUBBER BASE	CERAMIC TILE
100 LOBBY											
101 VOLUNTEERS OFFICE											
102 SAMPLES ROOM											
103 LAB											
104 WATER HEATER CLOSET											
105 HALL											
106 WOMEN'S RESTROOM											
107 MEN'S RESTROOM											
108 CORRIDOR											
109 MD 3B											
110 MD 3A											
111 RN MANAGER											
112 SECRETARY											
113 SITE MANAGER											
114 WHEELCHAIR AREA											
115 CORRIDOR											
116 MD WORKROOM											
117 CONFERENCE ROOM											
118 TRAINING ROOM											
119 VESTIBULE											
120 COMM. ROOM											
121 STAFF DINING											
122 MD 2A											
123 MD 2B											
124 NP 1A											
125 UTILITY CLOSET											
126 RESTROOM											
127 WOMEN'S HEALTH											
128 HOLSBERG											
129 ELECTRIC CLOSET											
130 CORRIDOR											
131 WOMEN'S RESTROOM											
132 MEN'S RESTROOM											
133 EXAM ROOM											
134 EQUIPMENT ROOM											
135 DIAGNOSIS											
136 TREATMENT ROOM											
137 MD 1A											
138 MD 1B											
139 CORRIDOR											
140 PC SVN											
141 RN/RN											
142 RN/RN											
143 RN/RN											
144 EYE CAMERA											
145 SPD											
146 CORRIDOR											
147 CORRIDOR											
148 SCALES AREA											
149 CHECK-OUT											
150 FAX/COOPER ROOM											
151 PHARM											
152 CHECK-IN											
153 CHECK-IN											
154 CHECK-IN											
155 PT. ADV.											
156 PHARMACY											
157 ALCOHOL											
158 WOMEN'S RESTROOM											
159 MEN'S RESTROOM											
160 SECURITY OFFICE											

DOOR & HARDWARE SCHEDULE


NO.	SIZE	TYPE	FRAME	HINGE	LOCK	ACCESS.	REMARKS
1	3.0x7.0	S. C. WOOD					
2	3.0x7.0	HOLLOW METAL					
3	3.0x7.0	STOREFRONT GLASS					
4	3.0x7.0		HOLLOW METAL				
5	2.0x7.0		ALUM. STOREFRONT				
6	3.0x7.0			BUTT			
7	3.0x7.0				KEYED HANDLE		
8	PR. 3.0x7.0				PRIVACY		
					PASSAGE		
					DOOR STOP		
					WEATHERSTRIP		
					THRESHOLD		
							EXISTING TO REMAIN

WINDOW SCHEDULE

NO.	SIZE	TYPE	FRAME	GLASS	LITES	ACCESS.	REMARKS
1	3.0x4.0	FIXED					
2	3.0x4.0	VERT. SLIDE					
3	3.0x4.0	HORIZ. SLIDE					
4	4.0x4.2	STOREFRONT					
5	1.34x9.0	ALUM. STOREFRONT					
6	EXISTING	HOLLOW METAL					
7		WOOD					
8		TEMPERED					
9		TINTED (MIRROR)					
10		PLAIN					
11		INSULATED					
12							
13							
14							
15							
16							
17							
18							
19							
20							
21							
22							
23							
24							
25							
26							
27							
28							
29							
30							
31							
32							
33							
34							
35							
36							
37							
38							
39							
40							
41							
42							
43							
44							
45							
46							
47							
48							
49							
50							
51							
52							
53							
54							
55							
56							
57							
58							
59							
60							
61							
62							
63							
64							
65							
66							
67							
68							
69							
70							
71							
72							
73							
74							
75							
76							
77							
78							
79							
80							
81							
82							
83							
84							
85							
86							
87							
88							
89							
90							
91							
92							
93							
94							
95							
96							
97							
98							
99							
100							
101							
102							
103							
104							
105							
106							
107							
108							
109							
110							
111							
112							
113							
114							
115							
116							
117							
118							
119							
120							
121							
122							
123							
124							
125							
126							
127							
128							
129							
130							
131							
132							
133							
134							
135							
136							
137							
138							
139							
140							
141							
142							
143							
144							
145							
146							
147							
148							
149							
150							
151							
152							
153							
154							
155							
156							
157							
158							
159							
160							

GENERAL NOTES

1. INSULATION AND INSULATION ASSEMBLIES SHALL MEET THE REQUIREMENTS OF SECTION 7.1.9.
- A. CONCEALED INSULATION SHALL HAVE A FLAME SPREAD OF 0-25 AND SMOKE DEVELOPED INDEX OF 0-450.
- B. EXCEPT THAT IN COMBUSTIBLE (WOOD FRAME) CONSTRUCTION.
2. FACING SHALL COMPLY WITH IBC 2006.
3. PROVIDE 5x6" LANDINGS. LEVEL WITH FINISHED FLOOR. OUTSIDE EXTERIOR DOORS ON REAR & SIDE OF BUILDING. THRESHOLDS SHALL BE NOT MORE THAN 1/2" IN HEIGHT AND SHALL BE BEVELED IF MORE THAN 1/4".
3. CONTRACTOR TO VERIFY ALL SITE CONDITIONS, BUILDING LOCATIONS, AND DIMENSIONS PRIOR TO CONSTRUCTION.
4. MATERIALS SHALL BE NEW AND U.L. LISTED.
5. NO WORK SHALL BE CONCEALED UNTIL APPROVED BY LOCAL INSPECTORS.
6. CONSTRUCTION SHALL COMPLY WITH ALL PARISH, STATE, AND LOCAL CODES.
7. CONTRACTOR TO GUARANTEE WORK FOR ONE YEAR.
8. CONTRACTOR SHALL FURNISH WATER AND POWER FROM EXISTING SOURCES.
9. EXTERIOR CAULKING SHALL BE THICK CAULK.
10. PAINT GRADE TO SHALL BE SHERWIN WILLIAMS OR EQUIVALENT. ALL WORK TO RECEIVE 3 COATS. COLOR SELECTION BY OWNER.
11. PROVIDE CLEANUP ON A REGULAR BASIS. NO TRASH STORED IN BUILDING.
12. ALL BATT INSULATION SHALL HAVE A CLASS "A" (0-25) FLAME SPREAD IN COMPLIANCE WITH APPLICABLE CODE.
13. USE 6" STUDS, OR 4" STAGGERED STUDS AT ALL PLUMBING WALLS.
14. PROVIDE GALVANIZED METAL PAN WITH DRAIN AT WATER HEATER LOCATION.
15. FLOORING SHALL BE NON-SLIP.
16. INTERIOR LOCKS ON DOORS IN MEANS OF EGRESS SHALL NOT REQUIRE THE USE OF A KEY, SPECIAL KNOWLEDGE, OR SPECIAL DEVICE TO OPEN IN THE DIRECTION OF EGRESS. ALL DOORS SHALL HAVE LEVER TYPE HANDLES.
17. INTERIOR WALLS AND CEILINGS SHALL HAVE A FLAME SPREAD OF 0-200 AND A SMOKE DEVELOPMENT RATING OF 0-450.
18. ALL WORK SHALL COMPLY WITH THE LATEST EDITION OF ALL LOCAL, STATE, AND NATIONAL CODES COVERING THE TYPE OF WORK BEING PERFORMED.
19. PROVIDE PORTABLE FIRE EXTINGUISHERS IN ACCORDANCE WITH NFPA 1.01. SEE APPENDIX "E" OF NFPA 1.01 FOR DISTRIBUTION OF EXTINGUISHERS.
20. ALL FIRE WALLS SHALL EXTEND TIGHT TO ROOF DECK AND BE SEALED WITH AN APPROVED FIRE CAULK.
21. ALL ELECTRICAL, MECHANICAL, AND PLUMBING MATERIALS PENETRATING FIRE WALLS SHALL BE FIRE CAULKED. PENETRATIONS THROUGH RATED CONSTRUCTION SHALL BE SEALED WITH A MATERIAL CAPABLE OF PREVENTING THE PASSAGE OF FLAMES AND HOT GASES WHEN TESTED IN ACCORDANCE WITH ASTM E 119 (4.1).
22. SERVICE COUNTERS SHALL HAVE A HCP ACCESSIBLE WRITING SURFACE. MAX. 34" FROM F.F. (ADAAG MANUAL 1996, PG. 135)
23. STAFF DINING ROOM DOUBLE SINK SHALL BE HCP ACCESSIBLE AND CABINET COUNTERS SHALL BE MAX. 34" FROM F.F. TO MEET ADA REQUIREMENTS.



DAMMON ENGINEERING, INC.
 CHIEF ENGINEER
 EMMETT DAMMON, P. E.

CHIEF ARCHITECT
 ROBERT WILTSE

1095 FLORIDA AVENUE
 SLIDELL, LA. 70456
 OFFICE: 985-649-5832
 FAX: 985-641-5950

WEBSITE:
 WWW.DAMMONENGINEERING.COM
 EMAIL:
 DAMMONENG@BELLSOUTH.NET

ARCHITECTURE
 ENGINEERING
 STUDIES
 PLANNING
 INVESTIGATION
 EXPERT WITNESS

SOUTHEAST
 LOUISIANA
 VETERANS
 HEALTH CARE
 SYSTEM

UNIT B
 SCHEDULES
 AND
 NOTES

REV:

SCALE: AS NOTED

JOB#: 2009

DATE: 01-13-09

SHEET 5

A-2