



PARTITION LEGEND

- ◆ 3-1/2" OR 6" (25 GA.) METAL STUDS @ 16" O.C. (MAX) O/C WITH (1) LAYER 5/8" GYPSUM BOARD EACH SIDE TO 6" ABOVE OF CEILING. PROVIDE R-11 BATT INSULATION BETWEEN STUDS FOR SOUND ATTENUATION. SEE PLAN FOR LOCATIONS OF BATT INSULATION. BRACE FRAMING TO UNDERSIDE OF STRUCTURE ABOVE.
- ◆ 3-1/2" 25 GA. MTL. 'CEE' STUD FRAMING @ 24" (MAX) WITH 5/8" MOISTURE RESISTANT GYPSUM BOARD TO 6" ABOVE CEILING WITH CERAMIC TILE WAINSCOT TO 5'-0" A.F.F. AS SPECIFIED (TOILET RM. SIDE). PROVIDE (1) LAYER 5/8" GYP. BD. ON OPPOSITE SIDE TO 6" ABOVE CEILING. PROVIDE R-11 OR R-19 BATT INSULATION IN WALLS FOR SOUND ATTENUATION. SEE PLAN FOR LOCATIONS. PROVIDE BLOCKING FOR TOILET ROOM ACCESSORIES.(PROVIDE CERAMIC TILE TO 9'-0" A.F.F. AT SHOWER AREA ONLY.)
- ◆ 3-1/2" OR 6" 20 GA. (SEE PLAN) MTL. CEE STUD FRAMING @ 16" O/C WITH (1) LAYER 5/8" GYPSUM BOARD (1/2" LEAD LINED) (X-RAY RM. SIDE) TO 9'-0" A.F.F. & (1) LAYER 5/8" GYPSUM BOARD FROM 9'-0" TO 6" ABOVE CEILING (X-RAY RM. SIDE). PROVIDE (1) LAYER 5/8" GYPSUM BOARD (OPPOSITE SIDE) TO 6" ABOVE CEILING. BRACE TO STRUCTURE ABOVE.
- ◆ 3-1/2" OR 6" (25 GA.) METAL STUDS @ 16" (MAX) O/C WITH (1) LAYER 5/8" GYPSUM BOARD EACH SIDE TO 6" ABOVE OF CEILING. BRACE FRAMING TO UNDERSIDE OF STRUCTURE ABOVE.
- ◆ 3-1/2" 25 GA. MTL. 'CEE' STUD FRAMING @ 24" (MAX) WITH 5/8" MOISTURE RESISTANT GYPSUM BOARD TO 6" ABOVE CEILING WITH CERAMIC TILE WAINSCOT TO 5'-0" A.F.F. AS SPECIFIED (BOTH SIDES). PROVIDE (1) LAYER 5/8" GYP. BD. ON OPPOSITE SIDE TO 6" ABOVE CEILING. PROVIDE R-11 OR R-19 BATT INSULATION IN WALLS FOR SOUND ATTENUATION. PROVIDE BLOCKING FOR TOILET ROOM ACCESSORIES.
- ◆ 1-1/2" 25 GA. MTL. CHANNEL FRAMING AT 16" O.C. WITH (1) LAYER OF 5/8" TYPE 'X' GYPSUM BOARD (BOTH SIDES) TO UNDERSIDE OF STRUCTURE. PROVIDE 9" LONG STEEL PLATE TO BE FASTENED WITH (2) #8 BY 3" LONG STEEL SCREWS. FIRE CAULK ALL PENETRATIONS AS REQUIRED BY CODE. REFER TO UL #420 (1HR RATING WALL) FOR ADDITIONAL INFORMATION.
- ◆ 5/8" INTERIOR SIDE GYPSUM BOARD ON 6" 25 GA. METAL STUD. 5/8" EXTERIOR GRADE GYPSUM BOARD WITH BUILDING PAPER, 2" GAP, MASONRY BRICK. (SEE SECTIONS FOR MORE INFORMATION.)
- ◆ 5/8" INTERIOR SIDE GYPSUM BOARD ON 6" 25 GA. METAL STUD ON 5/8" EXTERIOR GRADE GYPSUM BOARD. PROVIDE PAPER BACK WIRE LATH WITH 3/4" STUCCO. (SEE SECTIONS FOR MORE DETAILS)

FLAME SPREAD NOTE:
 ALL INTERIOR FINISHES INCLUDING WALLS, PARTITIONS, CEILINGS AND OTHER EXPOSED INTERIOR SURFACES, COMPRISING BOTH PLASTER, WOOD OR OTHER INTERIOR FINISH MATERIAL AND ANY SURFACING MATERIAL SUCH AS PAINT OR WALL PAPER APPLIED THEREOF SHALL HAVE A FAME SPREAD CLASSIFICATION OF CLASS A.

- ### ARCHITECTURAL NOTES
- A) ARCHITECTURAL:
 1. ALL INTERIOR DOORS SHALL HAVE 4 INCHES CLEAR OF THE ADJOINING WALL ON THE HINGE SIDE OF THE DOOR, UNLESS NOTED OTHERWISE OR WHERE CENTERED ON WALL.
 2. THIS SHEET IS TO BE USED IN CONJUNCTION WITH THE STRUCTURAL DRAWINGS. ALL COLUMN AND BEAM SIZES ARE TO REFER BACK TO STRUCTURAL DRAWINGS.
 3. NOT USED.
 4. SEE SHEET A-10.03 FOR ALL RATED SLAB FIRE-THROUGH PENETRATION DETAILS.
 5. SEE SHEET A-10.03 FOR ALL RATED PARTITION TYPE DETAILS.
 6. NOT USED.
 7. NOT USED.
 8. NOT USED.
 9. NOT USED.
 10. COORDINATE WITH ELECTRICAL DRAWINGS FOR REQUIRED PLYWOOD BACKING.

DRAWING LEGEND

	ELEVATION
	BUILDING/WALL SECTION
	DETAIL
	INTERIOR ELEVATION
	ROOM NUMBER
	INDICATES PARTITION TYPE (SEE SHEET A-10.02)
	INDICATES WINDOW TYPE (SEE SHEET A-10.01)
	INDICATES DOOR TYPE (SEE SHEET A-10.01)
	INDICATES SOUND BATT INSULATION
	INDICATES FIRE WALL SEPARATION

PROGRESS SET

BID SET

FLOOR PLAN
 SCALE: 3/16" = 1'-0"
 NORTH

SATNOH, LLC 130 W. RUELLE MANDEVILLE, LA 70471
GARCIA BRENNER STROMBERG ARCHITECTS 711 Park of Commerce Drive, Suite 118 Bossier Parish, Louisiana 70601 Tel: 504.251.7575 Fax: 504.251.7441
TULANE / HONTAS MEDICAL CENTER
A-2.01