



ARCHITECTURAL FLOOR PLAN - LEVEL 1
 SCALE: 1/8" = 1'-0"
 N

- ### GENERAL SHEET NOTES
1. ALL DIMENSIONS ARE FACE-OF-WALL TO FACE-OF-WALL UNLESS NOTED OTHERWISE.
 2. ALL PLUMBING FIXTURES, FURNITURE, AND APPLIANCES THAT ARE SHOWN AS GRAYED AND DIMED ARE TO BE OWNER PROVIDED AND NOT IN CONTRACT (NO) AND ARE SHOWN FOR COORDINATION PURPOSES ONLY. CONTRACTOR TO VERIFY THESE ITEMS OWNER FINISHED AND CONTRACTOR INSTALLED (OTO).
 3. REFER TO PARTITION TYPES FOR PARTITION THICKNESS WHERE NOT SHOWN ON PLAN.
 4. ALL MANUFACTURED ARTICLES, MATERIALS, AND EQUIPMENT SHALL BE CLASSED, APPROVED, AND INSTALLED CONFORMED TO THE MANUFACTURER'S SPECIFICATIONS OR INSTRUCTIONS.
 5. FOR ALL WOOD MEMBERS REQUIRED BY CODE TO BE FIRE RETARDANT TREATED, PROVIDE FIRE RESISTIVE PENETRATION WITH FIRE RETARDANT CHEMICALS TO PROVIDE UL FRS FIRE HAZARD CLASSIFICATION. ALL WOOD SHALL BE IDENTIFIED WITH A UL LABEL, CERTIFYING THIS CLASSIFICATION AND F41 DAMOND.
 6. APPROVED FIRE EXTINGUISHERS SHALL BE FINISHED, LOCATED, AND INSTALLED BY THE GENERAL CONTRACTOR, AS REQUIRED BY THE GOVERNING BODY. COORDINATE EXACT LOCATION WITH THE ARCHITECT.
 7. ALL FIRE EXTINGUISHERS SHALL BE FIVE POUND, ABC RATED FIRE EXTINGUISHER(S) AND/OR CABINET(S) WHERE SHOWN ON THESE PLANS.
 8. ALL PENETRATIONS OF FIVE RESISTIVE FLOORS OR SHIRT WALLS SHALL BE CLASSIFIED AND APPROVED BY THE ARCHITECT AND SHALL CONFORM TO UL STANDARDS FOR THROUGH PENETRATIONS FIRESTOP SYSTEMS. SEAL AROUND ALL PENETRATIONS (DUCTS, PIPES, CONDUITS, ETC.) AT FIRE-RATED ASSEMBLIES. SEAL SHALL NOT DIMISH RATING OF ASSEMBLY. AT CONCRETE OR MASONRY, SEAL OFF OPENINGS WITH CONCRETE GROUT. AT PLASTER OR DRYWALL, DAV UP GAPS AND FILL WITH UL APPROVED SEALANT OR PUTTY PER MANUFACTURERS RECOMMENDATIONS FOR THROUGH PENETRATIONS FIRESTOP SYSTEMS. SEAL AROUND ALL ARCHITECTURAL, MECHANICAL, OR ELECTRICAL PENETRATIONS (DUCTS, PIPES, CONDUITS, ETC.) AT CONCRETE OR MASONRY, SEAL OFF OPENINGS WITH CONCRETE GROUT. AT PLASTER OR DRYWALL, DAV UP GAPS AND FILL WITH UL APPROVED SEALANT OR PUTTY PER MANUFACTURERS RECOMMENDATIONS.
 9. MAKE AROUND ALL ARCHITECTURAL, MECHANICAL, OR ELECTRICAL PENETRATIONS (DUCTS, PIPES, CONDUITS, ETC.) AT CONCRETE OR MASONRY, SEAL OFF OPENINGS WITH CONCRETE GROUT. AT PLASTER OR DRYWALL, DAV UP GAPS AND FILL WITH UL APPROVED SEALANT OR PUTTY PER MANUFACTURERS RECOMMENDATIONS.
 10. SEE SHEET A201 FOR MASONRY EXPANSION JOINT LOCATIONS NOT SHOWN ON THIS SHEET.
 11. SEAL AROUND ALL PENETRATIONS (DUCTS, PIPES, CONDUITS, ETC.) AT CONCRETE OR MASONRY, SEAL OFF OPENINGS WITH CONCRETE GROUT. AT PLASTER OR DRYWALL, DAV UP GAPS AND FILL WITH UL APPROVED SEALANT OR PUTTY PER MANUFACTURERS RECOMMENDATIONS.

DAMMON

ENGINEERING, INC.

Architects & Engineers

Chief Architect: Kevin J. Kinchen, NCARB
 Chief Engineer: Brian Mistich, PE
 554 Old Spanish Trail
 Stidell, LA 70458
 www.dammoneengineering.com
 info@dammoneengineering.com
 PH: 985.649.5832
 F: 985.641.5950

#	DESCRIPTION	DATE	REVISIONS

PRELIMINARY
 NOT FOR
 CONSTRUCTION

SPORTSMAN

03

A101

SHEET TITLE:
 ARCHITECTURAL FLOOR
 PLAN - LEVEL 1
 DRAWING NUMBER:
 A101

LOT #1 LA HWY 27
 HACKBERRY, LA 70645
 JOB No: 2141 DATE: JUN 20 2019
 DRAWN BY: CKD/JTL CHECKED BY: CKD

A101

SHEET No: _____
 VALUE OF \$ _____