

ELA

Remote Lamp Heads

Intended Use

To be powered by 6, 12 or 24V battery equipment as part of an emergency lighting system providing light for the path of egress. Order separately.



Standard PAR36



Multi-Faceted Reflector



Indura® Remote



Sealed and Gasketed PAR36



Metal PAR36



Hazardous PAR36

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: ELA IND H2012

Series	Finish	Number of lamps	Lamp head style	Lamp type ¹
ELA	(blank) Standard color	(blank) Single	(blank) Standard PAR36	Specify lamp type, see configuration tables below.
	B Black	T Twin	MR24 Multi-faceted reflector	
	W White		IND Indura ²	
	ITN Instrument tan (Titan® Series match)			
	TN Desert tan			
	Specify color, see availability table below			
			NX Sealed and gasketed PAR36	
			MT Metal PAR36	
			Z Hazardous PAR36 (Class I, Division II)	

ADDITIONAL INFORMATION

For additional product information, visit www.lithonia.com.

COMPOSITE LAMPS

	6V HALOGEN		6V KRYPTON		12V HALOGEN		12V KRYPTON	24V INCANDESCENT	24V HALOGEN
Wattage	12W	20W	6W	9W	12W	20W	9W	18W	20W
Lamp type	H1206	H2006	K0606	K0906	H1212	H2012	K0912	N1824	H2024
MR24	■	■	■	■	■	■	■		
IND	■	■	■	■	■	■	■	■	■

SEALED-BEAM LAMPS

	6V INCANDESCENT			6V HALOGEN			12V INCANDESCENT				12V HALOGEN				24V INCANDESCENT	120V PAR36		
Wattage	8W	12W	18W	6W	8W	12W	12W	18W	25W	35W	8W	12W	35W	50W	50W	15W	30W	50W
Lamp type	N0806	N1206	N1806	H0606	H0806	H1206	N1212	N1812	N2512	N3512	H0812	H1212	H3512	H5012	N5024	N15120	N30120	N50120
IND ²													■	■	■			
NX	■	■		■	■	■	■	■	■	■	■	■	■	■				
Standard PAR36	■	■		■	■	■	■	■	■		■	■						
MT	■	■	■	■	■	■	■	■	■		■	■	■	■		■	■	■
Z	■		■	■	■	■	■	■	■		■	■						

REMOTE HEAD AND DIMENSIONS³

SERIES	STANDARD COLOR	OTHER COLOR	WIDTH (SINGLE HEAD)	WIDTH (TWIN HEADS)	HEIGHT (SINGLE HEAD)	HEIGHT (TWIN HEADS)	DEPTH
Standard PAR36	Desert tan	White, black, instrument tan	4-3/4 (12.1)	13 (33)	7-3/4 (19.7)	7-3/4 (19.7)	5-1/16 (12.9)
MR24	White	Black	4-5/8 (11.7)	6-5/8 (16.8)	6-5/8 (16.8)	4-1/2 (11.4)	2-1/2 (6.3)
IND	Gray/blue	White	5-7/8 (14.9)	7-1/8 (18.1)	5-1/8 (13)	5-1/8 (13)	5-3/8 (13.7)
NX	Gray	White, black	4-3/4 (12.1)	13 (33)	7-3/4 (19.7)	7-3/4 (19.7)	5-1/16 (12.9)
MT	Brushed aluminum	N/A	4-5/8 (11.7)	10-1/2 (26.7)	5-1/8 (13)	5-1/8 (13)	6-1/2 (16.5)
Z	Gray	N/A	4-3/4 (12.1)	1" (33)	7-3/4 (19.7)	7-3/4 (19.7)	5-1/16 (12.9)

MOUNTING PLATE DIMENSIONS³

SERIES	WIDTH	HEIGHT
MT (single head)	2-3/4 (7.0)	4-1/2 (11.5)
MT (twin heads)	4-9/16 (11.6)	4-1/2 (11.5)
IND	5-1/8 (13)	4-11/16 (11.9)
MR24	6-7/8 (17.5)	4-5/8 (11.7)
All others	3-1/8 (7.9)	5 (12.7)

■ = Available

Notes

- Consult factory for additional lamp availability.
- For Indura sealed beam lamps, add suffix S to lamp nomenclature. Example: H3512S.
For photometric information, visit www.lithonia.com
- Dimensions are shown in inches (centimeters) unless otherwise noted.