



Customer Load Data Form

FAX TO: Designer: \_\_\_\_\_ Fax Number: \_\_\_\_\_

Account # \_\_\_\_\_ Project: \_\_\_\_\_

Address: \_\_\_\_\_

Service:  Overhead  Underground Voltage: \_\_\_\_\_ Amperage: \_\_\_\_\_
 3 Wire  4 Wire Conduit Size: \_\_\_\_\_ Number: \_\_\_\_\_
 1 Phase  3 Phase Conductor Size: \_\_\_\_\_ Number Per Phase: \_\_\_\_\_

Has point of service (metering location) been approved by ENTERGY?  Yes  No

REQUESTED IN-SERVICE DATES: temporary \_\_\_\_\_ permanent \_\_\_\_\_ All-electric facility?  Yes  No

\*\* 480V service requires customer to install a disconnect switch before service meter point on self contained meters. \*\*

Connected Load

Table with 3 columns: Load Type, 1 Phase, 3 Phase. Rows include Lighting, Air Conditioning, Heating, Water Heater (electric), Cooking Equipment, Refrigeration, Receptacles, Motor Load Total, Largest Single Motor, Miscellaneous, Total Connected Load, Total Diversified Connected Load.

Special Instructions \_\_\_\_\_

From: \_\_\_\_\_ Phone #: \_\_\_\_\_ Fax #: \_\_\_\_\_

Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Note: Service will be provided according to Entergy's Customer Installation Standards for Electric Service in effect at the time of the arrangements. The latest version is available at www.entergy.com. All charges applicable shall be paid in advance of any construction.