

EXISTING CMU WALL.

EXISTING PIPE

EXISTING PATIO FOUNDATION

INSTALL GALV STEEL L ANGLE 3/4" x 1/2" x 1/8" THICK; EACH SIDE.

ALL COMPLETED WORK SHALL BE SMOOTH WITH SIDEWALK ELEVATION WITH NO PROJECTIONS ABOVE SIDEWALK ELEVATION.

NEW SIDEWALK

NEW CURB

NEW PAVING

NOTES:

1. CONTRACTOR SHALL CONSTRUCT A 6" WIDE x 4" DEEP TRENCH DRAIN THE LENGTH OF SIDEWALK ON THE NORTH END OF BUILDING. LEAVE A 1/2" WIDE KEY WAY EACH SIDE TO SUPPORT GRATE.
2. SLOPE INVERT .8% TO .9% TOWARD DRAINAGE DITCH.
3. CONCRETE MIX SHALL OBTAIN A MINIMUM STRENGTH OF 3,000 PSI IN 30 DAYS.
4. INSTALL A METAL GRATE AT THE TOP OF THE TRENCH. GRATE SHALL BE A HEAVY DUTY, HEEL PROOF, ANTI SLIP GRATE WITH LOCKABLE COVER.




**1 TRENCH DRAIN**  
SCALE: 1"=1'-0"

DRAINAGE ANALYSIS FOR THE  
**EL PASO MEXICAN RESTAURANT**  
200 WEST GLORIA SWITCH ROAD  
CARENCRO, LA 70520

JOB No:	2269	DATE:	4/2/2020
DRAWN BY:	DD	CHECKED BY:	BAM

**C1.4.2**



**DAMMON ENGINEERING, INC.**

554 Old Spanish Trail Suidell, LA 70458 (985) 649-5832

CHIEF ENGINEER: BRIAN A. MISTICH, P.E.  
554 OLD SPANISH TRAIL  
SUIDELL, LA 70458

dammonengineering.com  
info@dammonengineering.com  
PHONE: 985-649-5832