

[illegible]

NOTE: ALL WINDOWS SHALL BE CONSTRUCTION GRADE LOW E.

[illegible][illegible]

EACH CONTRACTOR IS RESPONSIBLE FOR THE CONSTRUCTION OF A MAIN WIND-FORCE-RESISTING COMPONENT OF THIS BUILDING AND SHALL SUBMIT A WRITTEN CONTRACTOR'S STATEMENT OF RESPONSIBILITY TO THE BUILDING OFFICIAL AND OWNER PRIOR TO COMMENCEMENT OF THE WORK ON THAT COMPONENT. (IBC 1706.3)

[illegible]

--

2'-5"

5'-0" STOOP

END OF RAMP AT DOOR STOOP

4"

3'-6"

2'-11"

1"

4"

TYP.

12

1:12 SLOPE

5'-0"

END OF RAMP AT PARKING LOT

END OF RAMP AT LANDING

4"

HEADER SCHEDULE	
SPAN (CLEAR OPENINGS)	HEADER SIZE
EXTERIOR OPENINGS TO 8'-0" MAX	(2)2x10'S
INTERIOR SPANS (NON-LOAD BEARING)	(2)2x4'S
INTERIOR SPANS UP TO 4'-0" (LOAD BEARING)	(2)2x6'S
INTERIOR SPANS 4'-0" TO 5'-11" (LOAD BEARING)	(2)2x8'S
INTERIOR SPANS 6'-0" TO 7'-11" (LOAD BEARING)	(2)2x10'S
INTERIOR SPANS 8'-0" TO 9'-11" (LOAD BEARING)	(2)2x12'S
ALL HEADERS TO HAVE PLYWOOD 1/2" PLYWOOD BET.	

1. PROVIDE DOUBLE JOISTS BELOW ALL BEARING WALLS PARALLEL TO JOIST SPAN, PERPENDICULAR TO JOIST SPAN SHALL PROVIDE SOLID BLOCKING.

NEW METAL SIDING

EDGE OF WAREHOUSE

NEW P.T. WOOD PORCH
w/HAND & GUARD RAILS

LEFT ELEVATION

SCALE: 1/4"=1'-0"

REMOVE WIRE FENCING
& REPLACE WITH NEW

NEW WOOD SIDING

NEW STAIR
w/HAND & GUARD RAILS

PERPENDICULAR TO JOIST SPAN, 12/7

12/7

RD RAILS

REMOVE WIRE FENCING & REPLACE WITH NEW

NEW WOOD SIDING

REMOVE EXISTING SEWER LINES

ADD NEW FOOTING

EDGE OF WAREHOUSE

NEW METAL SIDING

RIGHT (FRONT ST.) ELEVATION

SCALE: 1/4"=1'-0"