

SAMSUNG

POS Printers

Heavy-duty industry standard printers are compatible with PC or POS systems and cash drawers.



Samsung SRP-350 Thermal Receipt Printer



With speed, quality and value, the Samsung SRP-350 thermal receipt printer is clearly first in its class. It easily withstands the rigors of tough environments, printing receipts, coupons, logos or bar codes at 150mm (about 6 inches) per second. The user-friendly design incorporates a small footprint, drop-and-load paper insertion and a standard cable cover. The SRP-350 features a modular interface so changing the printer from an RS-232C or IEEE-1284 interface to USB or RS-485 is easily done.



SRP-350 thermal receipt printer shown actual size.

Features

- Fast 150mm/second (47.2/lps) print speed
- Multiple interface (standard RS-232C/IEEE-1284, option RS-485/USB)
- Compatible with competitor's emulations including Epson, Star, Citizen
- Saves installation space (compact size, wall mount option)
- Easy to use
 - Drop and print paper supply
 - Simple to eliminate paper jam
 - Compact design
- Auto cutter
- Near-end sensor and paper-end sensor

SRP-270/350 Applications

- POS System
- Kitchen Printer
- Banking
- Kiosk
- Credit Card Authorization
- Data Logging
- Measuring Equipment



Drop and Load Paper Insertion



Standard Cable Cover



Easy to Change Interface Boards



Universal Power Adapter with Lock-in-Place Connector

Samsung SRP-270 Series Dot-Matrix Receipt Printer



The SRP-270 series two-color dot-matrix printer combines high reliability with a low cost of ownership. The SRP-270 is an ideal printer to install in any environment where high-volume transactions are required. Customers can select from three SRP-270 models (standard, auto-cutter, and auto-cutter with paper take-up). The SRP-270 offers a compact design in two different cabinet colors (ivory and dark gray). The SRP-270 features the most current interfaces such as RS-232C, Parallel, RS-485 and USB. The modular interfaces can be easily changed by only having to replace the interface board without opening the cabinet.

SRP-270A shown. Sample kitchen receipt shown actual size.

Features

- Very fast dot-matrix printing speed of 4.5 lines per second
- High quality easy to read print
- High reliability at 18,000,000 lines MCBP
- Compatible with competitor's emulations including Epson, Star, Citizen
- Compact design
- Easy to use
 - Plug & play
 - Auto paper loading for paper replacement
- Near-end sensor and paper-end sensor



Semi-Automatic Paper Loading



Optional Power Connection Security Tie Strap



Easy to Change Interface Boards



Standard SRP-270 Series Power Adapter

Specifications



Samsung SRP-350

Samsung SRP-270 Series

| | | |
|------------------------------------|--|--|
| Printing Method: | Direct Thermal Line | 9-Pin Serial Dot Matrix |
| Printer Speed: | 150mm/sec (47.2 lines per second) | 4.6 lps (40 columns) 8.4 lps (16 col.) |
| Dot Density/Printing Direction: | 180 dpi (7 dot/mm) | Bidirectional |
| Character Per Line: | Font A: 40 / 42 Font B: 33 / 35 | Font A: 40 / 42 Font B: 33 / 35 |
| Character Per Line/Character Size: | Font A: 42 Font B: 56 | Font A: 1.2W x 3.1H Font B: 1.6 x 3.1 |
| Paper Type: | 80mm Thermal Paper | 76mm Plain Paper |
| MCBF: | 37,000,000 Lines | 18,000,000 Lines |
| TPH Line: | 1 x 10 ⁸ Pulse, 100Km | Not Applicable |
| Character Set: | Alphanumeric: 95 International: 32 | Alphanumeric: 95 International: 32 |
| Extended Graphic: | 128 x 7 Page (1 Space Page) | 128 x 8 Page |
| Barcode: | EAN-13, EAN-8, Code 39, 93, 128, ITF, Code Bar, UPC-A, UPC-E | Not Applicable |
| Emulation: | Epson, Citizen, Star | Epson, Citizen, Star |
| Driver: | Windows 3.1/95/98/2000/NT | Windows 95/98/2000/NT |
| Sensor: | Near-End Sensor, Paper-End Sensor | Near-End Sensor, Paper-End Sensor |
| Drawer Port: | 2 Port | 1 Port (Maximum 2 Drawer) |
| Interface: | Serial, Parallel, RS-485, USB | Serial, Parallel, RS-485, USB |
| Power Supply (Adapter): | AC 120V ~ 230V ± 10% (Included) | AC 120V ~ 230V ± 10% (Included) |
| Data Buffer: | 4 kb | 4 kb |
| Power Consumption: | Standby: 28.8W; Operating: 55.2W | 0.21A / 25W |
| Operating Temperature: | 40° ~ 114°F | 40° ~ 114°F |
| Operating Humidity: | 10% ~ 90% | 10% ~ 90% |
| Dimensions: | 5-11/16"W x 7-9/16"L x 5-7/8"H | 270A = 6-5/16"Wx9-11/16"Lx5-1/8"H |
| | — | 270C = 6-5/16"Wx9-11/16"Lx5-7/8"H |
| | — | 270D = 6-5/16"Wx11-9/16"Lx6-1/4"H |
| Weight: | 4 lbs. (1.8 kg) | 5.3 lbs. (2.4 kg) |

All product features are subject to change without notice.