

Depository Safes

PROVIDES IMMEDIATE DEPOSITS FOR CASH AND MISCELLANEOUS VALUABLES.



DSC2714KC



DSF2014 W/ESL10 LOCK

Instant protection from Hold-up and Burglary.

Even though the safe is locked, deposits can be made via a top loading rotary hopper or a front loading deposit door.

AMSEC's exclusive saw tooth baffle resists contents from being removed through the deposit opening. A wide variety of sizes and designs are available to suit your exact security requirements. Each safe can be equipped with a Group II lock, Bank service dual control key locks or electronic key pad locks with management features such as time delay, duress control or multiple users.

Reversed doors available on the 2014 and 2714 size.

MODEL NO.	INSIDE		OUTSIDE*		DOOR OPENING	CAPACITY CUBIC INCH	WEIGHT LBS.
	H	W x D	H	W x D	H x W		
DST2014	11-1/2	10 x 13-3/4 x 11	20	14 x 14	9-3/4 x 9-3/4	1,739	100
DSF2014	10	13-3/4 x 11	20-1/4	14 x 14	9-3/4 x 9-3/4	1,513	94
DST2714	18-1/2	18 x 13-3/4 x 11	27-1/4	14 x 14	9-3/4 x 9-3/4	2,798	120
DSF2714	18-1/2	18 x 13-3/4 x 11	27-1/4	14 x 14	9-3/4 x 9-3/4	2,798	110
DST3214	12	13-3/4 x 11 ^{TOP}	32-1/4	14 x 14	9 x 8-1/2	1,815	152
	11-1/4	13-3/4 x 11 ^{BTM}			9 x 8-1/2	1,702	
DSF3214	12	13-3/4 x 11 ^{TOP}	32-1/4	14 x 14	9 x 8-1/2	1,815	144
	11-1/4	13-3/4 x 11 ^{BTM}			9 x 8-1/2	1,702	
DST2731	18-1/2	14-3/8 x 18 ^{LEFT}	27-1/4	30-3/4 x 21	9 x 8-1/2 ^L	4,579	276
	27	16 x 18 ^{RIGHT}			22-1/2 x 13 ^R	7,776	
DSF2731	18-1/2	14-3/8 x 18 ^{LEFT}	27-1/4	30-3/4 x 21	9 x 8-1/2 ^L	4,579	276
	27	16 x 18 ^{RIGHT}			22-1/2 x 13 ^R	7,776	

* Add 2" to Outside Depth for dial and handle projection.

T=Top Loading, F=Front Loading, R=Reverse hopper, K=Keylock, C=Combo lock.