



SEE DWG A-6 FOR FLOOR PLAN W/STAIRS  
 1 HR WALL 10' EA SIDE OF EXIT OPENING-SEE DWG A-2, A-3  
 TYPICAL EA 2nd FLOOR EXIT-FROM GROUND TO 22' ABOVE GROUND. UL# U468

1 HR CONSTRUCTION ON 1 LAYER 5/8" FIRE RATED GYP BRD EA SIDE OF INTERIOR WALL & CEILING IN MAIN DOOR W/ FIRE DAMPER IN DOOR RETURN AIR LOUVER.

\* UL#W415  
 USG #WP1200

1 HR WALL 10' EA SIDE OF EXIT OPENING. DWG A-3. TYPICAL EA 2nd FLOOR EXIT-FROM GROUND TO 22' ABOVE GROUND. UL# U468

\* 1 HR CONSTRUCTION ON 1 LAYER 5/8" FIRE RATED GYP BRD EA SIDE OF INTERIOR WALL & CEILING IN MAIN DOOR W/ FIRE DAMPER IN DOOR RETURN AIR LOUVER.

\* 1 HR CONSTRUCTION ON 1 LAYER 5/8" FIRE RATED GYP BRD EA SIDE OF WALLS & CEILING.

1st FLOOR PLAN  
 SCALE 1/4"=1'-0"

REVISED 4/18/98

BEN'S FORD BAPTIST CHURCH  
 EDUCATIONAL BUILDING

BEN'S FORD BAPTIST CHURCH  
 BOGALUSA LOUISIANA

DAMMON ENGINEERING INC  
 ARCHITECTS - ENGINEERS  
 737 ROBERT ROAD, SUITE 1  
 SLIDELL, LA. 70458

VIEWE  
 FIRE  
 LAUDU

SCALE  
 FILE  
 JOB NO.  
 DATE 4/13/98  
 SHEET  
 A-1