



1ST LEVEL FLOOR PLAN
SCALE 1/4"=1'-0"

CONTRACTOR TO VERIFY THAT ALL EXISTING PANIC HARDWARE IS IN PLACE, OPERABLE, AND COMPLIANT WITH THE REQUIREMENTS OF IBC 1002.3 (TYPICAL ALL DOORS)

NOTES:

- SPRAY FOAM ON UNDER SIDE OF ROOF PANELS AND SUPPORTS
- INSULATE EXTERIOR WALLS WITH STANDARD METAL BUILDING INSULATION THAT MEETS CODE
- NO SPRINKLERS THEREFORE NO LOAD CALCULATIONS REQUIRED
- HVAC UNITS ARE ON THE GROUND SEE PLANS FOR APPROXIMATE LOCATION

ASSEMBLY-GROUP A
OCCUPANCY RATINGS:
50 TO 270 OCCUPANTS;
ASSEMBLY TYPES: GROUP A-2

IBC 2021
WFCM
ECC 2021
40 MPH WIND SPEED
EXPOSURE B
DESIGN WINDS THE PRESCRIPTIVE
ENERGY CODE REQUIREMENTS
CLIMATE ZONE 2
MANUAL J CALCULATIONS BY OTHERS

BUILDING IS NOT LOCATED IN A
WINDBORNE DEBRIS PROTECTION REGION

THERMAL COMPONENT CRITERIA (U-FACTOR AND R-VALUE) (MAX. SHGC = 0.25 FOR GLAZING)			
MAXIMUM GLAZING PERCENTAGE	GLAZING U-FACTOR	WALLS R-VALUE	FLOORS R-VALUE
15%	0.30	R-5	R-5

R-5 DUCT INSULATION
ATTIC ACCESS INSULATED
INSULATE HOT/COLD WATERLINE IN UNCONDITIONED ATTIC AND CRAWFACES.
PURGE OUT 24 HOURS AS REQUIRED FOR BATT INSULATION AT CEILING/CRAWL SPACE OR USE SPRAYED FOAM INSULATION IF ACCEPTABLE.

NOTES

- CONTRACTOR SHALL SELECT WINDOW & DOOR PRODUCTS MEETING THE ENERGY EFFICIENCY REQUIREMENTS OF THE BUILDING CODE
- CONTRACTOR SHALL SELECT WINDOW & DOOR PRODUCTS MEETING WIND DESIGN PRESSURE REQUIREMENTS OF IBC 602
- SAFETY GLAZING (TEMPERED GLASS) IS REQUIRED AT LOCATIONS IDENTIFIED IN BC 2406
- PROVIDE CODE COMPLIANT HAND RAIL AT PORCH AND STAIRS
- OPENING IN THE BUSINESS SHALL BE PROTECTED BY 45 MIN. RATED DOORS

WINDOW SCHEDULE

MARK	DESCRIPTION	HDR
AA	6040 VINYL FIXED GLASS	13'-4"

DOOR SCHEDULE

MARK	WIDTH	HEIGHT	THICK.	DESCRIPTION
1	6'-0"	8'-0"	1 3/4"	SEE ELEVATION
2	6'-0"	8'-0"	1 3/8"	PR. 3080 RAISED PANEL INT.
3	3'-0"	8'-0"	1 3/8"	RAISED PANEL INTERIOR
4	2'-8"	8'-0"	1 3/8"	RAISED PANEL INTERIOR
5	3'-0"	8'-0"	1 3/8"	PR. 1680 RAISED PANEL INT.
6	3'-0"	-	-	BATHROOM STALL DOOR
7	2'-4"	-	-	BATHROOM STALL DOOR
8	3'-0"	8'-0"	1 3/4"	RAISED PANEL EXTERIOR

1ST LEVEL FLOOR PLAN

TRANSFERS
TRUE LIFE CHURCH
6216 AIRPORT ROAD
ST. TAMMANY PARISH, LA

AREA		AREA U.B.
LOWER LEVEL HEATED & COOLED SPACE	10,080	
DRIVE THRU CAR-PORT	1,330	
TOTAL AREA UNDER B/W	11,410	
UPPER LEVEL STORAGE	494	

HOUSE PLANS by
DesignTech
OF LOUISIANA, LLC
St. Tammany Parish, LA
SULZBERG 288-SHT-0000

CODE	REVISED	DATE	INDEX
0	10080	11/10	13069

DESIGNED BY: JWC
CHECKED BY: DWH
DATE: 4-11-24
SHEET SIZE: 36" X 60"
SCALE: A-1

© 2024 DesignTech of Louisiana, LLC. ALL RIGHTS RESERVED.
E-MAIL: houssplans@designtechusa.com