



TYPICAL WALL PANEL NOTES

1. SET CAST IN-PLACE CONCRETE WALL PANEL NOTES.
2. SET ORIGINAL NOTES, STATIONS, "CONCRETE" AND STRUCTURAL STEEL, FOR CONCRETE, REINFORCEMENT BARS, AND DISBURD PLATE SPECIFICATIONS.
3. PANEL LIFT REINFORCEMENT SHALL BE AS FOLLOWS:

REINFORCEMENT	
8# AT 12" O.C. VERTICAL	
8# AT 12" O.C. HORIZONTAL	
7# TO 8# INCLUSE	
8# AT 12" O.C. VERTICAL, EACH FACE	
8# AT 12" O.C. HORIZONTAL, EACH FACE	
4. THE CONTINUITY OF THE WALL PANEL SHALL BE MAINTAINED THROUGHOUT THE ENTIRE LENGTH OF THE WALL. THE WALL SHALL BE CONSIDERED AS A SINGLE UNIT. THE WALL SHALL BE CONSIDERED AS A SINGLE UNIT. THE WALL SHALL BE CONSIDERED AS A SINGLE UNIT.
5. REMOVE 1-# 8# BARS FROM EACH END OF THE WALL PANEL AT THE TOP AND BOTTOM AND SETS OF EACH PANEL AT THE HEAD, CHASE AND FOOT. REMOVE 1-# 8# BARS FROM EACH END OF THE WALL PANEL AT THE TOP AND BOTTOM AND SETS OF EACH PANEL AT THE HEAD, CHASE AND FOOT.
6. PROVIDE 1-# 8# BARS FROM EACH END OF THE WALL PANEL AT THE TOP AND BOTTOM AND SETS OF EACH PANEL AT THE HEAD, CHASE AND FOOT.
7. UNLESS OTHERWISE NOTED ON THE PANEL DETAIL, PROVIDE 3-# VERTICAL BARS FULL HEIGHT AT THE HEAD/CHASE CORNER AND 3-# VERTICAL BARS FULL HEIGHT AT THE FOOT/CHASE CORNER.
8. ALL PANEL LIFT 1-# 8# BARS FROM EACH END OF THE WALL PANEL AT THE TOP AND BOTTOM AND SETS OF EACH PANEL AT THE HEAD, CHASE AND FOOT. REMOVE 1-# 8# BARS FROM EACH END OF THE WALL PANEL AT THE TOP AND BOTTOM AND SETS OF EACH PANEL AT THE HEAD, CHASE AND FOOT.
9. THE GENERAL CONTRACTOR SHALL REVIEW AND VERIFY ALL PANEL DIMENSIONS, OPENINGS, BARS AND JOIST POCKET LOCATIONS. FIELD PANEL LOCATIONS AND BARS ARE TO BE TIED TO THE MAIN STEEL TOWARD THE EXTERIOR FACE OF THE WALL PANEL.
10. THE PANELS ARE TO BE TIED TO THE MAIN STEEL TOWARD THE EXTERIOR FACE OF THE WALL PANEL.
11. GENERAL NOTES OF THIS DRAWING SHALL BE OBSERVED. CHECK FOR THE MOST RECENT REVISIONS. SEE ADDITIONAL NOTES FOR THIS DRAWING.
12. THE PANELS HAVE BEEN DESIGNED FOR THE IN-SERVICE CONDITION ONLY. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR THE PANEL LIFTING DESIGN AND METHOD. CONTRACTOR SHALL DISTRIBUTE LOADS TO THE SLAB ON GRADE IN SUCH A MANNER SO AS NOT TO OVERLOAD THE WALL PANELS.
13. UPON RECEIPT OF THE PANELS, THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR THE PANEL LIFTING DESIGN AND METHOD. CONTRACTOR SHALL DISTRIBUTE LOADS TO THE SLAB ON GRADE IN SUCH A MANNER SO AS NOT TO OVERLOAD THE WALL PANELS.
14. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR THE PANEL LIFTING DESIGN AND METHOD. CONTRACTOR SHALL DISTRIBUTE LOADS TO THE SLAB ON GRADE IN SUCH A MANNER SO AS NOT TO OVERLOAD THE WALL PANELS.
15. PROPOSED REVISIONS TO THIS DRAWING SHALL BE SUBMITTED TO THE ARCHITECT FOR REVIEW.

GENERAL COMPLETION OF WALL PANELS



HAYNES WHALEY ASSOCIATES, INC.
 Structural Engineering
 Houston, Texas
 713-227-0811
 713-227-0812 fax

811 Rock Street
 Suite 101
 Houston, Texas 77002

Chem C. House, Jr., AIA
 Edward M. Bell, Jr., AIA
 William M. Burwell, AIA

Owens & Minor Medical, Inc.

ISSUE FOR PERMIT
 20 February 1996
 14 March 1996