


Fixed Intake/Exhaust Louvers



No. 4FZF3



Modular units seamlessly fit together for custom openings. Channel style frame is 4" deep. Blades are positioned at approximately 45° and spaced approximately 4" center to center. Each unit includes pre-installed bird screen.

**GALVANNEALED STEEL**

Very fine matte finish acts like a primer, easily accepts paint, and provides corrosion resistance.

**ALUMINUM**

Strong, lightweight, and corrosion resistant.

**DRAINABLE ALUMINUM**


Channels rain water away from blades and down the jambs, eliminating cascading.

Outside H (in.)	Outside W (in.)	Min. Wall Opening (in.)	Max. Intake (cfm)	Max. Exhaust (cfm)	GALVANNEALED STEEL			ALUMINUM			DRAINABLE ALUMINUM		
					Free Area (sq. ft.)	Item No.	\$ Each	Free Area (sq. ft.)	Item No.	\$ Each	Free Area (sq. ft.)	Item No.	\$ Each
17½	17½	18H x 18W	744	1063	0.622	4FZG3	164.50	0.622	4FZF3	146.90	0.885	5NKJ2	183.75
23½	23½	24H x 24W	1342	1918	1.384	4FZG4	196.00	1.384	4FZF4	218.25	1.878	5NKJ3	232.00
23½	35½	24H x 36W	2028	2897	2.175	4FZG7	225.50	2.175	4FZF7	264.75	2.951	5NKJ6	287.50
29½	29½	30H x 30W	2115	3022	2.234	4FZG6	265.75	2.234	4FZF6	275.50	2.930	5NKJ5	310.25
35½	23½	36H x 24W	2028	2897	2.091	4FZG5	243.75	2.091	4FZF5	256.00	2.917	5NKJ4	294.00
35½	35½	36H x 36W	3063	4376	3.286	4FZG8	314.50	3.286	4FZF8	359.00	4.583	5NKJ7	372.75
35½	47½	36H x 48W	4099	5855	4.481	4FZH1	359.50	4.481	4FZG1	407.50	6.216	5NKJ9	492.00
47½	35½	48H x 36W	4099	5855	4.397	4FZG9	362.25	4.397	4FZF9	426.00	6.250	5NKJ8	465.50
47½	47½	48H x 48W	5484	7834	5.996	4FZH2	454.50	5.996	4FZG2	455.50	8.477	5NKK0	596.00

Fixed-Height Adjustable-Width Intake/Exhaust Louvers



No. 4F422



Tabbed louvers lock securely into frame, providing smooth finish and clean appearance. 5/32 x 1/2" oblong mounting holes. Blades are set at a 45° angle, 4" spacing. Use multiple louvers when larger sizes are needed. Each includes 2 x 2" bird screen and fasteners.

**G-90 GALVANIZED STEEL**

4"-deep G-90 galvanized steel frame has 2" flanges.

**0.040" ALUMINUM**

For extra corrosion resistance in problem environments. 4" deep, 0.04" aluminum frame has 2" flange.

Outside H (in.)	Outside W (in.)	Min. Wall Opening (in.)	Max. Intake (cfm)	Max. Exhaust (cfm)	Free Area (sq. ft.)	G90 GALVANIZED STEEL		0.040" ALUMINUM	
						Item No.	\$ Each	Item No.	\$ Each
18	16 to 24	14H x 12W	616	875	0.360 to 0.550	4F421	88.20	4F951	108.30
18	28 to 46	14H x 24W	1565	2240	0.740 to 1.310	2FTV2	187.25	2FTV4	238.25
22	22 to 28	18H x 18W	1050	1500	0.730 to 0.980	3C972	130.55	4F952	165.25
22	28 to 46	18H x 24W	2010	2875	0.980 to 1.750	2FTV5	202.50	2FTV9	256.00
28	22 to 34	24H x 18W	1750	2500	1.140 to 1.950	3C973	153.50	4F953	204.50
28	40 to 52	24H x 36W	3030	4330	2.350 to 3.150	2FTY1	231.75	2FTX2	321.50
34	25 to 40	30H x 21W	2625	3750	1.620 to 2.830	4F422	215.00	4F954	300.00
40	28 to 40	36H x 24W	3150	4500	2.350 to 3.570	3C974	259.50	4F955	363.50
40	40 to 52	36H x 36W	4200	6000	3.570 to 4.790	3C975	347.25	4F956	457.25
46	28 to 46	42H x 24W	4290	6125	3.160 to 5.610	4F423	428.75	4F957	513.50
52	28 to 40	48H x 24W	5200	6000	3.230 to 4.900	3C976	387.50	4F958	460.00
52	40 to 52	48H x 36W	5600	8000	4.900 to 6.570	3C977	462.50	4F959	563.50

Combination Louver Dampers



No. 5NKH6



No. 5NKP0

Mill-finish extruded aluminum drainable frame is 4" deep, 0.081" thick, and has 45° fixed louvers spaced on 4" centers, with pivoting louvers and TPV seals for weathertight closure. 1/2" flattened birdscreen is mounted on exterior.

Damper is manually operated; optional actuator motor No. 5NKP0 (sold separately) automatically closes damper if a power failure occurs. Includes vertical mounting bracket, linkage, and 36" leads with junction box.

Outside H (in.)	Outside W (in.)	Min. Wall Opening (in.)	Max. Intake (cfm)	Max. Exhaust (cfm)	Free Area (sq. ft.)	Item No.	\$ Each
17½	17½	18H x 18W	438	625	0.521	5NKH6	333.50
23½	23½	24H x 24W	1005	1444	1.349	5NKH7	438.50
29½	29½	30H x 30W	1724	2475	2.203	5NKH8	561.50
35½	35½	36H x 36W	2406	3781	3.667	5NKH9	649.50
41½	41½	42H x 42W	3413	4875	5.010	5NKJ0	884.50
47½	47½	48H x 48W	5027	7219	7.109	5NKJ1	1,018.00

Accessory

Optional Actuator Motor, 100 to 240V, 50/60 Hz, For Use With Dayton Combination Louver Dampers

5NKP0 ✓ 332.25