



FLOOR PLAN
SCALE: 3/16"=1'-0"

DOOR & HARDWARE SCHEDULE		NO.	SIZE	TYPE	FRAME	HINGE	LOCK	ACCESSORIES	RATINGS	REMARKS
1	3/05/08	1	3/05/08	SOLID WOOD	GLASS	ALUM.	VERT. ROLLING	STEEL	STEEL	WOOD
2	3/05/08	2	3/05/08	ALUM.	WOOD	WOOD	DBL SWING	BUTT	BURGLERPRF	ROLL UP
3	12/05/10	3	12/05/10	STEEL	STEEL	STEEL	PASSAGE	PRIVACY	DEADBOLT	KEYED HANDLE
4	3/05/08	4	3/05/08	STEEL	ALUMINUM	WOOD	PUSH PULL	PANIC	THRESHOLD	WEATHERSTRIP
										DOOR STOP
										FULL GLASS
										CLOSER
										FRONT EXTERIOR
										INTERIOR
										BACK EXTERIOR

WINDOW SCHEDULE		NO.	SIZE	TYPE	FRAME	GLASS	LITES	ACCESS.	REMARKS
1	3/05/08	1	3/05/08	FIXED	STEEL	PLAIN	15 LITES	SCREEN	
2	3/05/08	2	3/05/08	VERT. SLIDE	STEEL	INSULATED	2/2	SHUTTER	
3	3/05/08	3	3/05/08	HORIZ. SLIDE	STEEL	INSULATED	2/2	NONE	
4	3/05/08	4	3/05/08	CIRCLEHEAD	STEEL	INSULATED	2/2	NONE	
5	3/05/08	5	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
6	3/05/08	6	3/05/08	TINTED	STEEL	INSULATED	2/2	NONE	
7	3/05/08	7	3/05/08	PLAIN	STEEL	INSULATED	2/2	NONE	
8	3/05/08	8	3/05/08	WIRED GLASS	STEEL	INSULATED	2/2	NONE	
9	3/05/08	9	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
10	3/05/08	10	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
11	3/05/08	11	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
12	3/05/08	12	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
13	3/05/08	13	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
14	3/05/08	14	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
15	3/05/08	15	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
16	3/05/08	16	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
17	3/05/08	17	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
18	3/05/08	18	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
19	3/05/08	19	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
20	3/05/08	20	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
21	3/05/08	21	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
22	3/05/08	22	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
23	3/05/08	23	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
24	3/05/08	24	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
25	3/05/08	25	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
26	3/05/08	26	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
27	3/05/08	27	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
28	3/05/08	28	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
29	3/05/08	29	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
30	3/05/08	30	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
31	3/05/08	31	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
32	3/05/08	32	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
33	3/05/08	33	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
34	3/05/08	34	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
35	3/05/08	35	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
36	3/05/08	36	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
37	3/05/08	37	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
38	3/05/08	38	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
39	3/05/08	39	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
40	3/05/08	40	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
41	3/05/08	41	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
42	3/05/08	42	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
43	3/05/08	43	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
44	3/05/08	44	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
45	3/05/08	45	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
46	3/05/08	46	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
47	3/05/08	47	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
48	3/05/08	48	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
49	3/05/08	49	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
50	3/05/08	50	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
51	3/05/08	51	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
52	3/05/08	52	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
53	3/05/08	53	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
54	3/05/08	54	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
55	3/05/08	55	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
56	3/05/08	56	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
57	3/05/08	57	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
58	3/05/08	58	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
59	3/05/08	59	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
60	3/05/08	60	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
61	3/05/08	61	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
62	3/05/08	62	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
63	3/05/08	63	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
64	3/05/08	64	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
65	3/05/08	65	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
66	3/05/08	66	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
67	3/05/08	67	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
68	3/05/08	68	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
69	3/05/08	69	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
70	3/05/08	70	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
71	3/05/08	71	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
72	3/05/08	72	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
73	3/05/08	73	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
74	3/05/08	74	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
75	3/05/08	75	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
76	3/05/08	76	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
77	3/05/08	77	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
78	3/05/08	78	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
79	3/05/08	79	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
80	3/05/08	80	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
81	3/05/08	81	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
82	3/05/08	82	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
83	3/05/08	83	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
84	3/05/08	84	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
85	3/05/08	85	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
86	3/05/08	86	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
87	3/05/08	87	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
88	3/05/08	88	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
89	3/05/08	89	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
90	3/05/08	90	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
91	3/05/08	91	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
92	3/05/08	92	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
93	3/05/08	93	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
94	3/05/08	94	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
95	3/05/08	95	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
96	3/05/08	96	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
97	3/05/08	97	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
98	3/05/08	98	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
99	3/05/08	99	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	
100	3/05/08	100	3/05/08	ALUMINUM	STEEL	INSULATED	2/2	NONE	

ROOM FINISH SCHEDULE		NO.	FINISH	REMARKS
1	3/05/08	1	CARPET	
2	3/05/08	2	CONCRETE	
3	3/05/08	3	VCT	
4	3/05/08	4	NONE	
5	3/05/08	5	CERAMIC TILE	
6	3/05/08	6	RUBBER WALL BASE	
7	3/05/08	7	WOOD BASE	
8	3/05/08	8	NONE	
9	3/05/08	9	CERAMIC TILE	
10	3/05/08	10	GYPSUM BOARD	
11	3/05/08	11	NONE	
12	3/05/08	12	2x2 LAY-IN PANELS	
13	3/05/08	13	GYPSUM BOARD	
14	3/05/08	14	NONE	

- GENERAL NOTES:**
- INSULATION AND INSULATION ASSEMBLIES SHALL MEET THE REQUIREMENTS OF SECTION 718, INTERNATIONAL BUILDING CODE, 2006.
 - CONCEALED INSULATION SHALL HAVE A FLAME SPREAD OF NOT MORE THAN 25 AND A SMOKE DEVELOPED INDEX OF NOT MORE THAN 450.
 - FACING SHALL COMPLY WITH IBC 718.2.1.
 - PROVIDE 5'X5' LANDINGS OUTSIDE EXTERIOR DOOR LEVEL WITH THE FLOOR. THRESHOLDS SHALL BE NOT MORE THAN 1/2" IN HEIGHT AND SHALL BE REVEALED IF MORE THAN 1/4".
 - DIMENSIONS ARE TO CENTER LINE OR FACE OF STUDS, CENTER LINES OF COLUMNS OR FACE OF VINYL.
 - CONTRACTOR TO VERIFY ALL SITE CONDITIONS AND ALL DIMENSIONS PRIOR TO CONSTRUCTION.
 - MATERIALS SHALL BE NEW AND U.L. LISTED.
 - NO WORK SHALL BE CONCEALED UNTIL APPROVED BY LOCAL INSPECTORS.
 - CONSTRUCTION SHALL COMPLY WITH ALL CITY, STATE AND LOCAL CODES.
 - CONTRACTOR TO GUARANTEE WORK FOR ONE YEAR.
 - CONTRACTOR SHALL FURNISH WATER AND POWER FROM EXISTING SOURCES.
 - EXTERIOR CAULKING SHALL BE THICKAL CAULK.
 - PAINT GRADE TO BE SHERWIN WILLIAMS OR EQUIVALENT. ALL WORK TO RECEIVE 2 COATS.
 - PROVIDE CLEANUP ON A REGULAR BASIS. NO TRASH STORED IN BUILDING.
 - ALL BATT INSULATION SHALL HAVE A CLASS "A" (0-25) FLAME SPREAD IN COMPLIANCE WITH APPLICABLE CODE.
 - USE 6" STUDS AT ALL PLUMBING WALLS.
 - PROVIDE GALV. METAL PAN WITH DRAIN AT WATER HEATER LOCATION.
 - ALL CORNERS SHALL BE PROPERLY BRACED FOR WIND LOADS. A 48" SHEATHING SHALL BE PROVIDED EVERY 20 FEET OF WALL LENGTH.
 - FLOORING SHALL BE NON-SLIP.
 - LOCKS ON DOORS IN MEANS OF EGRESS SHALL NOT REQUIRE THE USE OF A KEY (INTERIOR SIDE). SPECIAL DEVICE OR SPECIAL KNOWLEDGE TO OPEN IN THE DIRECTION OF EGRESS. ALL DOORS SHALL HAVE LE