



FEATURES & SPECIFICATIONS

INTENDED USE

Ideal for applications where accurate color rendition is critical – signs, entry monuments, residential facades and landscaping.

CONSTRUCTION

Compact, rugged die-cast aluminum housing is ribbed for maximum heat dissipation. TQ has a die-cast aluminum doorframe, TQE lens attaches via tool-less clips. Finish is polyester powder paint for lasting durability.

OPTICAL SYSTEMS

Anodized aluminum reflector with high efficiency and wide beamspread. Tempered glass lens with high temperature gasketing to inhibit entrance of external contaminants.

Double-ended quartz lamp included in carton.

INSTALLATION

Adjustable mounting knuckle with 1/2" NPS threaded stem mounts to standard outlet boxes.



LISTING

UL/CUL listed suitable for wet locations (25° C maximum ambient temperature).

Catalog Number	
Notes	Type

Floodlighting TQ/TQE

500W QUARTZ



Height: 6.5" (16.51 cm)
Width: 8.875" (22.54 cm)
Depth: 3.5" (8.89 cm)
Weight: 2.07lbs/.93 kg

ORDERING INFORMATION

Example: **TQE 500 120 LPI**

Choose the boldface catalog nomenclature that best suits your needs and write it on the appropriate line. Order accessories as separate catalog numbers (shipped separately).

Series	500	120	Options	LPI
TQE TQ	Wattage /Source 500	Voltage 120	(blank) Bronze (standard) DWH White	LPI

TQ TQE 500 Quartz Floodlighting



Sheet#: TQ-TQE ©2000 Lithonia Lighting, Rev. 3/02 TQ-TQE.P65

Lithonia Lighting
Acuity Lighting Group, Inc.
Outdoor Lighting
One Lithonia Way, Conyers, GA 30012-3957
Phone: 770-922-9000 Fax: 770-918-1209
In Canada: 1100 50th Ave., Lachine, Quebec H8T 2V3
www.lithonia.com