

This document is not an ASTM standard and is intended only to provide the user of an ASTM standard an indication of what changes have been made to the previous version. Because it may not be technically possible to adequately depict all changes accurately, ASTM recommends that users consult prior editions as appropriate. In all cases only the current version of the standard as published by ASTM is to be considered the official document.



Designation: D 2980 – 71 (Reapproved 1996)



Designation: D 2980 – 02

Standard Test Method for Volume Weights, Water-Holding Mass, Moisture-Holding Capacity, and Air Capacity Porosity of Water-Saturated Saturated Peat Materials¹

This standard is issued under the fixed designation D 2980; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

¹ This test method is under the jurisdiction of ASTM Committee D-18 on Soil and Rock and is the direct responsibility of Subcommittee ~~D18.18~~ D18.22 on ~~Peats and Related Materials—Soil as a Media for Plant Growth.~~

Current edition approved ~~Sept. 20, 1974;~~ Nov. 10, 2002. Published ~~November 1974;~~ January 2003. Originally published as D 2980-71. Last previous edition D 2980-71(1996).

1. Scope

1.1 This ~~empirical~~ test method was designed to evaluate the aeration, water penetration, and water retention properties of peat under field conditions of water saturation.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

D 653 Terminology Relating to Soil, Rock, and Contained Fluids²

D 2974 Test Methods for Moisture, Ash, and Organic Matter of Peat and Other Organic Soils²

D 3740 Practice for Minimum Requirements for Agencies Engaged in the Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction²

D 4753 Specification for Evaluating, Selecting, and Specifying Balances and Scales for Use in Soil, Rock, and Construction Materials Testing²

D 6026 Practice for Using Significant Digits in Geotechnical Data³

E 11 Specification for Wire-Cloth Sieves for Testing Purposes⁴

3. Summary of Test Method

3.1 The test method sets up standardized conditions for measuring the volume and ~~weight mass of water-saturated~~ saturated peat. From these data, saturated volume ~~weights, water-holding masses,~~ moisture-holding capacity (on a ~~weight mass~~ and volume basis), dry peat volumes, and ~~air volumes~~ porosity can be determined.

4. Significance and Use

4.1 ~~A~~ This test method ~~that will measure under conditions of water saturation,~~ measures the air spaces of peat and the ~~moisture-holding capacity on either a mass and/or a volume basis as well as the weight basis provides useful information in evaluating peat materials. under conditions of saturation.~~ If large air spaces are present, ~~high water penetration and aeration exist.~~ If air can penetrate easily. If spaces are smaller, ~~retention of the water holding capacity is increased.~~ Water ~~retention would be greater holding capacity is larger~~ in humified peat materials (small ~~air inter-particulate~~ spaces), whereas water ~~penetration and aeration would be greater air-penetration is larger~~ in unhumified peat (larger ~~air inter-particulate~~ spaces). The ~~air spaces~~ can also be a ~~measure~~ an indication of the oxygen available to the plant roots.

4.2 The quality of the result produced by this standard is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice D 3740 are generally considered capable

² This test method is currently undergoing an extensive review by

² Annual Book of ASTM Committee D-18, Standards, Vol 04.08.

³ Annual Book of ASTM Standards, Vol 04.089.

⁴ A Cenco No. 14782-2 drying tube has been found suitable for this purpose.

⁴ Annual Book of ASTM Standards, Vol 14.02.

of competent and objective testing/sampling/inspection/etc. Users of this standard are cautioned that compliance with Practice D 3740 does not in itself assure reliable results. Reliable results depend on many factors; Practice D 3740 provides a means of evaluating some of those factors.

5. Apparatus

5.1 *Dispensing Apparatus*—Two dispensing burets, 250-mL capacity in 1-mL subdivisions, ± 2 -mL tolerance, pinch-cock type; a one-hole No. 6 rubber stopper; straight polyethylene drying tube with serrated rubber tubing fittings, 150 mm long, 19 mm ($\frac{3}{4}$ in. (19 mm) in) in outside diameter, 16 mm ($\frac{5}{8}$ in. (16 mm) in.) in inside diameter;⁵ a 4-mesh sieve; a balance; a moisture-proof (air-tight) container; a 5-gal (20-L) bottle equipped with a siphon device; and a stainless steel sieve circle about 16 mesh and 28.7 mm in diameter to be attached to one end of the drying tube and sealed. (A soldering iron is useful.) Adjust the length of the tube to match conveniently the graduation of the buret; then scallop the end without the sieve to allow for water drainage, and insert the tube into the dispensing buret with the sieve side up.

6. Sample

6.1 Place a representative field sample on a square rubber sheet, paper, or oil cloth. Reduce the sample to the quantity required by quartering and place in a pre-tared moisture-proof container. Work rapidly to prevent moisture losses.

7. Procedure

7.1 Determine the moisture content on a separate test specimen by Method I or II of Test Methods D 2974.

7.1.1 Weigh the buret fitted with the plastic tube and screen. Working rapidly to prevent moisture losses, mix the sample thoroughly, place on top of a 4-mesh sieve, and shake until sieving is complete. Use only the portion that has passed through the sieve for the determination. Firmly pack the buret with ~~10 in. (250 mm)~~ 250 mm (10 in.) of the material passing the 4-mesh sample sieve as follows: Attach the rubber stopper to the delivery end of the buret. Add 20-mL portions of the sample, firmly tapping on the rubber stopper 3 times vertically from a height of ~~6 in. (150 mm)~~ 150 mm (6 in.) for a final height of 50 mm (10 in.) (This will ensure that the height of the final wet volume is ~~7.5 190 to 10 in. (190 to 250 mm. (7.5 to 10 in.))~~ 190 to 10 in. (190 to 250 mm. (7.5 to 10 in.))). Remove the stopper and weigh the buret to nearest 1 g.

7.1.2 Position the buret to use a sink as the drain. Place a ~~5-gal (20-L)~~ 20-L (5-gal) bottle equipped with a siphon device above the level of the buret. Connect the clamped rubber tubing of the siphon device to the buret by inserting glass tubing about ~~5 in. (125 mm) long~~ 125 mm (5 in.) and constricted at one end into the one-hole rubber stopper fitted tightly into the top of the buret. Attach the rubber tubing with the pinch clamp to the delivery end of the buret. Open both clamps and pass water through the sample for ~~not less more~~ more than 24 h, maintaining a water reservoir over the sample at all times. (Moss-type samples may float but gradually settle as the sample becomes wet.) After initial soaking, regulate the water flow through the column by adjusting the screw clamp at the delivery end of the buret. (The in-flow of water should be about equal to the out-flow; a flow of about 1 drop/s is suitable.) When the sample is ~~supersaturated,~~ saturated, close both clamps and let the sample settle in water for about 5 min. The top surface of the sample should be as level as possible.

7.1.3 Raise the buret and replace the rubber stopper on the delivery end of the buret with a 250-mL dispensing buret filled with water, using the rubber stopper for the connection. Connect the two burets tightly, with no air leaks. Remove the siphon device and open the outlet clamps on both burets to empty. (The suction created is equivalent to about 38 mm (15 in.) of water. Check for air leaks to ensure that the standard suction is exerted on the sample. It is important to remove excess water as described.) Measure the height of the wet peat. The height should be ~~7.5 190 to 10 in. (190 to 250 mm (7.5 to 10 in.))~~ 190 to 10 in. (190 to 250 mm (7.5 to 10 in.)). Record the volume in millilitres and weigh the buret, the plastic tube with the sieve, and the wet peat to the nearest 1 g. Wet the sample again as above for ~~not less more~~ more than 1 h, drain by suction, record the volume, and ~~weigh.~~ weigh mass. Repeat until consistent results are obtained.

8. Calculation

8.1 Calculate the saturated volume ~~weights,~~ mass, S , in grams per millilitre as follows:

As-received:

$$S = W_r/V_w \quad (1)$$

Oven-dried:

$$S = W_d/V_w \quad (2)$$

Wet:

$$S = W_w/V_w \quad (3)$$

where:

W_r = ~~weight~~ mass of test specimen as received, g,

⁵ A Cenco No. 14782-2 drying tube has been found suitable for this purpose.

- V_w = wet volume, mL,
 W_d = ~~weight~~ mass of dried test specimen, g = $W_r \times (100 - M)/100$,
 M = moisture, %, and
 W_w = ~~weight~~ mass of wet test specimen, g.

8.2 Calculate the ~~wa~~ moisture-holding capacity in percent as follows:

8.2.1 ~~Weight~~ Mass basis, W :

As-received:

$$W = [(W_w - W_r) \times 100]/W_r \quad (4)$$

Oven-dried:

$$W = [(W_w - W_d) - W_d] \times 100/W_d \quad (5)$$

8.2.2 Volume basis, V :

$$V = [(W_w - W_d) \times 100]/(V_w \times 1.0) \quad (6)$$

8.3 Calculate the dry peat volume, P , in percent as follows:

$$P = (W_d \times 100)/(V_w \times 1.4) \quad (7)$$

8.4 Calculate the ~~air volume~~, porosity, A , in percent as follows:

$$A = 100 - (V + P) \quad (8)$$

9. Report

9.1 Report the saturated volume-~~weights~~ mass to the nearest 0.01 g. Report percentage results to the nearest whole number.

10. Precision and Bias

10.1 *Precision*—Due to the nature of the soil or rock materials tested by this method it is either not feasible or too costly at this time to produce multiple specimens which have uniform physical properties. Any variation observed in the data is just as likely to be due to specimen variation as to operator testing variation. Subcommittee ~~D18.18~~ D18.22 welcomes proposals that would allow for development of a valid precision statement.

10.2 *Bias*—There is no accepted reference value for this test method, therefore, bias cannot be determined.

11. Keywords

~~11.1 peat; water; water retention~~

11.1 moisture; moisture holding capacity; peat; porosity

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).