



Standard Test Method for Acidity of Formaldehyde Solutions¹

This standard is issued under the fixed designation D 2379; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers the determination of the acidity of commercially available formaldehyde solutions.

1.2 For hazard information and guidance, see the supplier's Material Safety Data Sheet.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* Specific hazard statements are given in Section 7.

2. Referenced Documents

2.1 *ASTM Standards:*

D 1193 Specification for Reagent Water²

D 2380 Test Method for Methanol Content of Formaldehyde Solutions³

E 200 Practice for Preparation, Standardization, and Storage of Standard and Reagent Solutions for Chemical Analysis⁴

3. Summary of Test Method

3.1 A specimen is titrated with standard alkali to the bromthymol blue end point.

4. Significance and Use

4.1 This test method provides a measurement of acidity (as formic acid) in formaldehyde solutions. The results of these measurements can be used for specification acceptance.

5. Apparatus

5.1 *Buret*, 25-mL, calibrated in 0.1-mL divisions. A TFE-fluorocarbon resin stopcock is suitable for this purpose.

6. Reagents and Materials

6.1 *Purity of Reagents*—Reagent grade chemicals shall be used in all tests. Unless otherwise indicated, it is intended that

all reagents shall conform to the specifications of the Committee on Analytical Reagents of the American Chemical Society, where such specifications are available.⁵ Other grades may be used, provided it is first ascertained that the reagent is of sufficiently high purity to permit its use without lessening the accuracy of the determination.

6.2 *Purity of Water*—Unless otherwise indicated, references to water shall be understood to mean reagent water conforming to Type IV of Specification D 1193.

6.3 *Bromthymol Blue Indicator Solution* (1.0 g/L)—Dissolve 0.1 g of the water-soluble form of bromthymol blue indicator powder in 100 mL of water.

6.4 *Sodium Hydroxide, Standard Solution* (0.1 N)—Prepare and standardize 0.1 N sodium hydroxide (NaOH) solution as described in Practice E 200.

7. Hazards

7.1 Formaldehyde and formaldehyde solutions are hazardous and exposure to them should be minimized to avoid acute effects and possible sensitization. Consult your supplier's Material Safety Data Sheet for specific hazard information.

7.2 Sodium hydroxide solutions are corrosive and hazardous. Exercise steps to prevent contact with the skin or eyes. Consult supplier's Material Safety Data Sheet for specific hazard.

8. Procedure

8.1 Measure 50 mL of the sample into a 250-mL Erlenmeyer flask, add 3 or 4 drops of bromthymol blue indicator solution, and titrate with 0.1 N NaOH solution to a blue end point.

8.2 If good laboratory practice dictates that the concentration of NaOH be adjusted as a result of higher or lower acid levels, then adjust as necessary using Practice E 200, and titrate to a blue end point.

9. Calculation

9.1 Calculate the percent of formic acid as follows:

$$\text{Formic acid, weight \%} = [(V \times N \times 0.046)/(S \times D)] \times 100 \quad (1)$$

¹ This test method is under the jurisdiction of ASTM Committee D-1 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.35 on Solvents, Plasticizers, and Chemical Intermediates.

Current edition approved June 10, 1999. Published August 1999. Originally published as D 2379 – 65 T. Last previous edition D 2379 – 93.

² *Annual Book of ASTM Standards*, Vol 11.01.

³ *Annual Book of ASTM Standards*, Vol 06.04.

⁴ *Annual Book of ASTM Standards*, Vol 15.05.

⁵ *Reagent Chemicals, American Chemical Society Specifications*, American Chemical Society, Washington, DC. For suggestions on the testing of reagents not listed by the American Chemical Society, see *Analar Standards for Laboratory Chemicals*, BDH Ltd., Poole, Dorset, U.K., and the *United States Pharmacopoeia and National Formulary*, U.S. Pharmacopoeial Convention, Inc. (USPC), Rockville, MD.

where:

V = millilitres of NaOH solution, required for titration of the specimen,

N = normality of the NaOH solution,

0.046 = the milliequivalent weight of formic acid,

S = millilitres of sample used, and

D = specific gravity of sample.

The value of D from Test Method D 2380, may be used, although specific gravity estimated to the second decimal is adequate.

10. Report

10.1 Report the percent formic acid to the nearest 0.001 %. Duplicate determinations which agree within 0.002 % absolute are acceptable for averaging (95 % confidence level).

11. Precision and Bias

11.1 In an interlaboratory study of this test method, the within-laboratory standard deviation was found to be 0.0007 % absolute at 60 degrees of freedom, and the between-laboratories standard deviation 0.0031 % absolute at 9 degrees

of freedom. Based on these standard deviations, the following criteria should be used for judging the acceptability of results at the 95 % confidence level:

11.1.1 *Repeatability*—Two results, each the mean of duplicates, obtained by the same analyst on different days should be considered suspect if they differ by more than 0.002 % absolute.

11.1.2 *Reproducibility*—Two results, each the mean of duplicates, obtained by analysis in different laboratories, should be considered suspect if they differ by more than 0.010 % absolute.

NOTE 1—The above precision estimates are based on an interlaboratory study involving ten laboratories using three samples with two analysts performing duplicate runs on each of two days. The mean level of the acidity value of the samples studied was 0.02 %.

11.2 *Bias*—Bias of this test method has not been determined because primary standards do not exist.

12. Keywords

12.1 formaldehyde; formic acid

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 100 Barr Harbor Drive, West Conshohocken, PA 19428.