



Designation: D 4835 – 93 (Reapproved 1998)

AMERICAN SOCIETY FOR TESTING AND MATERIALS
100 Barr Harbor Dr., West Conshohocken, PA 19428
Reprinted from the Annual Book of ASTM Standards. Copyright ASTM

Standard Specification for Propylene Glycol Monomethyl Ether Acetate¹

This standard is issued under the fixed designation D 4835; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers propylene glycol monomethyl ether acetate (PMA).

NOTE 1—Propylene glycol monomethyl ether acetate (PMA) is a mixture of 1-methoxy-2-acetoxyp propane and 2-methoxy-1-acetoxyp propane.

1.2 For specific hazard information and guidance, consult the supplier's Material Safety Data Sheet for materials listed in this standard.

2. Referenced Documents

2.1 ASTM Standards:

D 1078 Test Method for Distillation Range of Volatile Organic Liquids²

D 1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)²

D 1364 Test Method for Water in Volatile Solvents (Karl Fischer Reagent Titration Method)²

D 1613 Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer, and Related Products²

D 4773 Test Method for Purity of Propylene Glycol Monomethyl Ether, Dipropylene Glycol Monomethyl Ether, and Propylene Glycol Monomethyl Ether Acetate²

E 300 Practice for Sampling Industrial Chemicals³

2.2 U.S. Federal Specification:

PPP-C-2020 Chemicals, Liquid, Dry, and Paste: Packaging of⁴

3. Properties

3.1 Propylene glycol monomethyl ether acetate (PMA) shall

conform to the following requirements:

Purity, min, weight %	99
Color, platinum-cobalt scale, max	15
Water, max, weight %	0.05
Distillation range, °C:	
Initial boiling point, min	140
Dry boiling point, max	150
Acidity (free acid as acetic acid), max, weight %	0.02 ⁴
Glycol ether, max, weight %	0.5

⁴Equivalent to 0.2 mg of potassium hydroxide (KOH) per gram of specimen.

4. Sampling

4.1 The material shall be sampled in accordance with Practice E 300.

5. Test Methods

5.1 The properties enumerated in this specification shall be determined in accordance with the following ASTM test methods:

5.1.1 *Gas Chromatographic Method*—Test Method D 4773.

5.1.2 *Color*—Test Method D 1209.

5.1.3 *Water*—Test Method D 1364.

5.1.4 *Acidity*—Test Method D 1613.

5.1.5 *Distillation Range*—Test Method D 1078.

6. Packaging and Package Marking

6.1 Package size shall be as agreed upon between the purchaser and the supplier.

6.2 Packaging shall conform to applicable carrier rules and regulations or when specified shall conform to Fed. Spec. PPP-C-2020.

7. Keywords

7.1 propylene glycol monomethyl ether acetate

¹ This specification is under the jurisdiction of ASTM Committee D-1 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.35 on Solvents, Plasticizers, and Chemical Intermediates.

Current edition approved May 15, 1993. Published July 1993. Originally published as D 4835 – 88. Last previous edition D 4835 – 89.

² *Annual Book of ASTM Standards*, Vol 06.04.

³ *Annual Book of ASTM Standards*, Vol 15.05.

⁴ Available from Standardization Documents Order Desk, Bldg. 4 Section D, 700 Robbins Ave., Philadelphia, PA 19111-5094.

NOTICE: This standard has either been superseded and replaced by a new version or discontinued. Contact ASTM International (www.astm.org) for the latest information.



The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 100 Barr Harbor Drive, West Conshohocken, PA 19428.