



Standard Practice for Data Exchange Format for Sewn Product Plotting Devices¹

This standard is issued under the fixed designation D 6959; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice describes a data format for transferring information from a sewn product computer aided design software program to a device that produces physical output, typically in the form of a printed or drawn image on paper.

1.2 This practice is based on a subset of the Hewlett Packard Graphics Language HPGL/2. Supported syntax and limitations are listed in 7.2. Unsupported syntax is listed in X1.1.

1.3 This practice only supports *X-Y* vector data and a limited set of additional functions. No provision is made to support bitmap/raster data used in applications like inkjet printing.

1.4 This practice supports a single system of units, an image fixed at 100 % scale and 1:1 aspect ratio. Scaling and custom unit systems are not supported.

1.5 This practice does not support curve interpolation or definitions. All curves are represented by discrete vectors (stroked) and are dependent on the resolution of the CAD software.

1.6 This practice requires that all coordinates are absolute, not relative, as defined in the HPGL/2 reference.

1.7 This practice only supports positive coordinates that are measured from a single *X-Y* origin point with coordinates 0,0.

1.8 This practice only supports fixed width fonts. Variable width fonts are not supported.

1.9 This practice intends to transfer a static image with no provision for editing.

1.10 This practice assumes monochromatic output. It does not support implied output colors.

1.11 This practice imposes no limits on the width or length of the plot data. Physical limitations imposed by the hardware and their effects on the output are the responsibility of the hardware manufacturer.

1.12 This practice does not support frame advance commands or any methods that insert multiple origin points or floating coordinate systems.

1.13 This practice limits the plot file to contain a single block of data demarked by a compatible header and terminator. Multiple blocks of data in a single file are not allowed.

1.14 The intended application of this practice is limited to the class of output devices found in the sewn product industries

that produce apparel, textiles, upholstery, and others that use soft or semi-rigid materials.

1.15 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

- D 6672 Practice for Formatting Cutting Data to Drive Numerically Controlled Fabric Cutting Machines²
- D 13.66 Terminology of Sewn Products²

3. Terminology

3.1 Definitions:

3.1.1 *command, n*—a two letter sequence, always written in capital letters, that governs interpretation of formatted data. Also known as a *syntax command*.

3.1.2 *data block, n*—an organized group of commands and parameters preceded by a header and followed by a terminator.

3.1.3 *header, n*—a specific group of commands required at the beginning of a data block.

3.1.4 *parameters, n*—values that modify the action of a command.

3.1.5 *plot file, n*—instructions organized in formatted blocks of ASCII characters and stored in a computer file which are used to control a plotter or printer.

3.1.6 *syntax command, n*—see *command*.

3.1.7 *terminator, n*—ASCII character(s) that signify the end of an instruction (with any associated parameters), or a data block.

4. Summary of Practice

4.1 Plot data are organized to allow a parsing algorithm to recognize adherence to the ASTM format then are written as a data block into a computer file.

4.1.1 A specific group of commands are required at the beginning of the data block, called a header.

4.2 Plot data follow a subset of the HPGL/2 ASCII language.

¹ This practice is under the jurisdiction of ASTM Committee D13 on Textiles and is the direct responsibility of Subcommittee D13.66 on Sewn Product Automation. Current edition approved Dec. 1, 2003. Published February 2004.

² *Annual Book of ASTM Standards*, Vol 07.02.

4.2.1 The practice specifies syntactical and parametric constraints to limit ambiguity.

4.2.2 Basic HPGL formatting is supported. Advanced HPGL functions are beyond the scope of the practice.

5. Significance and Use

5.1 This practice provides a common format that allows a computer design system to generate data that an output device can accurately reproduce independent of the hardware manufacturer.

6. Plot File

6.1 Plot data are written in data blocks of ASCII characters, one data block per computer file.

6.2 Data blocks are made up of commands.

6.2.1 Each command is a two-letter sequence (see 7) always written in CAPITAL letters.

6.2.2 An instruction and its associated parameters (if required) are terminated by the semi-colon (;) terminator. Other terminators are not supported that is mnemonic, <CR>, or <LF>.

6.3 Some commands are followed by parameters.

6.3.1 Parameters immediately follow the command with no separating space and come before the command terminator.

6.3.2 Multiple parameters are separated by a comma (,). Other separators are not supported that is blank space, etc. Strings of coordinates are not allowed; that is, PDX,Y,X,Y,X,Y.

6.4 Blocks of data that adhere to this practice begin and end in a specific way.

6.4.1 Blocks begin with specific commands in a defined order, commonly called a header, as follows (information in brackets, [], are variable):

IN; CO "ASTMXXXXX-XX"; CO "Author: [Author Name]"; CO "Creation Date: [DD-MM-YYYY]"; CO "Creation Time: [HH-MM on a 24 hour time scale]"; PA; DTETX,1; LM0; [All subsequent plot file data follow this header]...

6.4.2 Blocks are terminated with the ASCII file separator character, FS (decimal 28).

6.5 All coordinate data use the HPGL/2 default plotter-unit system.

6.5.1 1 plotter-unit = 0.025 millimeter (mm)

6.5.2 40 plotter-units = 1 mm

6.5.3 1016 plotter-units = 1 inch (in.)

6.5.4 3.39 plotter-units = 1 dot at 300 dots per in. (dpi)

7. Syntax

7.1 Syntax commands are used to govern interpretation of formatted data. The following is a list of the supported syntax and a brief description. Detailed summaries of the commands are outlined in 7.2. HPGL/2 commands not listed below are not supported by the practice and are documented in Appendix X1.

7.1.1 *CO*—Comments,

7.1.2 *DI*—Absolute Direction,

7.1.3 *DT*—Define Label Terminator,

7.1.4 *IN*—Initialize,

7.1.5 *LB*—Label,

7.1.6 *LM*—Label Mode,

7.1.7 *LT*—Line Type,

7.1.8 *PA*—Plot Absolute,

7.1.9 *PD*—Pen Down,

7.1.10 *PU*—Pen Up,

7.1.11 *SI*—Absolute character Size, and

7.1.12 *SP*—Select Pen.

7.2 The following descriptions outline the implementation of HPGL/2 syntax commands allowed by this practice. Unless otherwise noted, usage exactly follows the specification described in the agreed HPGL/2 reference.

7.2.1 *CO*—Comments. Parameters between quotes are ignored by the output device. This practice requires four sequential *CO* commands containing specific text as header data. These must immediately follow the *IN*; and precede the *PA*; syntax at the beginning of the file and use the format that follows. Information in brackets, [], are variable. Example:

CO "ASTMXXXXX-XX"; CO "Author: [Author Name]"; CO "Creation Date: [DD-MM-YYYY]"; CO "Creation Time: [HH-MM on a 24 hour time scale]";

7.2.2 *DI*—Absolute Direction. Specifies the direction characters in a label are drawn. In this practice, *DI* syntax only affects usage of *LB* and *SI*. Default values are *DI*1,0. Example:

...*DI*1,0;...

Result: defines label direction as horizontal, the default for this practice.

7.2.3 *DT*—Define Label Terminator (header only). Indicates the end of a text string associated with an *LB* command. This practice requires a single *DT* command near the end of the header immediately following the *PA* syntax. The required arguments for *DT* are *ETX* (decimal 03) and mode 1. These are the only allowed parameters. No other instances of *DT* are allowed. Example:

... *PA*;*DTETX*,1;...

Result: defines the label terminator as *ETX* (decimal 03). Mode "1" indicates that this character is not printed.

7.2.4 *IN*—Initialize (header only). Resets the configuration of the output device to defaults and raises the logical pen, equivalent to a *PU*; syntax command. Also indicates the beginning of a plot file conforming to this practice and is always the first syntax command in the header. No other instances of *IN* are allowed.

7.2.5 *LB*—Label. Prints the subsequent text string using the currently defined font. Requires the label terminator, *ETX*, at the end of the text string, as defined by the *DT* command included in the header. In this practice, *LB* syntax is only affected by the *DT*, *LM* and *SI* syntax. Example:

...*LBSM-FrontETX*;

Result: prints "SM-Front" at the current pen position.

7.2.6 *LM*—Label Mode (header only). Determines whether the *LB* command interprets characters in 8 or 16 bit segments. This practice requires a single *LM* command at the end of the header immediately following the *DT* syntax. The required argument for *LM* is 0 (8-bit mode). This is the only allowed parameter. No other instances of *LM* are allowed. Example:

... *DTETX*,1;*LM*0;...

Result: 8-bit mode, each byte is a character.

7.2.7 *LT*—Line Type. Determines the pattern of the drawn line. *LT* is allowed in two forms. *LT*; creates a solid line (the default line type). Non-solid line types are available only by using *LT* with three required parameters; *line_type*, *pattern_length* (always in millimeters), and *mode* (always 1). This practice only supports line types +2 through -2 (including 0) as specified in the HPGL/2 reference. Unsupported line types require stroked equivalents. The line type is used until a subsequent *LT* is encountered. In this practice, *LT* only affects the *PD* command. Examples:

...*LT*;...

Result: all subsequent lines drawn with the *PD* command are solid. This is the default line type.

...*LT*2,3,1;...

Result: all subsequent lines drawn with the *PD* command use pattern #2, a dashed line comprised of segments 1.5 mm long separated by 1.5 mm spaces (3 mm total). The line type is used until an *IN* or *LT* is encountered.

7.2.8 *PA*—Plot Absolute (header only). Establishes absolute plotting. Do not use *PA* with parameters. This practice requires a single *PA* command near the end of the header immediately following the last *CO* and before the *DI* syntax. No other instances of *PA* are allowed. Example:

...";*PA*;*DT*...

7.2.9 *PD*—Pen Down. Lowers the pen and/or begins a line segment. Parameters are *X* and *Y* coordinate data, separated by a comma, that adhere to the unit system defined earlier in this practice. Strings of coordinates are not allowed that is *PDX*-,*Y*,*X*,*Y*,*X*,*Y*;. In this practice, *PD* is affected by the *LT* syntax. Example:

...*PD*1016,2032;...

Result: Puts the logical pen down and moves from the current position to *X* coordinate 1016 and *Y* coordinate 2032 in a straight line.

7.2.10 *PU*—Pen Up. Raises the logical pen and/or ends a line segment. Parameters are *X* and *Y* coordinate data, separated by a comma, that adhere to the unit system defined earlier in this practice. Strings of coordinates are not allowed that is *PUX*,*Y*,*X*,*Y*,*X*,*Y*;. Example:

...*PU*2032,1016;...

Result: Raises the logical pen and moves from the current position to *X* coordinate 2032 and *Y* coordinate 1016 in a straight line.

7.2.11 *SI*—Absolute character Size. Specifies the size of characters in centimeters (cm). Accepts two parameters, width and height, separated by a comma. Changes to *SI* remain in effect until a subsequent *SI* is encountered. In this practice, *SI* affects the *DI* and *LB* commands. Default values are *SI*0.285,0.375. Example:

...*SI*2,1;...

Result: subsequent characters are 2 cm wide and 1 cm high.

7.2.12 *SP*—Select Pen. Defines which pen is used for all subsequent commands. Changes to *SP* remain in effect until a subsequent *SP* is encountered. In this practice, *SP* affects *PD* and *LB*. Different tools are also supported. Only the parameters listed below are accepted. If a specified tool is not supported by the output device, the default tool is used.

*SP*0— (equivalent to *SP*;) No Pen

*SP*1—Pen (default)

*SP*9—Knife

*SP*17—Drill

*SP*25—Punch

Example:

...*SP*1;...

Result: Selects a pen for all subsequent drawing.

8. Keywords

8.1 apparel; HPGL; marker; plot file; plotter; printer; sewn goods; sewn product; upholstery; vector data

APPENDIXES

(Nonmandatory Information)

X1. UNSUPPORTED HPGL/2 SYNTAX

X1.1 This appendix describes standard HPGL/2 syntax that is not supported by this practice.

X1.1.1 *AA*—Arc Absolute,

X1.1.2 *AC*—Anchor Corner,

X1.1.3 *AD*—Alternate Font Definition,

X1.1.4 *AR*—Arc Relative,

X1.1.5 *AT*—Absolute Arc Three Point,

X1.1.6 *BP*—Begin Plot,

X1.1.7 *BR*—Bezier Relative,

X1.1.8 *BZ*—Bezier Absolute,

X1.1.9 *CF*—Character Fill Mode,

X1.1.10 *CI*—Circle,

X1.1.11 *CP*—Character Plot,

X1.1.12 *CR*—Set Color Range for Relative Data,

X1.1.13 *CT*—Chord Tolerance,

X1.1.14 *DC*—Digitize Clear,

X1.1.15 *DF*—Defaults,

X1.1.16 *DL*—Download character,

X1.1.17 *DP*—Digitize Point,

X1.1.18 *DR*—Relative Direction,

X1.1.19 *DV*—Define Variable Text Path,

X1.1.20 *EA*—Edge rectangle Absolute,

X1.1.21 *EC*—Enable Cutter,

X1.1.22 *EP*—Edge Polygon,

X1.1.23 *ER*—Edge Rectangle Relative,

X1.1.24 *ES*—Extra Space,

X1.1.25 *EW*—Edge Wedge,

X1.1.26 *FI*—Primary Font Selection by ID,

X1.1.27 *FN*—Secondary Font Selection by ID,

X1.1.28 *FP*—Fill Polygon,

- X1.1.29 *FR*—Frame advance,
- X1.1.30 *FT*—Fill Type,
- X1.1.31 *IP*—Input Points,
- X1.1.32 *IR*—Input relative,
- X1.1.33 *IW*—Input Window,
- X1.1.34 *LA*—Line Attributes,
- X1.1.35 *LO*—Label Origin,
- X1.1.36 *MC*—Merge Control,
- X1.1.37 *MG*—Message,
- X1.1.38 *MT*—Media Type,
- X1.1.39 *NP*—Number of Pens,
- X1.1.40 *NR*—Not Ready,
- X1.1.41 *OD*—Output Digitized point,
- X1.1.42 *OE*—Output Error,
- X1.1.43 *OH*—Output Hard Clip Limits,
- X1.1.44 *OI*—Output Identification,
- X1.1.45 *OP*—Output P1, P2,
- X1.1.46 *OS*—Output Status,
- X1.1.47 *PC*—Pen Color Assignment,
- X1.1.48 *PE*—Polyline Encoded,
- X1.1.49 *PG*—Page advance,
- X1.1.50 *PM*—Polygon Mode,
- X1.1.51 *PP*—Pixel Placement,
- X1.1.52 *PR*—Plot Relative,
- X1.1.53 *PS*—Plot Size,
- X1.1.54 *PW*—Pen Width,
- X1.1.55 *QL*—Quality Level,
- X1.1.56 *RA*—Fill Rectangle Absolute,
- X1.1.57 *RF*—Raster Fill Definition,
- X1.1.58 *RO*—Rotate Coordinate System,
- X1.1.59 *RP*—Replot,
- X1.1.60 *RR*—Fill Rectangle Relative,
- X1.1.61 *RT*—Relative Arc Three Point,
- X1.1.62 *SA*—Select Alternate font,
- X1.1.63 *SB*—Scalable or Bitmap Fonts,
- X1.1.64 *SC*—Scale,
- X1.1.65 *SD*—Standard Font Definition,
- X1.1.66 *SL*—Character Slant,
- X1.1.67 *SM*—Symbol Mode,
- X1.1.68 *SR*—Relative character Size,
- X1.1.69 *SS*—Select Standard font,
- X1.1.70 *ST*—Sort,
- X1.1.71 *SV*—Screened Vectors,
- X1.1.72 *TD*—Transparent Data,
- X1.1.73 *TR*—Transparency Mode,
- X1.1.74 *UL*—User Defined Line Type,
- X1.1.75 *VS*—Velocity Select,
- X1.1.76 *WG*—Fill Wedge, and
- X1.1.77 *WU*—Pen Width Unit Selection.

X2. SAMPLE PLOT FILE COMPLIANT WITH ASTM XXXXX-XX

X2.1 The following example is a plot file in compliance with the ASTM XXXXX-XX practice. It will render a 36 by 40 in. box with an origin at 0,0.

X2.1.1 Example:

IN; CO “ASTMXXXXX-XX”; CO “Author: John Doe”; CO “Creation Date: 01-01-2003”; CO “Creation Time: 16-34”; PA; DTETX, 1; LM0; PU0,0; PD36576, 0; PD36576 ,40640; PD0, 40640; PD0,0; FS

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).