



## Standard Practice for Exposing a Membrane Switch to Variation in Atmospheric Pressure<sup>1</sup>

This standard is issued under the fixed designation F 1762; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope

1.1 This practice covers a procedure for exposing a membrane switch to variations in atmospheric pressure. It can be used to determine the effects of pressure variations on chemical and mechanical properties and functional characteristics of the switch.

### 2. Referenced Documents

#### 2.1 ASTM Standards:

F 1570 Test Method for Determining the Tactile Ratio of a Membrane Switch<sup>2</sup>

F 1597 Test Method for Determining the Actuation Force and Contact Force of a Membrane Switch<sup>2</sup>

### 3. Terminology

#### 3.1 Definitions:

3.1.1 *membrane switch*—a momentary switching device in which at least one contact is on (or made of) a flexible substrate.

3.1.2 *contact closure*—the point at which a specified resistance is achieved.

3.1.3 *specified resistance*—the maximum allowable resistance as a measure between two terminations whose internal switch contacts complete a circuit when held closed.

### 4. Significance and Use

4.1 Erratic operation or malfunction of a membrane switch resulting from changes in the specified switch characteristics,

4.2 Rupture, implosion or explosion of seals due to pressure variations,

4.3 Change in physical or chemical properties due to pressure differentiations, and

4.4 Delaminations of a membrane switch may occur due to pressure variations.

### 5. Interferences

5.1 Time duration before, during and after pressure cycling,

5.2 Temperature,

5.3 Humidity,

5.4 Mounting Method (if applicable).

### 6. Apparatus

6.1 *Pressure Chamber*, a chamber or cabinet capable of maintaining a specified pressure. If procedurally required, the apparatus shall be capable of providing pressure variation at a specified rate.

6.2 *Monitoring Device*, suitable to detect contact closure (that is, ohm meter, etc.).

### 7. Conditioning

7.1 Condition all specimens for 72 h at ambient laboratory conditions immediately prior to exposure, or prior to pressure cycling. This is to enable the specimens to stabilize.

### 8. Procedure

#### 8.1 Pretest Setup:

8.1.1 Measure or observe the desired characteristics of the switch so that comparable measurements and observations can be made during or after the test.

8.1.1.1 Document the setup, test equipment, and mounting procedure (if applicable) used to measure the characteristics.

8.1.2 Connect predetermined switch terminations to contact closure measuring device.

#### 8.2 In-Process Test:

8.2.1 Place specimens in the chamber at ambient conditions, record time and date, and initiate contact closure monitoring device.

8.2.2 Adjust the ramp rate to decrease air pressure at 2000 ft/min unless otherwise specified.

8.2.3 Set pressure as specified.

8.2.4 Maintain the chamber pressure for the specified time interval.

8.2.5 Return chamber pressure to the initial ambient conditions at the specified rate.

8.2.6 Remove specimens and record time and date.

#### 8.3 Post Test:

8.3.1 Measure and observe the characteristics of the switch as in 8.1.1. Record time and date for each characteristic measured.

8.4 For determining the tactile ratio of a membrane switch, test in accordance with Test Method F 1570.

8.5 For determining the actuation force and contact force of

<sup>1</sup> This test method is under the jurisdiction of ASTM Committee F-1 on Electronics and is the direct responsibility of Subcommittee F01.18 on Membrane Switches.

Current edition approved Dec. 10, 1997. Published February 1998. Originally published as F 1762–96. Last previous edition F 1762–96.

<sup>2</sup> *Annual Book of ASTM Standards*, Vol 10.05.

a membrane switch, test in accordance with Test Method F 1597.

## **10. Keywords**

10.1 contact closure; delamination; membrane switch

## **9. Precision and Bias**

9.1 The precision and bias of this test are under investigation.

*The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 100 Barr Harbor Drive, West Conshohocken, PA 19428.*