



# Standard Terminology Relating to Underwater Search, Rescue, and Recovery Activities<sup>1</sup>

This standard is issued under the fixed designation F 1549; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 The purpose of this terminology is to establish uniformity in terminology used in the field of underwater search, rescue, and recovery.

1.2 The terminology is appropriate to those underwater search, rescue, or recovery activities that use self-contained or surface-supplied underwater breathing apparatuses to provide a breathing gas supply for the searcher(s).

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

## 2. Significance and Use

2.1 This terminology is not intended to be used as a replacement for proper training and experience in the skills necessary to conduct an underwater search and rescue operation safely.

## 3. Terminology

### 3.1 Definitions:

**ascent rate**, *n*—the speed of vertical movement toward the water's surface.

**bail-out bottle**, *n*—A diver-carried supply of air or mixed gas (as appropriate) sufficient under standard operating conditions to allow the diver to reach the surface or another source of breathing gas, or to be reached by a safety diver.

**bottom time**, *n*—the total elapsed time measured in minutes from the time that the diver leaves the surface in descent to the time that the diver begins ascent.

**console**, *n*—an instrument package that contains one or more instruments used to monitor depth, bottom time, surface intervals, air pressure, compass direction, decompression status, or some combination thereof.

**D.A.N.**, *n*—Divers Alert Network.<sup>2</sup>

**DCS**, *n*—decompression sickness, a medical condition with a

variety of symptoms that may result from gas or bubbles in the tissues of divers after pressure reduction.

**decompression**, *n*—the technique used to allow the controlled removal of excess inert gas from the body during and after a dive to prevent decompression sickness (DCS).

**dive computer**, *n*—a microprocessor-based electronic instrument that provides data based on a specific decompression model.

**dive profile**, *n*—the depth/time history of a dive that typically consists of bottom time, maximum depth, and surface interval.

**Doppler bubble detector**, *n*—a device that uses the Doppler Effect to monitor specific areas of the circulatory system and detect the presence of bubbles as a measure of decompression stress.

**hyperbaric chamber**, *n*—a chamber in which the internal pressure can be elevated by the introduction of compressed air (or other gasses) that is used primarily for medical treatment (including decompression sickness and arterial gas embolism) and physiological studies.

**J-valve**, *n*—a manually operated, spring-loaded, SCUBA cylinder check valve that incorporates a low air warning/reserve air mechanism.

**K-valve**, *n*—a simple, manually operated on-off SCUBA cylinder valve.

**line tender**, *n*—the individual who controls the diver's search pattern.

**nitrogen narcosis**, *n*—a distinct anesthetic effect, characterized by loss of judgment and disorientation, caused from breathing nitrogen at increased partial pressures.

**repetitive diving**, *n*—any dive conducted while the decompression model being followed for the dives indicates that inert gases are still present in the tissues from a previous dive. This is within the context of a fixed time period, usually 12 to 24 h, depending on the model being followed.

**repetitive group designation**, *n*—an assigned letter on a decompression table that relates directly to the amount of residual inert gas in the diver's tissues following a dive. This group changes with time as the diver's body off-gases.

**residual nitrogen**, *n*—nitrogen gas that is still dissolved in a diver's tissues after he has surfaced from a dive using compressed air as a breathing gas.

**RNT**, *n*—residual nitrogen time.

**safety diver**, *n*—diver who is dressed completely in dive gear and who remains on the surface to go to the immediate aid

<sup>1</sup> This terminology is under the jurisdiction of ASTM Committee F-32 on Search and Rescue and is the direct responsibility of Subcommittee F32.06 on Terminology. Current edition approved August 15, 1994. Published September 1994.

<sup>2</sup> D.A.N. is an organization that disseminates diving safety information, provides diving medical insurance, and offers telephone assistance for answering questions related to diving medicine and for locating hyperbaric treatment facilities that can provide medical care for barotrauma injuries. It can be contacted by telephone at 919-684-2948 for non-emergency questions and at 919-684-8111 for emergencies.

of a distressed diver underwater.

**safety stop, *n***—additional time spent at shallow depths even though the dive computer or dive table indicates that a direct ascent to the surface is possible.

**standby diver, *n***—a diver at the dive location available to assist a diver in the water.

**treatment table, *n***—a recompression schedule used to treat decompression sickness or embolisms.

**umbilical, *n***—in surface-supplied diving, diver's gas and a communication and safety line all in one bundle.

*The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 100 Barr Harbor Drive, West Conshohocken, PA 19428.*

*This standard is copyrighted by ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or [service@astm.org](mailto:service@astm.org) (e-mail); or through the ASTM website (<http://www.astm.org>).*