

AutoFlush® New and Improved with Visual Indicators (LED's)

For Sloan and Zum
Flush Valves

- 400938 Urinal-White
- 400939 Toilet-White
- 401186 Urinal-Chrome
Finish
- 401187 Toilet-Chrome
Finish

For Coyne & Delany
Flushboy Valves

- 401194 Urinal-White
- 401195 Toilet-White
- 401207 Urinal-Chrome
Finish
- 401206 Toilet-Chrome
Finish

Retrofit Automatic Flushing Unit

No need to replace your current investment of flush valves or move plumbing rough-in to accommodate ADA compliance. Installing battery operated automatic flushing device onto your existing flush valves makes economic sense. Installation of the AutoFlush® Unit is quick and simple—you don't even have to turn the water off. The AutoFlush® is the easiest and most cost effective way to gain the benefits of an automatic flushing system—No more unflushed fixtures, foul odors, and valve damage from handle kicking.

New Improved Design


New angled sensor allows for user detection even with the toilet seat in the raised position.

Smart Technology

The AutoFlush® infrared *Object Lock Technology* ensures dependable activation flushing like no other system today. The use of cam gears instead of solenoid valves provides dependable trouble-free operation.

Easy 2 Minute Retrofit Installation


No water shut off required. Simply remove your existing flush handle with the supplied wrench, replace with your new AutoFlush® unit, and tighten the collar nut with the same wrench. Insert supplied batteries, and you have just converted your washroom to a higher standard in hygiene.




Case Pack: 6
Case Weight: 14 lbs.
Case Cube: 1.00

SANITARY NO TOUCH OPERATION


A) User Approaches




B) Object Lock
Infrared
Senses
User



C) Fixture is Flushed
as User Walks
Away





Specifications

Product:

AutoFlush® unit, right-hand or left-hand valve, retrofitting.

Trap Seal Protection (24hr flush):

Ensures fixtures are flushed at least once every 24 hours. This feature prevents sewer gases escaping through open trap. This feature can be turned off by placing switch #1 in the down position.

Valve Type:

Retrofits to all Sloan Royal and Zurn flush valve systems, or Coyne and Delany flushboy valves. Adaptable for both left and right hand supply. Works with toilets & urinals.

Flush Volume:

Operates with any flush volume cycle.

Power Supply:

4 C- Cell alkaline batteries - Included! Average 3+ years battery life under normal operation.

Sensor Type:

Infrared convergence type object lock detection. Adjustable range: 8" to 48." (32" factory set)

User In View L.E.D.:

Green light flashes 3 times when user is detected for 5 seconds.

Battery Replacement L.E.D.:

Yellow light flashes when batteries are low.

Battery Replacement Tone:

Optional audio tone reinforces yellow LED (change batteries). This feature can be turned off by placing switch #2 in the down position.

Installation Time

Easy 2 minute installation. Water does not need to be shut off.

Compliance:

Designed to meet A.D.A. requirements.

Warranty:

3 years against defects in parts and workmanship. Successfully tested for over 1 million flushes!

High Mount Adapter:


Angles AutoFlush® unit down 27.5° (part # 401096).

Allen Wrench:

3mm / 1/8" Allen wrench - Included.

Courtesy Manual Flush:

Toilet model only.



Air Delights

www.airdelights.com

9974 SW Arctic Dr.
Beaverton, OR 97005 Toll
Free: 1-800-440-5556