



## Standard Practice for Qualification of Radioscopic Systems<sup>1</sup>

This standard is issued under the fixed designation E 1411; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope

1.1 This practice provides test and measurement details for measuring the performance of X-ray and Gamma ray radiosopic systems. Radioscopic examination applications are diverse. Therefore, system configurations are also diverse and constantly changing as the technology advances.

1.2 This practice is intended as a means of initially qualifying and requalifying a radiosopic system for a specified application by determining its performance level when operated in a static mode. System architecture including the means of radiosopic examination record archiving and the method for making the accept/reject decision are also unique system features and their effect upon system performance must be evaluated.

1.3 The general principles, as stated in this practice, apply broadly to transmitted-beam penetrating radiation radiosopic systems. Other radiosopic systems, such as those employing neutrons and Compton back-scattered X-ray imaging techniques, are not covered as they may involve equipment and application details unique to such systems.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* For information on safety requirements, refer to the applicable documents listed in Section 2.

### 2. Referenced Documents

#### 2.1 ASTM Standards:

E 747 Practice for Design, Manufacture and Material Grouping Classification of Wire Image Quality Indicators (IQI) Used for Radiology<sup>2</sup>

E 1025 Practice for Design, Manufacture, and Material Grouping Classification of Hole-Type Image Quality Indicators (IQI) Used for Radiology<sup>2</sup>

E 1255 Practice for Radioscopy<sup>2</sup>

E 1316 Terminology for Nondestructive Examinations<sup>2</sup>

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee E-7 on Nondestructive Testing and is the direct responsibility of Subcommittee E07.01 on Radiology (X and Gamma) Method.

Current edition approved Dec. 10, 1995. Published February 1996. Originally published as E 1411 – 91. Last previous edition E 1411 – 91.

<sup>2</sup> *Annual Book of ASTM Standards*, Vol 03.03.

E 1647 Practice for Determining Contrast Sensitivity in Radioscopy<sup>2</sup>

#### 2.2 Other Standard:

British Standard 3971—1980 Specification for Image Quality Indicators for Industrial Radiography (including guidance on their use)<sup>3</sup>

### 3. Terminology

3.1 *Definitions*—For definitions of terms used in this practice, see Terminology E 1316.

### 4. Summary of Practice

4.1 This practice provides a standardized procedure for the initial qualification and requalification of a radiosopic system to establish radiosopic examination capabilities for a specified range of applications.

4.2 This practice is intended for use in association with a standard practice governing the use of radiosopic examination, such as Practice E 1255.

4.3 This practice specifies the procedures to be used in determining the performance level of the radiosopic system. Unique system features, including component selection, system architecture, programmability and image archiving capabilities are important factors and are taken into account in this practice. The overall system performance level, as well as key system features, are to be recorded in a qualification document which shall qualify the performance level of the total radiosopic system. An example of the Radioscopic System Qualification document form is included in the Appendix. This document may be tailored to suit the specific application.

### 5. Significance and Use

5.1 As with conventional radiography, radiosopic examination is broadly applicable to the many materials and test object configurations which may be penetrated with X-rays or gamma rays. The high degree of variation in architecture and performance among radiosopic systems due to component selection, physical arrangement and test object variables, makes it necessary to establish the level of performance which the selected radiosopic system is capable of achieving in specific applications. The manufacturer of the radiosopic system, as well as the user, require a common basis for determining the performance level of the radiosopic system.

<sup>3</sup> Available from British Standards Institute, 2 Park Street, London, England W1A2B5.

5.2 This practice does not purport to provide a method to measure the performance of individual radioscopic system components which are manufactured according to a variety of industry standards. This practice covers measurement of the combined performance of the radioscopic system elements when operated together as a functional radioscopic system.

5.3 This practice addresses the performance of radioscopic systems in the static mode only. Radioscopy can also be a dynamic, real-time or near real-time examination technique which can allow test-part motion as well as parameter changes during the radioscopic examination process. The use of this practice is not intended to be limiting concerning the use of the dynamic properties of radioscopy. Users of radioscopy are cautioned that the dynamic aspects of radioscopy can have beneficial as well as detrimental effects upon system performance and must be evaluated on a case-by-case basis.

5.4 This qualification procedure is intended to benchmark radioscopic system performance under selected operating conditions to provide a measure of system performance. Qualification shall not restrict operation of the radioscopic system at other radioscopic examination parameter settings which may provide improved performance on actual test objects.

5.5 Radioscopic system performance measured pursuant to this practice does not guarantee the level of performance which may be realized in actual operation. The effects of test part-geometry and test part-generated scattered radiation cannot be reliably predicted by a standardized test. All radioscopic systems age and degrade in performance as a function of time. Maintenance and operator adjustments, if not correctly made, can adversely affect the performance of radioscopic systems.

5.6 The performance of the radioscopic system operator in manual and semi-automatic radioscopic systems is not taken into account in this practice and can have a major effect upon radioscopic system performance. Operator qualifications are an important aspect of system operation and should be covered in a separate written procedure.

## 6. Application and Equipment Information Statement

6.1 The following minimum application and qualification standard information shall be reported in the qualification document.

6.1.1 A brief statement about the intended application,

6.1.2 Material(s) and thickness range(s) for which the system is to be qualified,

6.1.3 Maximum test part size or radioscopic examination envelope,

6.1.4 A brief statement about the kind of test part features which are to be detected,

6.1.5 The required spatial resolution to resolve, or detect the presence of, the smallest required feature dimension lying in a plane at right angles to the radiation beam. This value shall be expressed in line-pairs per millimeter and is equal to the reciprocal of twice the required small feature size expressed in millimeters,

6.1.6 The required contrast sensitivity to resolve, or detect the presence of, the smallest feature dimension lying along the radiation beam expressed as a percentage of the total path length of the radiation beam in the material,

6.1.7 The desired throughput requirements expressed in

linear and area dimensions per unit time, and

6.1.8 The standardized image quality indicator to be used in qualifying the radioscopic system.

6.2 The following minimum equipment information shall be included in the qualification document:

6.2.1 The system make, model number, serial number, date of manufacture and configuration,

6.2.2 Radioscopic scan plan details and whether manual or programmable,

6.2.3 Accept/Reject decision as to whether manual, computer-aided or fully automated, and

6.2.4 Pertinent equipment details for each radioscopic system sub-system.

6.3 This practice neither approves nor disapproves the use of the qualified radioscopic system for the specified application. It is intended only as a standardized means of evaluating system performance.

## 7. Qualification Procedure

7.1 Before testing, the radioscopic system shall be determined to be in good operating condition. Each sub-system shall be checked to ascertain that it performs according to the manufacturer's specifications.

7.2 The radioscopic system and each component thereof shall be operated within its ratings at all times during qualification.

7.3 The radioscopic system shall be determined to be in compliance with applicable local, state and federal radiation safety standards. Proper procedures must be taken to safeguard personnel during the performance of these tests.

7.4 The image display shall be placed in an area of subdued, controllable lighting which is free from glare and reflections which might affect image assessment.

7.5 The radioscopic system shall be at operating temperature and stabilized. All operator accessible operating controls may be adjusted as necessary to obtain the optimal image quality.

7.6 Maintenance adjustments shall not be made during the testing process. If maintenance tests are necessary, all affected tests shall be repeated.

7.7 Where provided, beam collimators and diaphragms shall be used to minimize scatter radiation thereby promoting the highest quality radioscopic image.

7.8 Radioscopic system performance shall be evaluated as to resolution and contrast sensitivity for the applicable material over the range of minimum and maximum section thicknesses for which the radioscopic system is to be qualified.

7.9 Each imager mode (field of view), radiation source focal spot size and imaging geometry which is to be used shall be evaluated. Any radioscopic examination geometry parameter which varies more than  $\pm 20\%$  from a tested geometry shall be treated as a new imaging geometry and must be evaluated. Imaging geometry parameters include FDD (focal detector distance), FOD (focal object distance) and magnification.

7.10 If the radioscopic system incorporates image processing, processed as well as unprocessed images shall be evaluated. All image processor enhancement functions used to produce the processed radioscopic image must be recorded and are a part of the qualification record.

7.11 If image recording devices are incorporated, each must be qualified as to playback quality with reference to the original radioscopic image.

7.12 Unprocessed resolution measurements shall be made at the image converter with no additional absorber. Recorded data shall include FDD, FOV, spatial resolution, radiation source energy and intensity for each imager mode and focal spot for which the radioscopic system is to be qualified. Resolution measurements shall be made using a line-pair gage consisting of equal width lead foil lines and spaces on an appropriate low density substrate, such as plastic. Horizontal (along the TV scan lines) and vertical (normal to TV scan lines) resolution shall be recorded.

7.13 Unprocessed resolution measurements shall also be made at the test object region of interest average position during manipulation with no additional absorber. Recorded data shall include FDD, average FOD, magnification, field of view, spatial resolution, source energy and intensity for each imager mode and focal spot which is to be qualified. Resolution measurements shall be made using a line-pair gage consisting of equal width lead foil lines and spaces on a radiation-transparent substrate. Horizontal (along TV or other scan lines) and vertical (normal to TV or other scan lines) resolution shall be recorded.

7.14 Unprocessed contrast sensitivity measurements shall be made at the test object position for the material over the range of the minimum and maximum thicknesses for which the system is to be qualified. Recorded data shall include field of view, contrast sensitivity, source energy and intensity for each imager mode and source tube focal spot for which the radioscopic system is to be qualified. Contrast sensitivity measurements shall be made by shims or a step wedge made of the material for which the system is to be qualified. The thickness increments shall represent at least 100 %, 99 %, 98 % and 97 % of the minimum and maximum thicknesses for which the system is to be qualified. All steps shall be adjacent to the 100 % step for comparison purposes. The minimum detectable differential thickness expressed as a percentage of the 100 % thickness shall be recorded. Measurement geometry shall be the same as for the resolution tests outlined in 7.13.

7.15 Qualification measurements for the performance of the radioscopic system shall be made using at least one type of standardized image quality indicator. The device(s) selected shall be appropriate for the materials and thicknesses to which they are applied. Such device(s) shall be capable of performing simultaneous radioscopic resolution and contrast measurements on the material and thickness for which the system is to be qualified. Suitable devices include, but are not limited to, Practice E 747, E 1025, and E 1647 and the BS 3971 Type IIIA Duplex Wire Gage. Selected device(s) shall be specified in the qualification report.

7.15.1 Measurements shall be made for unprocessed and processed radioscopic images for the material at the minimum and maximum thicknesses for which the system is to be qualified.

7.15.2 Measurements shall be recorded for each image converter mode or field of view.

7.15.3 Measurements shall be recorded for each radioscopic image display and each image recording device.

7.15.4 Resolution measurements shall be at right angles to each other if the image quality measurement device has directional characteristics as in the case of single or duplex wires. If the radioscopic system involves a raster scan in the image formation process, resolution measurements shall be made both parallel to and at right angles to the scan lines.

7.15.5 Sufficient radioscopic system parameter settings shall be recorded to allow the qualification measurements to be repeated. Required parameters include FDD, average FOD, average magnification, field of view at the test part, kV, mA and focal spot size. Where image processing is utilized, all applied image enhancement processes, including noise reduction, edge sharpening, contrast manipulation and any other functions which may affect image quality must be fully documented.

7.16 All qualification performance measurements shall be made in the static mode.

## 8. Qualification Statement

8.1 The following qualification statement shall apply to radioscopic systems qualified pursuant to this practice: "Using the qualification device(s) selected, the qualified radioscopic system, when in identical operating condition, properly adjusted, operated and viewed by a skilled operator in the static model, is capable of performing to the level reported in this qualification document. The user is cautioned that deviation from these conditions can significantly alter the radioscopic system's performance."

## 9. Records and Associated Documentation

9.1 The overall system performance level, as well as key system features, are to be recorded in a qualification document which shall certify the performance level of the total radioscopic system. All information and measurements required in Sections 6 and 7 are to be recorded and retained until the radioscopic system is re-qualified. As an aid to standardization of the qualification document, a sample format of the Radioscopic System Qualification document is included in the Appendix X1. Not all parts of Sections 8 and 9 are applicable to all radioscopic systems. These sections should be tailored to the radioscopic system being qualified.

## **10. Periodic Re-qualification and Verification**

10.1 Re-qualification is necessary whenever the radioscopic system undergoes significant maintenance or alterations which could affect performance or the application changes beyond the material and thickness ranges for which the system was qualified.

10.2 Periodic verification may also be necessary if performance monitoring methods are not adequate to assure the continued level of performance to which the system was initially qualified.

## **11. Keywords**

11.1 Compton back-scattered; contrast manipulation; contrast sensitivity; duplex wire gage; edge sharpening; focal detector distance (FDD); focal object distance (FOD); focal spot size; image processor; image quality indicator; imager; line-pair gage; magnification; near real-time radioscopy; noise reduction; penetrating radiation; programmability; radioscopic; radioscopic examination geometry; raster scan; real-time radioscopy; spatial resolution; static mode; step wedge; transmitted beam

APPENDIX

(Nonmandatory Information)

X1. SUGGESTED RADIOSCOPIC SYSTEM QUALIFICATION DOCUMENT FORMAT

X1.1 The format given in this Appendix is intended to be representative of the kind of radioscopic system qualification information which is required, and may be changed to suit the particular circumstances.

X1.2 Application

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

X1.3 Material(s) and Thickness Range(s) for Which System is to be Qualified

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

X1.4 Maximum Test Part Size

\_\_\_\_\_ cm × \_\_\_\_\_ cm × \_\_\_\_\_ cm (required radioscopic examination envelope)

X1.5 Required Spatial Resolution

(based upon the smallest feature which must be resolved lying in a plane at right angles to the radiation beam)

Horizontal = \_\_\_\_\_ mm; Vertical = \_\_\_\_\_ mm

X1.6 Required Contrast Sensitivity

Required Contrast Sensitivity = \_\_\_\_\_ %

X1.7 Desired Radioscopic Examination Throughput

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

X1.8 Equipment Details

X1.8.1 The following is a suggested listing of pertinent radioscopic system equipment details. The listing may be changed to suit the particular system configuration as may be necessary.

System Manufacturer \_\_\_\_\_ System Model Number \_\_\_\_\_

Serial Number \_\_\_\_\_ Date of Manufacture \_\_\_/\_\_\_/\_\_\_

System Configuration: Cabinet \_\_\_\_\_ or Walk-in Room \_\_\_\_\_

Scan Plan: Manual Control Y/N Program Control Y/N

Accept/Reject Decision: Manual Y/N Computer Aided Y/N Automatic Y/N

X1.9 X-Ray Generating System

Manufacturer \_\_\_\_\_ Model \_\_\_\_\_ Under System Control Y/N

Conventional \_\_\_\_\_ ; Minifocus \_\_\_\_\_ ; Microfocus \_\_\_\_\_ ; kV Range \_\_\_\_\_ to \_\_\_\_\_

Minimum mA \_\_\_\_\_ ; Maximum mA \_\_\_\_\_ ; Ripple at highest mA \_\_\_\_\_ kV;

kV measurement: Primary \_\_\_\_\_ or Voltage Divider \_\_\_\_\_ ; Large Focal

Spot \_\_\_\_\_ mm × \_\_\_\_\_ mm, \_\_\_\_\_ watts; Small Focal Spot \_\_\_\_\_ mm × \_\_\_\_\_ mm,

\_\_\_\_\_ watts; Inherent filtration \_\_\_\_\_ ;

Additional filtration \_\_\_\_\_ ;

or



X1.16 Radioscopic Examination Record Archiving

X1.16.1 Analog Video Cassette Recorder

Manufacturer \_\_\_\_\_ Model \_\_\_\_\_ Under System Control Y/N  
 Tape Width and Format \_\_\_\_\_; Bandwidth \_\_\_\_\_ MHz;  
 Resolution \_\_\_\_\_ TV lines at Standard Speed; \_\_\_\_\_ TV lines at Slow Speed;  
 \_\_\_\_\_ TV lines at Very Slow Speed: Input Video Standard \_\_\_\_\_; Output Video Standard \_\_\_\_\_;  
 Voice narrative Y/N; Manufacturer's Stated Storage Life \_\_\_\_\_ Under Environmental Conditions of \_\_\_\_\_

X1.16.2 Analog Video Hard Copy Printer

Manufacturer \_\_\_\_\_ Model \_\_\_\_\_ Under System Control Y/N;  
 Image size \_\_\_\_ cm × \_\_\_\_ cm; Monochrome Y/N; Color Y/N;  
 Resolution \_\_\_\_\_ TV lines; Grey Shades \_\_\_\_\_; Manufacturer's Stated Storage Life \_\_\_\_\_ Under  
 Environmental Conditions of \_\_\_\_\_

X1.16.3 Analog Optical Disk Storage

Manufacturer \_\_\_\_\_ Model \_\_\_\_\_ Under System Control Y/N;  
 Input Video Standard \_\_\_\_\_; Output Video Standard \_\_\_\_\_;  
 Monochrome Y/N; Color Y/N; Bandwidth \_\_\_\_\_ MHz; Voice Narrative Y/N;  
 Resolution \_\_\_\_\_ TV lines; Grey Shades \_\_\_\_\_; Manufacturer's Stated Storage Life \_\_\_\_\_ Under  
 Environmental Conditions of \_\_\_\_\_

X1.16.4 Digital Magnetic Media Storage

Manufacturer \_\_\_\_\_ Model \_\_\_\_\_ Under System Control Y/N;  
 Computer System Interface Standard \_\_\_\_\_;  
 Radioscopic Image Storage Format \_\_\_\_ × \_\_\_\_ Pixels × \_\_\_\_ Bits;  
 Drive Recording Format Standard \_\_\_\_\_;  
 Manufacturer's Stated Storage Life \_\_\_\_\_ Under  
 Environmental Conditions of \_\_\_\_\_

X1.16.5 Digital Optical Media Storage

Manufacturer \_\_\_\_\_ Model \_\_\_\_\_ Under System Control Y/N  
 Computer System Interface Standard \_\_\_\_\_;  
 Radioscopic Image Storage Format \_\_\_\_ × \_\_\_\_ Pixels × \_\_\_\_ Bits;  
 Erasable Y/N; Drive Recording Format Standard \_\_\_\_\_;  
 Manufacturer's Stated Storage Life \_\_\_\_\_ Under Environmental Conditions of \_\_\_\_\_

X1.16.6 Photographic Storage

Manufacturer \_\_\_\_\_ Model \_\_\_\_\_ Under System Control Y/N  
 Image taken from: Image Display Monitor Y/N; Dedicated Monitor Y/N;  
 Film Size \_\_\_\_ mm × \_\_\_\_ mm; Film Type \_\_\_\_\_  
 Manufacturer's Stated Storage Life \_\_\_\_\_ Under Environmental Conditions of \_\_\_\_\_

X1.17 Manipulators

Test Part Manipulator

Manufacturer _____	Model _____ Under System Control Y/N				
	No. 1	No. 2	No. 3	No. 4	No. 5
Axis Name					
Manual					
Powered					
Reversible					
Min Speed cm/sec					
Max Speed cm/sec					
Programmable					

**Radiation Source Manipulator**

Manufacturer _____	Model _____	Under System Control Y/N			
No. 1	No. 2	No. 3	No. 4	No. 5	
Axis Name					
Manual					
Powered					
Reversible					
Min Speed cm/sec					
Max Speed cm/sec					
Programmable					

**Imager Manipulator**

Manufacturer _____	Model _____	Under System Control Y/N			
No. 1	No. 2	No. 3	No. 4	No. 5	
Axis Name					
Manual					
Powered					
Reversible					
Min Speed cm/sec					
Max Speed cm/sec					
Programmable					

**X1.18 Radioscopic System Controller**

Manufacturer \_\_\_\_\_ Model Number \_\_\_\_\_ Host Computer Y/N;  
 Dedicated Controller Y/N; Radioscopic System Elements Controlled:  
 Radiation Source Y/N; Source Primary Beam Collimator Y/N;  
 Imager Primary Beam Collimator Y/N; Image Conversion System Y/N;  
 Video Image Transmission System Y/N; Digital Image Processor Y/N;  
 Manipulation System Y/N; Radiation Enclosure Access Doors Y/N  
 Radioscopic Image Archiving System Y/N; Accept/Reject Decision Y/N;  
 Other \_\_\_\_\_;  
 Manual Manipulation while in Program Mode Allowed Y/N; Resume Program after Interruption for Manual Manipulation Y/N; Programmed Dwell at Radioscopic Step Y/N; Override of Programmed Dwell Y/N; Programming Method—Teach/Learn Y/N; Off-Line Programming Y/N; Maximum Number of Steps per Program \_\_\_\_\_; Program Storage Method \_\_\_\_\_

**X1.19 Radiation Shielding System**

Manufacturer \_\_\_\_\_ Model \_\_\_\_\_ Under System Control Y/N;  
 Cabinet X-Ray Standard System per 21 CFR 1020.40 Y/N; Designed to Admit Humans Y/N; Enclosure per ANSI (NIST) Handbook 114 Y/N; Radiation Leakage Limits \_\_\_\_\_ mR/hr; Interior Dimensions \_\_\_\_\_ cm × \_\_\_\_\_ cm × \_\_\_\_\_ cm;  
 Doors No. 1 \_\_\_\_\_ cm × \_\_\_\_\_ cm; No. 2 \_\_\_\_\_ cm × \_\_\_\_\_ cm; Type of Interlock Switch \_\_\_\_\_;  
 Access Panels No. 1 \_\_\_\_\_ cm × \_\_\_\_\_ cm; No. 2 \_\_\_\_\_ cm × \_\_\_\_\_ cm; Type of Interlock Switch \_\_\_\_\_;  
 Number and Location of Radiation Warning Devices \_\_\_\_\_

**X1.20 Qualified Radioscopic System Static Performance Level**

Qualification device selection:  
 \_\_\_\_\_ ASTM E 747 Wire Penetrimeters  
 \_\_\_\_\_ ASTM E 1025 Hole-Type Image Quality Indicators  
 \_\_\_\_\_ BS 3971 Type III Duplex Wire Gage  
 \_\_\_\_\_ Other—please specify \_\_\_\_\_

Using the qualification device(s) selected, the qualified radioscopic system, when in identical operating condition, properly adjusted, operated and viewed by a qualified operator in the static mode, is capable of performing to the level reported in this qualification document. The user is cautioned that deviation from these conditions can significantly alter the radioscopic

system's performance.

The following data is to be recorded with the radioscopic system set up as it would be for normal operation:

**X1.21 Unprocessed Resolution Measurements at the Image converter**

FDD = \_\_\_\_ mm FS = \_\_\_\_ mm × \_\_\_\_ mm

Field of View	F.O.V.	H-LP/mm	V-LP/mm	E	I
Normal Imager Mode					
Mag. 1 Imager Mode					
Mag. 2 Imager Mode					

**X1.22 Unprocessed Resolution and Contrast Measurements at the Test Object Position**

FDD = \_\_\_\_ mm FOD = \_\_\_\_ mm (average)

Average Magnification = FDD/FOD = \_\_\_\_

Focal Spot = \_\_\_\_ mm × \_\_\_\_ mm

**X1.22.1 Resolution Measurement**

Field of View	F.O.V.	H-LP/mm	V-LP/mm	E	I
Normal Imager Mode					
Mag. 1 Imager Mode					
Mag. 2 Imager Mode					

**X1.22.2 Minimum Thickness Contrast Measurement**

Material \_\_\_\_\_ Nominal Thickness \_\_\_\_\_ mm

Step Wedge Steps:

Field of View	F.O.V.	CONTRAST SENSITIVITY	E	I	FS
Normal Imager Mode					
Mag. 1 Imager Mode					
Mag. 2 Imager Mode					

**X1.22.3 Maximum Thickness Contrast Measurement**

Material \_\_\_\_\_ Nominal Thickness \_\_\_\_\_ mm

Step Wedge Steps:

Field of View	F.O.V.	CONTRAST SENSITIVITY	E	I	FS
Normal Imager Mode					
Mag. 1 Imager Mode					
Mag. 2 Imager Mode					

**X1.23 Qualified Minimum Thickness Unprocessed Image Performance**

Material \_\_\_\_\_ Nominal Thickness \_\_\_\_\_ mm

FDD = \_\_\_\_ mm FOD = \_\_\_\_ mm (average)

Average Magnification = FDD/FOD = \_\_\_\_

Focal Spot = \_\_\_\_ mm × \_\_\_\_ mm

Qualification Device Used \_\_\_\_\_

Field of View	RTR		Image 1		Image 2		Image 3		Values	
	H	V	H	V	H	V	H	V	E	I
Normal Imager Mode										
Mag. 1 Imager Mode										
Mag. 2 Imager Mode										

**Key to Chart**

RTR = IQI Hole or Horizontal and Vertical wires observable in the Radioscopic image

Image 1 = IQI Hole or Horizontal and Vertical wires visible in the image as archived on the \_\_\_\_\_

Image 2 = IQI Hole or Horizontal and Vertical wires visible in the image as archived on the \_\_\_\_\_

Image 3 = IQI Hole or Horizontal and Vertical wires visible in the image as archived on the \_\_\_\_\_

X1.24 Qualified Maximum Thickness Unprocessed Image Performance

Material \_\_\_\_\_ Nominal Thickness \_\_\_\_\_ mm

FDD = \_\_\_\_\_ mm FOD = \_\_\_\_\_ mm (average)

Average Magnification = FDD/FOD = \_\_\_\_\_

Focal Spot = \_\_\_\_\_ mm × \_\_\_\_\_ mm

Qualification Device Used \_\_\_\_\_

Field of View	RTR		Image 1		Image 2		Image 3		Values	
	H	V	H	V	H	V	H	V	E	I
Normal Imager Mode										
Mag. 1 Imager Mode										
Mag. 2 Imager Mode										

Key to Chart

RTR = IQI Hole or Horizontal and Vertical wires observable in the Radioscopic image

Image 1 = IQI Hole or Horizontal and Vertical wires visible in the image as archived on the \_\_\_\_\_

Image 2 = IQI Hole or Horizontal and Vertical wires visible in the image as archived on the \_\_\_\_\_

Image 3 = IQI Hole or Horizontal and Vertical wires visible in the image as archived on the \_\_\_\_\_

X1.25 Qualified Minimum Thickness Processed Image Performance

Material \_\_\_\_\_ Nominal Thickness \_\_\_\_\_ mm

FDD = \_\_\_\_\_ mm FOD = \_\_\_\_\_ mm (average)

Average Magnification = FDD/FOD = \_\_\_\_\_

Focal Spot = \_\_\_\_\_ mm × \_\_\_\_\_ mm

Digital Image Processor Settings Utilized

X1.25.1 Noise Reduction Functions

---



---

X1.25.2 Edge Sharpening Functions

---



---

X1.25.3 Contrast Manipulation Functions

---



---

X1.25.4 Other Functions

---



---

Qualification Device Used \_\_\_\_\_

Field of View	RTR		Image 1		Image 2		Image 3		Values	
	H	V	H	V	H	V	H	V	E	I
Normal Imager Mode										
Mag. 1 Imager Mode										
Mag. 2 Imager Mode										

Key to Chart

RTR = IQI Hole or Horizontal and Vertical wires observable in the Radioscopic image

Image 1 = IQI Hole or Horizontal and Vertical wires visible in the image as archived on the \_\_\_\_\_

Image 2 = IQI Hole or Horizontal and Vertical wires visible in the image as archived on the \_\_\_\_\_

Image 3 = IQI Hole or Horizontal and Vertical wires visible in the image as archived on the \_\_\_\_\_

X1.26 Qualified Maximum Thickness Processed Image Performance

Material \_\_\_\_\_ Nominal Thickness \_\_\_\_\_ mm

FDD = \_\_\_\_\_ mm FOD = \_\_\_\_\_ mm (average)

Average Magnification = FDD/FOD = \_\_\_\_\_

Focal Spot = \_\_\_\_\_ mm × \_\_\_\_\_ mm

Digital Image Processor Settings Utilized

X1.26.1 Noise Reduction Functions

---

X1.26.2 Edge Sharpening Functions

---

X1.26.3 Contrast Manipulation Functions

---

X1.26.4 Other Functions

---

Qualification Device Used \_\_\_\_\_

Field of View	RTR		Image 1		Image 2		Image 3		Values	
	H	V	H	V	H	V	H	V	E	I
Normal Imager Mode										
Mag. 1 Imager Mode										
Mag. 2 Imager Mode										

Key to Chart

RTR = IQI Hole or Horizontal and Vertical wires observable in the Radioscopic image

Image 1 = IQI Hole or Horizontal and Vertical wires visible in the image as archived on the \_\_\_\_\_

Image 2 = IQI Hole or Horizontal and Vertical wires visible in the image as archived on the \_\_\_\_\_

Image 3 = IQI Hole or Horizontal and Vertical wires visible in the image as archived on the \_\_\_\_\_

X1.27 Key to Terms Used in the Qualification Form

Contrast Sensitivity = Minimum detectable test object thickness or density change measured along the X-ray beam and expressed as a percentage of the total X-ray beam path length in the material.

FDD = Focal Spot to Detector Distance

FOD = Focal Spot to Object Distance; Average FOD is the distance from the focal spot to the center of the test object

FS = Focal Spot Dimensions in mm

FOV = Field of view diameter or diagonal measurement in mm


Magnification = FDD/FOD

H-LP/mm = Limiting horizontal resolution as measured with a line-pair gage oriented so that the line-pairs are vertical in the image display

V-LP/mm = Limiting vertical resolution as measured with a line-pair gage oriented so that the line-pairs are horizontal in the image display

E (Energy) = The indicated X-ray tube kilovoltage or radioisotope energy

I (Intensity) = Indicated X-ray tube milliamperage, intensity in Rads/meter/minute or source strength in Curies

 **E 1411**

*The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.*

*This standard is copyrighted by ASTM, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or [service@astm.org](mailto:service@astm.org) (e-mail); or through the ASTM website ([www.astm.org](http://www.astm.org)).*