

**Therma-Stor** LLC Driven by Performance. Powered by Design.™[Home Page](#) | [Site Search](#) | [Site Map](#)[Our Company](#)[Our Brands](#)[Products](#)[How to Purchase](#)[Product Support](#)[Resources](#)[Forum](#)[Contact Us](#)

Commercial Solutions

Dehumidification

- [HI-E DRY Model 100](#)
- [HI-E DRY Model 195](#)
- [HI-E DRY Vehere](#)

Additional Information

- [Commercial Dehumidification Brochure](#)
- [Pool & Spa Humidity Control](#)
- [Water Treatment Facilities](#)

HI-E DRY 195 Dehumidifier

- *Removes 192 pints/day (80°F, 60% RH)*
- *5.9 pints/KWH efficiency (80°F, 60% RH)*
- *Uses only 12 amps*

The HI-E DRY 195 high efficiency dehumidifier is designed and built with emphasis on efficiency and durability. The HI-E DRY 195 removes 183 pints of water per day at a rate of 5.9 pints per kilowatt hour in an 80°F and 60% RH environment, while the industry average remains at only two to three pints. The high-efficiency design of the HI-E DRY 195 offers more than just dramatically reduced utility costs. The larger water removal capacity from a smaller, more efficient refrigeration system eliminates the need for 220 volt circuits in many applications. The smaller refrigeration system allows HI-E DRY 195 to cost less than other commercial dehumidifiers of equal capacity. The HI-E DRY Model 195 features a dehumidistat controller with settings from 20 to 80 percent relative humidity and a positive "on" and "off" setting. A blower switch permits continuous blower operation independent of dehumidification. The unit is portable and has four casters. The internal condensate pump is capable of lifting condensate 17 feet, and 20 feet of condensate hose is included. The unit's 6 ft. power cord plugs into a 115 volt receptacle with ground.



HI-E DRY 195 Resources

- [HI-E DRY 195 Spec Sheet](#)
- [HI-E DRY 195 Manual](#)
- [HI-E DRY 195 Warranty](#)

HI-E DRY 195 Performance and Technical Specifications

Part Number:	4030060
Power:	115 VAC, 12 amps
Kilowatts:	1.25 (80°F, 60% RH)
Blower:	540 CFM
Capacity (24 hrs.):	192 pints (80°F, 60%)
Pints/KWH:	5.9 pints/KWH (80°F, 60% RH)
Temp. Range:	33°F – 110°F
Warranty:	5 Year Limited

Product Dimensions

Width:	36.6"
Height:	42"
Depth:	19"
Weight:	175 lbs.

Shipping Dimensions

Width:	39.25"
Height:	48.75"
Depth:	30"
Weight:	214 lbs.

[Home Page](#) | [Our Company](#) | [Our Brands](#) | [Our Products](#) | [How to Purchase](#) | [Product Support](#) | [Resources](#) | [Forum](#)[Purchase Order Terms and Conditions](#) | [Site Map](#) | [Inbound LTL Carrier Guide](#) | [Site Search](#) | [Privacy Policy](#) | [Careers](#) | [Contact Us](#)

Copyright © 2016 Therma-Stor LLC