



The World Leader In Engine Exhaust Removal
Systems for the Fire and EMS Industry

PROPOSAL – AIRVAC 911® Multi-Directional (Horizontal & Vertical) Air Flow Exhaust Removal System

THE SALE OF AIRVAC 911®, ENGINE EXHAUST AIR FILTRATION SYSTEM, BY AIR VACUUM CORPORATION OF DOVER N.H., FOR REMOVAL OF HAZARDOUS EMISSIONS FROM FIRE, RESCUE, TRUCKING, AND OTHER HEAVY EQUIPMENT FLOOR AREAS.

THIS QUOTATION HAS BEEN PREPARED FOR: 9/9/2025



Bidding Agency
Saint Tammany Fire District #1 - St# 10
Lakeshore Vista Blvd
Slidell, LA 70458

SPECIFICATIONS

MODEL: AIRVAC 911®, VERTICAL AIR FLOW DESIGN, CEILING HUNG, RE-CIRCULATING AIR FILTRATION SYSTEM. MANUFACTURED BY: AIR VACUUM CORPORATION, 32 NADEAU DRIVE, ROCHESTER NH 03867.

FILTRATION: “4-STAGE” FILTER PACK. ALL FILTERS ARE INDUSTRY STANDARD SIZED, UL TESTED & CERTIFIED.

PRE-FILTER (STAGE 1): 24" X 24" X 1". 3-PLY POLYESTER CONSTRUCTION. TWO LAYERS OF 16/40 DUAL DENIER POLY FIBERS WITH A FINAL DUST CATCHING ADHESIVE LAYER. SELF-SEALING FILTER WITH PRE-INSTALLED INTERNAL HEAVY GAGE WIRE FRAME. MERV 8. PERFORMANCE BASED ON A.S.H.R.A.E. 52.1-1992 TEST METHOD. CLASSIFIED AS A UL CLASS 2 FILTER, ACCORDING TO UL STANDARD 900 AND CAN 4-S111.

MAIN MEDIA FILTER (STAGE 2): 24" X 24" X 6". “HEPA MAX 3000” HIGH EFFICIENCY PARTICULATE AIR FILTER. DOP TESTED WITH 0.3 MICROMETER SIZED PARTICLES TO HAVE A **MINIMUM EFFICIENCY OF UP TO 95% AND EXCEEDS THE MAXIMUM EFFICIENCY OF 98% ASHRAE 52.1 TESTED FILTERS.** CONSIST OF A PLEATED MEDIA PACK ENCLOSED WITHIN A GALVANIZED STEEL FRAME ASSEMBLY. ULTRA-FINE FIBERGLASS MEDIA FORMED IN A SERIES OF PLEATS SEPARATED BY CORRUGATED ALUMINUM DIVIDERS TO MAINTAIN UNIFORM SPACING BETWEEN EACH PLEAT FOR OPTIMAL AIRFLOW. CLASSIFIED CLASS 2 ACCORDING TO U.L. STANDARD 900 AND IS CLASSIFIED MERV 16 IN ACCORDANCE WITH ASHRAE STANDARD 52.2. FOR INSTALLATION SAFETY, TOTAL WEIGHT NOT TO EXCEED 16 LBS.

GAS-PHASE EXTRACTOR (STAGES 3&4): ONE 24" X 24" X 4", “MULTISORB 3000” BLENDED GAS PHASE EXTRACTOR. 50/50 RESPIRATOR GRADE ACTIVATED CARBON GRANULES EFFECT FOR REMOVAL OF HIGH WEIGHT MOLECULAR GASES WITHIN DIESEL EXHAUST (VOC’S, HYDROCARBONS, BENZENE, OCTANE, METHANOL AND MORE) AND POTASSIUM PERMANGANATE FOR REMOVAL OF LIGHT WEIGHT MOLECULAR GASES (SULFUR DIOXIDE, NITROGEN DIOXIDE, FORMALDEHYDE AND MORE). FILTER IS CONSTRUCTED WITHIN A 24ga METAL FRAME WITH INTERNAL “HONEYCOMB” CONTAINMENT STRUCTURE. 50/50 BLEND EQUATES TO 28+/- LBS OF CARBON. FOR INSTALLATION SAFETY, TOTAL WEIGHT NOT TO EXCEED 30 LBS.

CABINET CONSTRUCTION: 18 & 16 GAUGE, ALL WELDED STEEL CONSTRUCTION. 25" X 26" X 28" CUSTOM GRAY POWDER COAT PAINT FINISH. **TWO HINGED ACCESS PANELS:** ONE, TO THE FILTER BANK AND THE OTHER TO THE MOTOR/BLOWER UNIT. A “DWYER” MAGNEHELIC STATIC PRESSURE GAGE, ALLOWS USER TO VISUALLY CHECK ON THE STATUS OF THE FILTER BANK. **FOUR HORIZONTAL & ADJUSTABLE AIRFLOW GRILLS.** “QUICK LATCH” FILTER COMPARTMENT WHICH IS CAPABLE OF HOLDING UP TO 15" OF FILTRATION!

ELECTRICAL: 3/4 H.P., 1725 RPM, 115 VOLT SINGLE PHASE ELECTRIC MOTOR, 13.6 F.L. AMP., RESILIENT MOUNT, AUTOMATIC THERMAL PROTECTION. ELECTRIC MOTOR, RESILIENT MOUNT. ALL MOTORS ARE UL APPROVED. **OPTIONS:** UNITS AVAILABLE @ 230 VOLT, SINGLE PHASE, 6.8 F.L. AMP, ADD \$75 EA. UNIT, SINGLE PHASE MOTOR USABLE @ 208-230 VOLT. 7.0 F.L. AMP. ADD \$115 EA UNIT, THREE PHASE 1 HP - @ 208-230/460 Volt, 3.4-3.6/1.8 F.L. AMPS, ADD \$255 EA. UNIT; TO BASE QUOTE.

BLOWER: CONTINENTAL CENTRIFUGAL IMPELLER AND FUNNEL CONE. NON-METAL & CHEMICALLY RESISTANT.

AVEC CONTROL PANEL: UL 508 CERTIFIED CUSTOM “AUTOMATIC VEHICLE EXHAUST CONTROL”, MULTI-CIRCUIT AUTOMATIC RESET TIMER CONTROL. TWO CIRCUIT CONFIGURATIONS RATED AT 20 AMPS PER. TIMING RANGE OF .1 TO 120 MIN. ENCLOSED WITHIN A NEMA-4 RATED ENCLOSURE, NECESSARY FOR APPLICATIONS WHERE WATER IS PRESENT (WASHING OF VEHICLES). MANUAL THREE POSITION SWITCH FOR: AUTO MODE, SYSTEM OFF & SYSTEM RUN OVERRIDE. LED “OPERATING” LIGHT.

AUTOMATIC ACTIVATION SWITCHES: (SEE ENCLOSURES) PHOTO ELECTRIC EYES ACTIVATE SYSTEM UPON VEHICLE MOVEMENT (OUTDOOR RANGES OF UP TO 200’) AND MAGNETIC DOOR SWITCHES (ONE PER OVERHEAD DOOR).



The World Leader In Engine Exhaust Removal Systems for the Fire and EMS Industry

PRICE QUOTATION

Bidding Agency
 Saint Tammany Fire District #1 - St# 10
 Lakeshore Vista Blvd,
 Slidell, LA 70458

DATE: 9/9/2025
 PHONE:
 FAX:

DESCRIPTION	QUANTITY	UNIT COST	TOTALS
AIRVAC 911® EXHAUST REMOVAL SYSTEM - Single Ph. 115V	4	\$4,584.00	\$18,336.00
AIRVAC 911® FILTER PACK (4-Stage Filter Pack, "Main Filters")	4	\$515.00	\$2,060.00
AIRVAC 911® FILTER GAUGE (Min. one per building section)	1	\$154.00	\$154.00
UL 508A CERTIFIED CONTROL PANEL - AVEC-4C	1	\$1,373.00	\$1,373.00
ACTIVATION PACKAGE - E-960-D90Q PHOTO EYE (set) & N505AUTM/STX01 (2") TRACK MOUNTED DOOR SWITCH	2	\$318.00	\$636.00
PREFILTERS (12 Per Box/Change date est. indicated below)	4	\$58.00	\$232.00
*ESTIMATED SHIPPING AND HANDLING	1	\$133.00	\$133.00
	4	\$425.00	\$1,700.00
			\$24,624.00

**Non-Schedule Item"

MADE IN THE USA

- ◆ *FREIGHT: FOB Origin,* ◆ **TERMS: 1/2 Payment with the order & final payment prior to release.** ◆ *Lead-Time 10 to 16 weeks.*
- ◆ Buyer is responsible for obtaining all permits, permit fees, State/local licensing fees and applicable taxes related to the purchase of product, shipping and installation or must provide all necessary tax-exempt certificates; state, local and/or county to Air Vacuum Corporation. ◆ *Please contact your sales rep for installation information and pricing.* ◆ Governmental Purchases please consult your sales rep for GSA price list.

The AIRVAC 911™ System is Provided With a FIVE YEAR WARRANTY On ALL Components (excluding consumable filters)

SEE DIAGRAM FOR RECOMMENDED AIRVAC 911 UNIT LOCATIONS

[Approximate Filter Life Expectancy](#)

Prefilters 2-4 months, Main filters 12 to 24 months.

This quotation has been prepared By: Thomas J. Vitko Date: 9/9/2025
Quotation Prices are valid for 60 calendar days from quotation date.

