

Ordering Information

Applicable product:		
With neck jets	K-1312-N	shown
Without neck jets	K-1312-H1	not shown
Accessories/hardware:		
Jet trim kit	K-9698	required
Drain	K-7161-AF	recommended
Apron	K-1311	optional

Requirements Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 20 A, 60 Hz

Product Information

Fixture*:	basin area	top area	weight
Bathing well	47" x 26"	64" x 31"	140 lbs.
	water depth	capacity	
To overflow	15-1/2"	91 gals.	
* Approximate measurements for comparison only.			

Pump:	HP	V	Hz	A
1-speed	2	120	60	18.5

Installation Notes

Refer to installation instructions included with fixture before beginning installation. The K-1311 apron, if used, must be installed BEFORE finished flooring is laid. If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck. Pump is supplied with a grounding type plug-in cord. Locate the outlet behind the whirlpool, and within 24" of the pump.

Roughing-In Notes

Fixture dimensions are nominal and conform to tolerances in ANSI Standard Z124.1.

No change in measurements if connected with drain illustrated.

Minimum access:

Pump/control box	40" W x 15" H panel	required
------------------	---------------------	----------

