

Ordering Information

| | | |
|-------------------------|---------|-------------|
| Applicable product: | | |
| Shower & foot whirlpool | K-1579 | shown |
| Shower receptor | K-1587 | not shown |
| Accessories/hardware: | | |
| Jet trim kit | K-9696 | required |
| Drain | K-11656 | recommended |
| Wood seat | K-9713 | required |
| Plastic seat | K-9714 | required |
| Shower enclosure | varies | optional |

Requirements Electrical Service

| | |
|---|---------------------|
| Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI): | |
| Pump/control | 120 V., 15 A, 60 Hz |

Product Information

| | | | | |
|---|--------------|--------------|--------|------|
| Fixture*: | basin area | top area | weight | |
| Bathing well | 1346 x 737mm | 1397 x 787mm | 43 Kg. | |
| | water depth | capacity | | |
| To overflow | 178mm | 121 litres | | |
| * Approximate measurements for comparison only. | | | | |
| Pump: | HP | V | Hz | A |
| 1-speed | 3/4 | 120 | 60 | 10.5 |

Installation Notes

Refer to installation instructions included with fixture before beginning installation.

Pump is supplied with a grounding type plug-in cord.

| | | |
|---|-------------------------|----------|
| Roughing-In Notes | | |
| Fixture conforms to ANSI Standard Z124.1. All dimensions are nominal. | | |
| No change in measurements if connected with drain illustrated. | | |
| Minimum access panel: | | |
| Pump/control | 762mm W x 381mm H panel | required |

