

Ordering Information

Applicable product:		
Left outlet	K-1035	shown
Right outlet	K-1036	not shown
Accessories/hardware:		
Tower	K-1030	required
Alcove enclosure	K-5161	required
Drain	K-7160-TF	recommended
Taboret Rite-Temp	K-1099	recommended
Taboret Two-handle	K-1098	

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V., 20 A, 60 Hz

Product Information

Fixture*:	basin area	top area	weight	
Bathing well	1118 x 914mm	1143 x 940mm	50 Kg.	
	water depth	capacity		
To overflow	210mm	163 litres**		
*Approximate measurements for comparison only. **140 litre minimum required for BodySpa operation.				
Pump:	HP	V	Hz	A
1-speed	2	120	60	18.5

Installation Notes

Refer to installation instructions included with fixture before beginning installation.
Locate control switch within the boundaries of the enclosure. 1829mm cable is included.
Allow 2121mm to 2134mm from sub-floor to finished ceiling or header for proper enclosure installation.
Top of unit must be enclosed to retain heat and contain water spray.
Pump is supplied with a grounding type plug-in cord. Locate the outlet behind the bath, and within 610mm of the pump.

