

Ordering Information

| | | |
|-----------------------|-----------|-------------|
| Applicable product: | | |
| Pump on left | K-1368-H | shown |
| Pump on right | K-1369-H | not shown |
| Accessories/hardware: | | |
| Jet trim kit | K-9696 | required |
| Drain | K-7161-AF | recommended |
| Removable pillow | K-1491 | optional |

Required Electrical Service

| | |
|---|---------------------|
| Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI): | |
| Pump/control | 120 V., 20 A, 60 Hz |

Product Information

| Fixture*: | basin area | top area | weight |
|--------------|-------------|-----------|----------|
| Bathing well | 48" x 29" | 66" x 36" | 160 lbs. |
| | water depth | capacity | |
| To overflow | 18" | 118 gal. | |

* Approximate measurements for comparison only.

| Pump: | high HP | low HP | V | Hz | A |
|---------|---------|--------|-----|----|------|
| 2-speed | 1 | 1/8 | 120 | 60 | 16.5 |

Installation Notes

Refer to installation instructions included with fixture before beginning installation.

Pump is supplied with a grounding-type plug-in cord. Locate the outlet behind the whirlpool, and within 24" of the pump.

| Roughing-In Notes | | |
|---|---------------|----------|
| Fixture conforms to ANSI Standard Z124.1. All dimensions are nominal. | | |
| Cut-out | 70-1/2" x 40" | |
| No change in measurements if connected with drain illustrated. | | |
| Minimum access panel: | | |
| Pump/control | 40" W x 15" H | required |

