

## Ordering Information

Accessories/hardware:		
Jet trim kit	K-9661	required
Transfer valve trim*	varies	required
Handshower*	varies	required
Faucet trim kit*	varies	required
Drain	K-7167	recommended

\*See specification sheet or price book for required accessories.

## Required Electrical Service

Two separate dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control, (waterfall)	120 V., 20 A, 60 Hz
Pump/control, (jets)	120 V., 20 A, 60 Hz

## Product Information

Fixture*:	basin area	top area	weight
Bathing well	1549 x 1168mm	1727 x 1473mm	109 Kg.
	water depth	capacity	
To overflow	508mm	814 litres	

\* Approximate measurements for comparison only.

## Product Information Cont.

Pump: (Qty. 2)	HP	V	Hz	A
1-speed	2	120	60	18.5

Included Components:	
Cutout template	85899-7

## Installation Notes

Refer to installation instructions included with fixture before beginning installation.

**NOTICE:** Unless otherwise specified, floor support under Riverbath must provide for a minimum of 36 Kg./square foot loading.

Pumps are supplied with grounding-type plug-in cords. Locate the outlets behind the RiverBath, and within 610mm of the pumps. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck other than that supplied.

Two 227 litre (454 litre total) water heaters are necessary to fill RiverBath.

## Roughing-In Notes

Fixture conforms to ANSI Standard Z124.1. All dimensions are nominal.

No change in measurements if connected with drain illustrated.

Cut-out	1867mm D.
Minimum access panel:	
Pump/control	1219mm W x 457mm H required

