

### Ordering Information

Applicable product:		
With neck jets	K-1466-N	shown
Without neck jets	K-1466-H1	not shown
Accessories/hardware:		
Jet trim kit	K-9696	required
Faucet trim kit	varies	required
Autofill mixer handle	varies	required
Grip rail kit	K-9596	required
Vinyl tiling-in bead*	K-1179	optional
*Use K-1179 vinyl bead when wall material contacts any top surface of bath		

### Required Electrical Service

Circuits protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 20 A, 60 Hz (dedicated)
Autofill system	120 V, 15 A, 60 Hz

### Product Information

Fixture*:	basin area	top area	weight
Bathing well	48" x 29"	66" x 36"	175 lbs.
	water depth	capacity	
To overflow	18"	118 gals.	

\* Approximate measurements for comparison only.

Pump:	HP	V	Hz	A
1-speed	2	120	60	18.5

### Installation Notes

Refer to installation instructions included with fixture before beginning installation.

Pump is supplied with a grounding-type plug-in cord. Locate the outlet behind the whirlpool, and within 610mm of the pump.

### Roughing-In Notes

Fixture conforms to ANSI Standard Z124.1. All dimensions are nominal.

Cut-out 1791 x 1016mm

No change in measurements if connected with drain illustrated.

Minimum access panel:

Pump/control	1016mm W x 381mm H panel	required
Autofill	368mm W x 305mm H panel	required

### SUPPLY DETAIL

