







LIGHTING FIXTURE SCHEDULE

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
Ⓡ	5" IC RATED, RECESSED CAN LIGHT; WHITE TRIM W/BLACK BAFFLE BY JUNO; SATCO S9148 LED LAMP	⎓	FLUSH MOUNT FLUORESCENT CEILING LIGHT; MINKA LAYERY 1010-44-PL
⊕ A	WALL SCONCE; BEVOLO GOVERNOR LATERN; H=30"		
⊕ B	WALL SCONCE; TT SINGLE SCONCE; ITEM SL 2860PN		5 BLADE, ANTIQUE WHITE, CEILING FAN W/O LIGHT FIXTURE; QUORUM MODEL 77525-67
	HEAT, VENT, LIGHT; BROAN MODEL 100HL		FLOOD LIGHTS, RAB LIGHTING MODEL QB2A

MEP SYMBOLS

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
\$	SINGLE SWITCH, 42" A.F.F.		220 V OUTLET
\$ ¹	SINGLE SWITCH, 42" A.F.F., AUTO. TURN ON W/ DOOR		GROUND FAULT INTERRUPTED OUTLET, WEATHER PROOF
\$ ²	3-WAY SWITCH, 42" A.F.F.		
\$ ³	4-WAY SWITCH, 42" A.F.F.	HFB	HOSE BIB
\$ ⁴	DIMMER SWITCH, 42" A.F.F.		CABLE OUTLET, 18" A.F.F.
\$ ⁵	AUTOMATIC DOOR SWITCH		TELEPHONE, 18" A.F.F.
⊕	DUPLEX OUTLET, 18" A.F.F.	Ⓢ	SMOKE DETECTOR
⊕ ⁴⁴	DUPLEX OUTLET, DIST. A.F.F.		
⊕ ⁵⁷ ⊕ ⁴⁴	GROUND FAULT INTERRUPTED OUTLET, DIST. A.F.F.		
—	GAS LOCATION		