



**Features:**

- Connects with and stores a complete access control and configuration database for one controlled door and 44,000 cardholders
- 255 configurable priorities for supervised inputs/alarms
- Compatible reader protocols includes all Wiegand or HID formats up to 128 bits
- Incorporates the HID OPIN® Technology TCP/IP API with an available Windows DLL tool
- Enables IP-based, two-way communication with iCLASS reader/writer, LCD keypad, and biometric reader products
- Built-in 802.3af Power over Ethernet (PoE), with 700 mA available for external field devices
- Accepts local connection option via laptop for diagnostics and configuration
- Connects to host on the IP network
- Controls and powers all access devices at the door
- Buffers up to 5,000 transactions if communication is disrupted with host and uploads when network communications are restored
- Controls and reports any passback (hard/soft/med)
- UL® 294 Listed — EdgePlus 82000B is UL® 294 listed for use with all Listed HID Global models: iCLASS, HID Prox, Indala Prox, bioCLASS, SmartID, SmartTRANS, and Mag Stripe series, up to 128-bit formats. EdgePlus is UL listed for installation within the protected area; attached remote Readers may be located outside the protected area.

**IP INTELLIGENCE AT THE DOOR INCORPORATING ANY READER IN A HOST SYSTEM • 82000B**

- **True Flexibility** — Provides network connectivity for any existing or new Wiegand or compatible HID Clock-and-Data readers.
- **Real Cost Savings** — Network access is CAT-5 for communications and Power over Ethernet (PoE). Eliminates the need for separate power supplies and controllers.
- **Established Open Architecture** — Built on the HID OPIN® platform and managed from a host application. Ideally suited for today’s IT-centric security environments.

The HID EdgePlus® IP Access Solution puts control and host interface right at the door. The EdgePlus E400 is a true IP access solution that manages up to 44,000 cardholders or credentials in complete and full-featured host systems. And an EdgePlus can be placed anywhere at the door to address all security requirements. A fully integrated processor right at the door that’s an ideal solution for retrofits or new installations, EdgePlus requires

less wiring and uses standard CAT-5 or 6 cabling for both data and power.

With a separately connected reader, EdgePlus is a perfect solution for migrating existing reader installations to the “edge” of the network. Whether the enterprise is iCLASS®, Prox, FlexSmart®, FlexPass®, MIFARE®/DESFire®, CRESCENDO™, or Wiegand output reader, EdgePlus delivers Intelligence at the Door.

**Mounting:**

Mount to a single-gang style electrical box with two screws. The EdgePlus® includes tamper protection for this type of installation to secure all wiring within the electrical box. For indoor mounting only.

**Non-latching wet/dry relay outputs for:**

- 1 door strike
- 1 auxiliary device: door held/forced alarm, alarm shunt, host offline (comms down), or general purpose

**Easily Interfaced:**

- RJ-45 connector for Ethernet TCP/IP
- Quick-disconnect screw terminal connectors
- External System Link capability enables direct integration with other security and building systems via TCP/IP, or HTTP.

**Inputs for:**

- 1 reader
- 1 door monitor switch
- 1 Request-to-Exit switch
- AC Fail Monitor\*
- Battery Fail Monitor\*
- Enclosure Tamper

\*Can be configured as a general purpose input

**SPECIFICATIONS**



<b>Mounting</b>	Single-gang style electrical box
<b>Dimensions</b>	3.3" W x 4.8" H x 1.5" D (83.8 mm x 121.9 mm x 36.3 mm)
<b>Weight</b>	6.8 oz (.195 kg)
<b>Style</b>	Attractive UL94 polycarbonate enclosure protects components from damage and all connections are fully identified by silk-screened nomenclature
<b>Card Data Formats</b>	Supports any card data format up to 128 bits
<b>Hardware</b>	32-bit RISC CPU, 100 MHz processor
<b>Memory</b>	8 MB onboard Flash memory, 32 MB SDRAM, 256K SRAM
<b>Visual Indicators</b>	Two LEDs indicate power/network activity and device I/O activity.
<b>Power Supply Requirements</b>	1A @ 12-16 VDC maximum <b>Recommended:</b> Power is supplied using the Power over Ethernet technology available with PoE (802.3af) enabled network devices. <b>Alternate:</b> Supervised linear power supply with battery backup, input surge protection, and AC Fail and battery low contact outputs. <b>Relays can be configured to supply power as follows:</b> <b>Available Power:</b> The E400 is capable of supplying a total of 700 mA to field devices. This power may be shared between a reader and one or two additional field devices. Unpowered, relay contacts are rated for 2A @ 30 VDC <b>Note:</b> Use of a Listed Access Control/Burglary power-limited power supply is required for all Listed installations.

**THE EDGEREADER IS INTENDED FOR USE IN INDOOR ENVIRONMENTS THAT COMPLY WITH THE FOLLOWING SPECIFICATIONS:**

<b>Operating Temperature</b>	32° to 122° F (0° to 50° C)
<b>Operating Humidity</b>	5% to 95% relative, non-condensing
<b>Communication Ports</b>	<b>Ethernet</b> – 10 or 100 Mbps;
<b>Certifications</b>	UL® 294 Listed Component, CSA 205 for Canada, FCC Class A Verification, ICES-003 Class A Canada, EU (CE Marking), Australia (C-Tick Mark), New Zealand
<b>Warranty</b>	Warranted against defects in materials and workmanship for 18 months (see complete warranty policy for details).

**CABLE SPECIFICATIONS**

<b>Ethernet</b>	300 feet (100 m) Category 5 cable	ALPHA 9504C ALPHA 9405F
<b>Wiegand</b>	500 feet (150 m) 9-conductor, stranded, overall shield 22 AWG	ALPHA 1299C
<b>Input Circuits</b>	500 feet (150 m) 2-conductor, shielded 22 AWG, 18 AWG	ALPHA 1292C ALPHA 2421C
<b>Output Circuits</b>	500 feet (150 m) 2-conductor 22 AWG 18 AWG	ALPHA 1172C ALPHA 1897C

Minimum wire gauge depends on cable length and current requirements.

North America: +1 949 732 2000  
 Toll Free: 1 800 237 7769  
 Europe, Middle East, Africa: +49 6123 791 0  
 Asia Pacific: +852 3160 9800  
 Latin America: +52 477 779 1492

**ASSA ABLOY**  
 An ASSA ABLOY Group brand

© 2011 HID Global Corporation. All rights reserved. HID, the HID logo, Crescendo, naviGO, HID on the Desktop, and iCLASS are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.  
 2011-11-11-edge-edgeplus-e400-reader-ds-en