



96" tall Chainlink Fabric with Knuckle/Barb Salvage and 2" Mesh Size.

135" tall, 3 1/2" diameter Terminal Post with 12" post footing diameter and 36" post footing depth with 6" concrete slab on top. Terminal Post shall be ASTM F1043 SC.1; 40; ASTM F1083 Regular Grade 30K psi yield.

135" tall, 2 7/8" diameter Line Post with 12" post footing diameter and 36" post footing depth with 6" concrete slab on top. Line Post shall be ASTM F1043 SCH 40; ASTM F1083 Regular Grade 30K psi yield.

Top Fence has 1 5/8" diameter Top Rail.

Bottom of Fence has 1 5/8" diameter Bottom Rail.

Fence is braced with 1 - 1 5/8" diameter Middle Rail.

Fence contains Vertical Slats.

Line Post Spacing: 120"

The Wire Spacing is every 24" on Rails.

Rails are attached with Boulevard Clamp.



3,000 PSI CONCRETE  
SLAB MINIMUM 6" THICK.



ARROW FENCE CO. DIV. OF NU-ARROW IND.

2445 Aberdeen St.  
KENNER, LA 70062  
(504) 467-6467

SLVHCS  
LA

96" Chainlink Line of Fence

Drawn: 1/30/2015

File:

*[Handwritten signature]*

