

480V

**PRODUCT SPECIFICATIONS**

MODEL	GAM2A0C60S51SE
RATED VOLTS/PH/Hz.	208-230/1/60
RATINGS ①	See O.D. Specifications
INDOOR COIL — Type	Plate Fin
Rows — F.P.I.	4 - 14
Face Area (sq. ft.)	5.50
Tube Size (in.)	3/8
Refrigerant Control	TXV
Drain Conn. Size (in.) ②	3/4 NPT
DUCT CONNECTIONS	See Outline Drawing
INDOOR FAN — Type	Centrifugal
Diameter-Width (In.)	11 X 10
No. Used	1
Drive - No. Speeds	Direct - 5 ③
CFM vs. in. w.g.	See Fan Performance Table
No. Motors — H.P.	1 - 1
Motor Speed R.P.M.	1050
Volts/Ph/Hz	208-230/1/60
F.L. Amps - L.R. Amps	7.6
FILTER	No
Filter Furnished?	No
Type Recommended	Throwaway
No.-Size-Thickness	1 - 22 X 20 - 1 In.
REFRIGERANT	R-410A
Ref. Line Connections	Brazed
Coupling or Conn. Size — in. Gas	7/8
Coupling or Conn. Size — in. Lq.	3/8
DIMENSIONS	H x W x D
Crated (In.)	62-13/16 x 25-1/2 x 24-1/2
Unrated	61-23/32 x 23-1/2 x 21-13/16
WEIGHT	
Shipping (Lbs.)/Net (Lbs.)	171/159

① These Air Handlers are A.H.R.I. certified with various Split System Air Conditioners and Heat Pumps (A.H.R.I. STANDARD 210/240). Refer to the Split System Outdoor Unit Product Data Guide for performance data.

② 3/4" MALE Plastic Pipe (Ref.: ASTM 1785-78)

③ Constant torque motor

Note: 14th digit may be A-E



Intertek



Heater	Minimum Air Speed Tap	
	With Heat Pump	Without Heat Pump
BAYEAAC04BK1AA BAYEAAC04LG1AA	Tap 2	Tap 2
BAYEAAC05BK1AA BAYEAAC05LG1AA	Tap 2	Tap 2
BAYEAAC08BK1AA BAYEAAC08LG1AA	Tap 5	Tap 2
BAYEAAC10BK1AA BAYEAAC10LG1AA	Tap 3	Tap 2
BAYEAAC10LG3AA	Tap 1	Tap 1
BAYEABC16BK1AA	Tap 4	Tap 3
BAYEABC15LG3AA	Tap 1	Tap 1
BAYEABC20BK1AA	Tap 4	Tap 3
BAYEACC20BK1AA	Tap 5	Tap 4

SEE AIR HANDLER NAMEPLATE OR PRODUCT DATA FOR EXCEPTIONS

Note: Heating and cooling speeds are the same, factory set at Speed Tap #2.