

Ordering Information

Applicable product:		
With neck jets	K-1466-N	shown
Without neck jets	K-1466-H1	not shown
Accessories/hardware:		
Jet trim kit	K-9696	required
Faucet trim kit	varies	required
Autofill mixer handle	varies	required
Grip rail kit	K-9596	required
Vinyl tiling-in bead*	K-1179	optional
*Use K-1179 vinyl bead when wall material contacts any top surface of bath		

Required Electrical Service

Circuits protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 20 A, 60 Hz (dedicated)
Autofill system	120 V, 15 A, 60 Hz

Roughing-In Notes

Fixture conforms to ANSI Standard Z124.1. All dimensions are nominal.	
Cut-out	70-1/2" x 40"
No change in measurements if connected with drain illustrated.	
Minimum access:	
Pump/control	40" W x 15" H panel required
Autofill	14-1/2" W x 12" H required

Product Information

Fixture*:	basin area	top area	weight	
Bathing well	48" x 29"	66" x 36"	175 lbs.	
	water depth	capacity		
To overflow	18"	118 gals.		
* Approximate measurements for comparison only.				
Pump:	HP	V	Hz	A
1-speed	2	120	60	18.5

Installation Notes

Refer to installation instructions included with fixture before beginning installation.

Pump is supplied with a grounding-type plug-in cord. Locate the outlet behind the whirlpool, and within 24" of the pump.

SUPPLY DETAIL

