

Ordering Information

Applicable product:		
With neck jets**	K-870-N	shown
Without neck jets**	K-870-H1	not shown
With neck jets	K-872-N	not shown
Without neck jets	K-872-H1	not shown
Accessories/hardware:		
Jet trim kit	K-9695	required
Seawall faucet**	varies	required
Drain	K-7166	recommended
Undermount installation kit (K-872 only)	K-580	optional
Vinyl tiling-in bead*	K-1179	optional
*Use K-1179 vinyl bead when wall material contacts any top surface of bath.		
**K-870-H1, K-870-N predrilled for Seawall faucets.		

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V., 20 A, 60 Hz

Product Information

Fixture*:	basin area	top area	weight
Bathing well	1194 x 635mm	1676 x 914mm	220 Kg.
	water depth	capacity	
To overflow	419mm	416 litres	

* Approximate measurements for comparison only.

Pump:	HP	V	Hz	A
1-speed	2	120	60	18.5

Installation Notes

Refer to installation instructions included with fixture before beginning installation.

Pump is supplied with a grounding type plug-in cord. Locate the outlet behind the whirlpool, and within 610mm of the pump.

Roughing-In Notes

Fixture dimensions are nominal and conform to tolerances in ANSI Standard A112.19.1.

Deck width must be 51mm min. to allow clearance for fittings. See faucet roughing-in requirements.

No change in measurements if connected with drain illustrated.

Cut-out for drop-in: 1791 x 1029mm

Cut-out for undermount: K-580 template required

Minimum access panel:

Pump/control: 864mm W x 381mm H panel required

