

LINTEL SCHEDULE

STRUCTURE PROPERTIES		L SHAPED ANGLE IRON PROPERTIES				R.M.K.S
H'	FRAMED OPENING	W'	L'	THICKNESS		
All	36"	3 1/2"	3"	1/4"		
All	48"	3 1/2"	3"	1/4"		
2ft	60"	3 1/2"	3"	1/4"		
2ft	72"	3 1/2"	3"	1/4"		
2ft	96"	5 1/2"	4"	1/4"	#1	
2ft	120"	5 1/2"	5"	3/8"	#1	
2ft	120"	5 1/2"	6"	5/16"	#1	
4ft & Higher	60"	3 1/2"	3"	1/4"		
4ft & Higher	72"	3 1/2"	3"	1/4"		
4ft & Higher	96"	5 1/2"	5"	5/16"	#1	
4ft & Higher	96"	5 1/2"	6"	5/16"	#1	
4ft	120"	5 1/2"	6"	1/16"	#1	
4ft	120"	5 1/2"	7"	3/8"	#1	
5ft & Higher	120"	5 1/2"	6"	1/2"	#1	
5ft & Higher	120"	5 1/2"	7"	3/8"	#1	

#1 - L SHAPED ANGLE IRON MUST BE PINNED AT EACH END & MIDSPAN TO STRUCTURE FRAMING TO COUNTERACT ROTATION.

GENERAL NOTE: ALL L SHAPED ANGLE IRON ARE TO BE GRADE A36 OR BETTER.

