

Ordering Information

Applicable product:		
Drop-in rim style	K-1244	shown
Integral flange	K-1244-F	not shown
Accessories/hardware:		
Jet trim kit	K-9695	optional
Drain	K-7161-AF	recommended
Apron	K-1243	optional
Vinyl tiling-in bead*	K-1179	optional
*Use K-1179 vinyl bead when wall material contacts any top surface of bath.		

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V., 15 A, 60 Hz

Product Information

Fixture*:	basin area	top area	weight
Bathing well	1270 x 1067mm	1524 x 1168mm	53 Kg.
	water depth	capacity	
To overflow	368mm	386 litres	
* Approximate measurements for comparison only.			
Pump:	HP	V	Hz
1-speed	3/4	120	60
Included Components:			
Cutout template			113925-7

Installation Notes

Refer to installation instructions included with fixture before beginning installation.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Pump is supplied with a grounding-type plug-in cord. Locate the outlet behind the whirlpool, and within 610mm of the pump. The apron must be installed before the finish floor and wall materials are installed.

